AREA NAME . AR	REA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles 53	30	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8501

		SIMULATOR SOLUTION (OR DRY GAS)**	NC	P TEM	PAS PAS ACCURACY CALIBRATION TEMP (°C) CHECK RESULTS' REQUIRED						1				
DATE TI	TEMI ME (°C)	LOT NO.	VALUE	TEST #1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO	REPAIRS/PROBLE!		
/11/2013		12B27-13-5-10-	.100	_	N)O	TIN	CACK	ine			Flick	15063	Printer B.O.		
		KKF24C													
		Prepared by:													
		Douglas C. Talbot					-								
		02-27-2012													
		Expires on:													
		02-27-2014													
											,				
				-											
				_											
								_							
		700000000000000000000000000000000000000	-	*			-								
													_		

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110). If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STÂTE OF CALÎFORNIA DEPARTMENT OF CALIFORNIA HIGHWAY PATROL PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	L NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		18785

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	ON.	P TEM	AS ≧ (°C)	PAS AC CHECK F	CURACY RESULTS*	CALIBI REQL	RATION JIRED					
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST #1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR:	I.D. NO.	REPAIRS/PROBLEM COMMENTS	
0/11/2013	1153	34	12B27-13-5-10-	.100	20		:101			8		Flick	15063	Printer B.O.	
			KKF24C												
					1	,									
										:					
			Prepared by:							,	*************				
			Douglas C. Talbot												
			02-27-2012												
			Expires on:												
			02-27-2014						_						
								_		-					
			THE PERSON NAMED IN COLUMN TO THE PE												
					~~~			_						_	
								_							
													<del> </del>		

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

# STATE OF CALIFORNIA DEPARTMENT OF CALIFORNIA HIGHWAY PATROL PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG CHP 202K (Rev. 8-08) OPI 051

							~
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL		1-511
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		85	16

DATE TIME (°C) LOT NO. VALUE TEST #1 (Optional) TEST #1 (Optional) YES NO RESULTS OPERATOR: 1.D. NO.	PAIRS/PROBLEMS/ COMMENTS er B.O.
TEMP	COMMENTS
TEMP   TIME (°C)   LOT NO.   VALUE   TEST #2   (Optional)   TEST #1 (Optional)   YES   NO   RESULTS   OPERATOR   LD. NO.   10/11/2013   1/47   34   12B27-13-5-10-   .100   2/	COMMENTS
10/11/2013 1/47 34 12B27-13-5-10100 2/ 101 × Flick 15063 Print	A CONTRACTOR OF THE CONTRACTOR
	er B.O.
KKF24C	
	-
Prepared by:	
Douglas C. Talbot	
02-27-2012	
Expires on:	
02-27-2014	
	·

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

3

AREA NAME AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO.		_
South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV	3559	

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

		SIMULATOR SOLUTION (OR DRY GAS)**	SANDA STATE	P	AS P (°C)	PAS ACC	CURACY	CALIBRAT REQUIRE	ION			
DATE TIME	TEMF (°C)		VALUE		TEST #2 (Optional)		TEST #2 (Optional)		PA RETE IO RESU	ST	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/11/2013 1/56	34	12B27-13-5-10-	.100	20		,102			X	Flick	15063	Printer B.O.
		KKF24C										
		D 1 h										
		Prepared by:							-			
	_	Douglas C. Talbot 02-27-2012										
	_	Expires on:					~					
		02-27-2014									<del>                                     </del>	
	-	02-27-2014										
	-										1	
			,									
			***************************************									
								1				
				*								
* If the reading is w		us or minus (+) 0.010 perce										

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	AL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		8580

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS. WHICHEVER OCCURS FIRST

	r	ASD	EVICES SHALL BE C		a construction of the con-	umanisti maman		****************	a concension of the same	(C)-40 (E)(C)-40 (E)(C)	U IESIS, WHIC	HEVERO	CURS F	RSI.
			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TFMI	AS P. (°C)	PAS AC	CURACY RESULTS*	CALIBR REQU	ATION				
	100000		100			1					PAS			12.5
DATE	TIME	TEMF (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST O	PERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/11/2013	1155	34	12B27-13-5-10-	.100	20	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	103			9	Flick		15063	Printer B.O.
	<del>/////</del>	7	KKF24C				100							
												-		
			Prepared by:		,									
			Douglas C. Talbot				Pot							
			02-27-2012											
***************************************			Expires on:											
			02-27-2014											
								_						
***************************************		<del></del>						×						
													1	
													-	
								ore						
	· · · · · · · · · · · · · · · · · · ·													-
	,		(,, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,											
					,									
				-										
		11 1		. 64				111				1.4		

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	1
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8	3032

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

tile Visit of the second	130 M 130 M 140 M	SIMULATOR SOLUTION (OR DRY GAS)**				AS P (°C)	PAS AC CHECK!	CURACY RESULTS*	CALIBI REQL	RATION JIRED	PAS		
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST #1	TEST #2- (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST OPERATOR	I.D. NO	REPAIRS/PROBLEMS COMMENTS
10/11/2013	1147	34	12B27-13-5-10-	.100	20		-101			D	Flick	15063	Printer B.O.
	** * /	,	KKF24C							/			
				www.									
			Prepared by:										
			Douglas C. Talbot										
			02-27-2012										
			Expires on:										
			02-27-2014										
								1					
	٠												
					-								
									_				
					,					_			
										-	2000		_

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

S

AREA NAME .	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	· / / - /-
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		X620

		SIMULATOR SOLUTION (OR DRY GAS)**			PAS PAS ACCURACY CALIBRATION REQUIRED					1000					
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR		I,D, NO.	REPAIRS/PROBLEM COMMENTS
10/11/2013	1213	34	12B27-13-5-10-	.100	20		a 101			X		Flick		15063	Printer B.O.
1			KKF24C							/					
													L		
			Prepared by:												
			Douglas C. Talbot												
			02-27-2012					•							
			Expires on:												
			02-27-2014												
			awa w												
		,	901170000000000000000000000000000000000												
									_				Ш		
													Ш		
													Ш		
													Ш		
													$\sqcup$		
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,								_				Ш		
													$\sqcup$		
													$\square$		
													$\sqcup$		
													$\sqcup$		·

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

			<del></del>			
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	L NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		82957
						-

	PAS DEVICES SHALL BE CHECKED FOR ACCURACT EVERT 10 DATS OR EVERT 150 TESTS, WHICHEVER OCCURS FIRST.													
			SIMULATOR SOLUTION	ON.	P	AS .	PASAC	CURACY	CALIB	RATION				
			(OR DRY GAS)**		TEM	P (°C)	CHECK	RESULTS*	REQU	JIRED				
		TEMP	2000000			TEST#2		TEST#2			PAS RETEST		1	REPAIRS/PROBLEMS/
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	(Optional)	TEST#1	(Optional)	YES	NO	RESULTS	OPERATOR	I.D. NÓ.	COMMENTS
10/11/2013	102	*********		.100	21		,098	7		~		Flick	15063	Printer B.O.
10/11/2015	10410	4	KKF24C		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	<u> </u>	1010							
			KKI 24C										-	
									ļ				-	
							<del> </del>							
							1							
			Prepared by:						_					
			Douglas C. Talbot											
			02-27-2012										_	
			Expires on:											
			02-27-2014							`				
								L						
													1	
					,								<u> </u>	
			The state of the s											
								2200					-	
									_					
			•											

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL N	Ю.			
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		7	257	2	5

	٢	AS D	EVICES SHALL BE C	HECKED	FUR ACC	JURACY	EVERY 1	UDAYS	UK EV	ERY 1	50 1ES 1S	, WHICHEVER O	CCURS	-IK3I.
140			SIMULATOR SOLUTION	ON,	P	AS	PAS AC	CURACY	CALIBI	RATION				
and the second			(OR DRY GAS)**		TEM	P (°C)	CHECK	RESULTS*	REQ	JIRED	DAG	100		1000
40.000		TEMP				TEST #2		TEST#2			PAS RETEST			REPAIRS/PROBLEMS/
DATE	TIME	(°C)	LOT NO.	VALUE	TEST#1	(Optional)	TEST#1	(Optional)	YES	NO	RESULTS	OPERATOR	I.D. NO	. COMMENTS
10/11/2013	1225	34	12B27-13-5-10-	.100	21		.099			10		Flick	15063	Printer B.O.
			KKF24C				10011			1				
	_		Prepared by:							_	<u> </u>			-
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
			N 174											
								<del>-</del>						
			AT AGOV											
													-	
		<del></del>											-	
													-	

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	AL NO.	7	_
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		77	14	79

h i		SIMULATOR SOLUTION (OR DRY GAS)**			P TEMI	AS ? (°C)	PAS AC	CURACY RESULTS:	CALIBI	RATION JIRED	4.0		10000000000000000000000000000000000000
DATE	TIME	TEMP	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST #1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS OPERATOR	I.D. NO.	REPAIRS/PROBLEI COMMENTS
0/11/2013	1230	34	12B27-13-5-10-	.100	20		09			2	Flick	15063	Printer B.O.
		- /	KKF24C							/			
					-								
			Prepared by:		ļ								
			Douglas C. Talbot										_
			02-27-2012					4			100		
			Expires on:										
			02-27-2014										
					*			_					
					-							+	

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	L NO.		_
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		8	70°	7
								,

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**		PAS PAS ACCURACY CALIBRATION REQUIRED						PAS RETEST			
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST #1	TEST #2 (Optional	) TEST#1	TEST #2 (Optional)	YES	NO	RETEST OPERATO	R	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/11/2013	1244	34	12B27-13-5-10-	.100	$\varnothing$		0/06			P	Flick		15063	Printer B.O.
	. ,		KKF24C		`									
				***************************************										
			Prepared by:											
			Douglas C. Talbot						,					
			02-27-2012											
			Expires on:											
			02-27-2014											
														_
									-					
	THE STATE OF THE S													
	energe en													
												$\perp \downarrow \downarrow$		
					,									
												$\dashv$		
						POLICE CONTRACTOR OF THE PROPERTY OF THE PROPE						$\dashv$		
T. T. (1)														

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

Chp202K_1108.pdf

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

•	•
CTATE OF	CALIFORNIA
SIMILEOR	CALIFORNIA
DEBARTA	ENT OF CALIFORNIA HIGHWAY PATROL

AREA NAME AREA NO. COORDINATOR NAME PAS MAKE/MODEL PAS SERIAL NO. I.D. NUMBER South Los Angeles 530 15063 Officer Brian Flick Intoximeters Inc./Alco-Sensor IV

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

SIMULATOR SOLUTION				P	AS .	PASAC	CALIBRATION REQUIRED			, WIIGHEVER G		10 mg 1 mg	
DATE	TEMP	(OR DRY GAS)** LOT NO.	VALUE	1936	TEST#2 (Optional)		TEST #2 (Optional)		140.04	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
10/11/2013		12B27-13-5-10-	.100		NOT	200	COCIU	-72			Flick	15063	Printer B.O.
,		KKF24C											
		Prepared by:											
		Douglas C. Talbot							,				
		02-27-2012										_	
		Expires on:											
		02-27-2014											
												ļ	
													1840
			**									-	
								<u> </u>				-	
												-	
				·····									
		330000											

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERI	AL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		8888

		A2 D	EVICES SHALL BE C	HECKED	FOR ACC	JURACY	EVERY	UDAYS	OK EV	ERYT	50 IES IS	, WHICHEVER O	CCURS F	IRSI.
			SIMULATOR SOLUTION	ON.	P	AS	PAS AC	CURACY		RATION		76		
			(OR DRY GAS)**		TEM	P (%C)	CHECK F	ESULTS*	REQ	JIRED	PAS		4-4	mers
		TEMP				TEST#2		TEST #2			RETEST			REPAIRS/PROBLEMS/
DATE	TIME	(°C)	LOT NO.	VALUE	TEST #1	(Optional)	TEST#1	(Optional)	YES	NO	RESULTS	OPERATOR	I.D. NO.	COMMENTS
10/11/2013	1231	34	12B27-13-5-10-	.100	21		POZ			X		Flick	15063	Printer B.O.
			KKF24C							<u></u>				
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012				l .							
			Expires on:											
			02-27-2014											

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERI	AL NO.		_
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		8/2	53	
						*		

	SIMULATOR SOLUTION (OR DRY GAS)**				PAS PAS ACCURACY CALIBRATION REQUIRED PAS								
DATE TIME	TEMP (°C)	LOT NO:	VALUE	TEST #1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEM COMMENTS
0/11/2013 1243	34	12B27-13-5-10-	.100	20		p101			Ø		Flick	15063	Printer B.O.
	/	KKF24C				P1							
	ļ					<u> </u>							
		Prepared by:											
		Douglas C. Talbot				ļ							
		02-27-2012											
		Expires on:											
		02-27-2014											
		•											
							TO THE PROPERTY						
									•				
				,									
					1								

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

AREA NAME COORDINATOR NAME AREA NO. I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO. South Los Angeles 530 15063 Officer Brian Flick Intoximeters Inc./Alco-Sensor IV

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

DATE TIME ('C) LOT NO.					P TEMI	CHECK	CURACY RESULTS* TEST#2	CALIBR	JIRED	PAS RETEST		Turk,	REPAIRS/PROBLEM	
	STATE OF THE PARTY	A STATE OF THE PARTY OF THE PAR		VALUE	TEST #1	(Optional)		(Optional)	YES	NO	RESULTS	112	I.D. NO.	and the second of the second o
.0/11/2013	1252	57	12B27-13-5-10-	.100	20		1096			P		Flick	15063	Printer B.O.
			KKF24C									,		
							1				1			
						_	~ ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~							
			Prepared by:					***************************************						
			Douglas C. Talbot											
			02-27-2012				<u> </u>							
			Expires on:											
			02-27-2014											
			•								***************************************			
											, manus			
				<u>,,</u>										
			7740											
														WATER CO.
														48-14-14-1
			or minus (+) 0.010 percer											

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

CHP 202K (Rev. 8-08) OPI 051

	TO STATE OF THE ST							
				O C C C C C C C C C C C C C C C C C C C				
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERI	AL NO.	.`	•
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		1868	4	
							,	

		SIMULATOR SOLUTION (OR DRY GAS)**  TEMP (*C) LOT NO. VALUE			PAS PAS ACCURACY CALIBRATION CHECK RESULTS: REQUIRED  TEST #2 TEST #2  TEST #1 (Optional) TEST #1 (Optional) YES NO					UIRED	PAS RETEST		REPAIRS/PROBLEMS/ COMMENTS		
10/11/2013	TIME	74	12B27-13-5-10-	.100	22 22	(Optional)	0./0Z		YES	NO W	RESULTS	OPERATOR Flick	I.D. NO. 15063	Printer B.O.	
10/11/2013	(x)_/_	17/	KKF24C	.100	24		0.102	-				THEK	15005	Timer B.O.	
										_				- CANADASSA AND AND AND AND AND AND AND AND AND AN	
			Prepared by:												
			Douglas C. Talbot												
			02-27-2012												
*			Expires on:												
·		~	02-27-2014												
								work							
	`							www.			*				
				38794046							**				
			,					***************************************							
									_					*	
			,												
**************************************															
				<del></del>											
					¥					_					

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG CHP 202K (Rev. 8-08) OPI 051

										_
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	L NO.		7		Ξ
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV			3	6	35	
									$\overline{}$	_

La sert Sec		AU D	EVICES SHALL BE	and the second second second	27-142000000000000000000000000000000000000	SO MARKON CONTRACTOR	A CONTRACTOR OF THE PARTY OF TH	************	A suspense services	·	4 5000000000000000000000000000000000000	, WHICHEVER	JCCURS	-IROI.
Supplies			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P (°C)	PAS AC	CURACY RESULTS*	CALIBI	RATION JIRED				
			7 A 1 A 1 A 1 A 1 A 1 A 1 A 1 A 1 A 1 A		, ILIVI	1,0)	GIILGKI	(LOULIS	NEG	MKED	PAS			
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEGT #4	TEST #2	TEST#1	TEST#2	YES	No	RETEST	OPERATOR	1	REPAIRS/PROBLEMS/
	A PLANT SERVICE			3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3		(Optional)			TES	МÒ	RESULTS		LD. NO	A Property of the Control of the Con
10/11/2013	1300	34		.100	21		103			٥		Flick	15063	Printer B.O.
			KKF24C	ļ	-									
				-										
		ļ												
<del></del>		***************************************	Prepared by:											24000
	<u> </u>		Douglas C. Talbot			3770								<u> </u>
			02-27-2012											
			Expires on:											
			02-27-2014			_								
								.5005						·
***************************************			470			<del></del>								
								,						
								•						
			4.00		,									
				W_177		_								
					`									
			V								***************************************			
* TC4	11 111		. (1) 0.010	4 - 6.1				111 .1						

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8845

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**			AS P (°C)	PAS AC CHECK I	CURACY RESULTS*	CALIBRATION REQUIRED		PAS			
DATE	TIME	(°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	I <u>.</u> D. NO.	REPAIRS/PROBLEM COMMENTS
0/11/2013	1310	34	12B27-13-5-10-	.100	21		.105			V		Flick	15063	Printer B.O.
		7	KKF24C							, , , , , , , , , , , , , , , , , , , ,				
		<u>'</u>												
														•
			Prepared by:								· · · · · · · · · · · · · · · · · · ·			
			Douglas C. Talbot											
	1211/12/11/11		02-27-2012											
			Expires on:											
			02-27-2014											
												***		
			·											
								_						
										<del>-,  </del>			_	
							-			-				
												_		

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

CHP 202K (Rev. 8-08) OPI 051

(C) (A)								
South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV	AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	, 10	
	South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	829	18	

			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P. TEMI	AS P (°C)	PAS AC	CURACY RESULTS*	CALIBI	RATION JIRED				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE		TEST#2	TEST#1	TEST #2		NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLE
1/2013	1313	34	12B27-13-5-10-	.100	20		0103			D		Flick	15063	Printer B.O.
	<i>J</i> ()	<del></del>	KKF24C											
													_	
			Prepared by:						,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					
			Douglas C. Talbot			anen, (								
			02-27-2012											
			Expires on:											
			02-27-2014											
									,					
		,												
													_	200
CAPPER	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,													
												10100		
														,
										-				
												THE PARTY OF THE P	l	
								_						

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG CHP 202K (Rev. 8-08) OPI 051

25

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERI	AL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		77591

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

Constitution of the second	-		SIMULATOR SOLUTI	Market National Association (National Associ	P	AS	PAS AC	CURACY	CALIB	RATION	en inconicerationales accommensation	18 m		The second secon
DATE	TIME	TEMP		VALUE		P (°C) TEST #2 (Optional)		TEST #2		UIRED NO	PAS RETEST RESULTS	OPERATOR	I.D. NO	REPAIRS/PROBLEMS/
10/11/2013	1317	34	12B27-13-5-10-	.100	ZO		102			X		Flick	15063	A CONTRACTOR OF THE PROPERTY O
	7,	7	KKF24C				1							
		/												
			D			1			<u> </u>					
			Prepared by:											
***************************************			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
м														
			NAME OF THE OWNER OWNER OF THE OWNER OWNE											
	•													
			management of the second of th											
												1000		
														<u> </u>
					٠									
						_								
· · ·														

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

26

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERI	AL NO.	800
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV			8550

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

		SIMULATOR SOLUTION (OR DRY GAS)**		TEMP (°C) CHECK RESULTS* R			CURACY RESULTS*	REQUIRED					The second secon	
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST #1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO	REPAIRS/PROBLEMS COMMENTS
10/11/2013	1349	34	12B27-13-5-10-	.100	21		101			Ø		Flick	15063	Printer B.O.
		,	KKF24C		,									
		<u> </u>	Prepared by:		<u></u>									
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
		,	02-27-2014											
		,												
											-			
			1.00					31.111						
	`													
					,									
* NEW .									-					

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

CHP 202K (Rev. 8-08) OPI 051

PAS MAKE/MODEL PAS SERIAL NO.

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	72573
					VED COOLIDO EIDOT

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

		SIMULATOR SOLUTION (OR DRY GAS)**		TEMP (°C) CHECK RESULTS* F			S* REQUIRED PAS		PAS		1 1 2 2 2		
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST OPERATOR.	I.D. NO	REPAIRS/PROBLEM COMMENTS
0/11/2013	1434	34	12B27-13-5-10-	.100	22		.096			X	Flick	15063	Printer B.O.
		-	KKF24C							·			
			and the second s										
			Prepared by:					-					
	-		Douglas C. Talbot										
			02-27-2012										
			Expires on:										
			02-27-2014										
		1,500											
					ļ								
					*								
			EMIZONE.										

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

28

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERI	AL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		8

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	NC	P. TEMI	AS P(°C)	PAS ACCURACY CALIBRATION CHECK RESULTS* REQUIRED				100 344 6 334		
DATE	TIME	TEMP	LOT NO.	VALUE	TEST#1			TEST #2 (Optional)	YES NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEM COMMENTS
0/11/2013	1217	34	12B27-13-5-10-	.100	25		0099		0		Flick	15063	Printer B.O.
	, ,		KKF24C				, ,						
										-			
			Prepared by:	***************************************									
			Douglas C. Talbot			***************************************							
			02-27-2012										
			Expires on:										
			02-27-2014										
				MATERIAL PROPERTY OF THE PROPE									
												-	
					,								
					`		-						
							`						

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

CHP 202K (Rev. 8-08) OPI 051

3

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8897

					I I SOME TO SOME THE			CALLED AND COMPANY OF STREET	A constitution of the	None And Control of Control	50 1ES15, WHICHEVER OCCURS FIRST.					
			SIMULATOR SOLUTION (OR DRY GAS)**	NC	P	AS P (°C)	PAS AC	CURACY RESULTS*	CALIBI	RATION JIRED				100		
<u></u>	Sec.		(OR DRT GAS)	1	I EIVII	T ( C)	CHECK	KESULIS	REGI	JIKED	PAS	and the second				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS		
10/11/2013	1448	34	12B27-13-5-10-	.100	20		104			p		Flick	15063	Printer B.O.		
	,,_	,	KKF24C				7			1						
			Prepared by:													
			Douglas C. Talbot													
,			02-27-2012													
			Expires on:													
			02-27-2014													
			-													
	,															
	_				4											
		-														

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

AREA NO.

530

CHP 202K (Rev. 8-08) OPI 051

AREA NAME

South Los Angeles

COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18624

31

	LOT NO.	VALUE						JIRED	DAG	Charles and the same	1302	
		VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
	12B27-13-5-10-	.100			3.0.					Flick	15063	Printer B.O.
 ]	KKF24C											
	Dronorod by:					2						
 												-
	02-27-2014											
				_								
 _		A A A A A A A A A A A A A A A A A A A										
_	-		1									
 	V-1								,			
_												
			,									
	2000											
	700000											
			Douglas C. Talbot 02-27-2012 Expires on: 02-27-2014	Douglas C. Talbot  02-27-2012  Expires on:  02-27-2014	Douglas C. Talbot  02-27-2012  Expires on:  02-27-2014	Douglas C. Talbot	Douglas C. Talbot	Douglas C. Talbot				

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL

3	2

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	AL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		18646

			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P (°C)	PAS ACC	CURACY ESULTS*	CALIBRA REQUIR	TION RED	2.31	E. 1965			
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST #1	TEST #2 (Optional)	YES.	NO F	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLE)	
/11/2013	1442	34	12B27-13-5-10-	.100	22		.098			p	Flic	k	15063	Printer B.O.	
1			KKF24C												
													-	•	
			Prepared by:												
			Douglas C. Talbot												
	•		02-27-2012	NO									<u> </u>		
			Expires on:												
			02-27-2014												
													ļ		
								_		$\rightarrow$					
					-										
													-		
								-							
					-										
									_						

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERI	AL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		77488
PAS DEVICES S	ALL BE C	HECKED FOR ACCURACY	EVERY 10 DAYS	OR EVERY 150 TESTS. WHICHE	VER C	CCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P/ TEM	AS P(°C)	PAS AC	CURACY ESULTS*	CALIBF REQL	ATION IIRED				REPAIRS/PROBLEMS/ COMMENTS
DATE	TIME	TEMP	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	
10/11/2013	1436	34	12B27-13-5-10-	.100	21		.101			×		Flick	15063	Printer B.O.
	7	7	KKF24C											
						_								
•						-							_	
			Prepared by:			******								
			Douglas C. Talbot											***************************************
			02-27-2012											
			Expires on:											
			02-27-2014											
			7.00											
					-									

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

CHP 202K (Rev. 8-08) OPI 051

COORDINATOR NAME PAS MAKE/MODEL PAS SERIAL NO. I.D. NUMBER

AREA NAME AREA NO. South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS. WHICHEVER OCCURS FIRST

F/-	SIMULATOR SOLUTI	Committee Commit	**************************************	AS		economico esta Su	CALIBRATION	de constant de la con	HICHEVER OC	CURS FI	ROI.
	(OR DRY GAS)**	ON		AS P (°C)	CHECK R	ESULTS*	REQUIRED				
	TEMP			TEST #2		TEST #2		PAS RETEST			REPAIRS/PROBLEMS/
DATE TIME	TEMP (°C) LOT NO.	VALUE	TEST #1	(Optional)	TEST #1	(Optional)	YES NO	RESULTS	OPERATOR	I.D. NO.	COMMENTS
10/11/2013	34/12B27-13-5-10-	.100	21		1103		Ø	Flie	ck	15063	Printer B.O.
	KKF24C										
		-									
	Prepared by:										
	Douglas C. Talbot										
	02-27-2012										
	Expires on:				,						
	02-27-2014										
		<del>                                     </del>									
					,						
	in also or minus (+) 0.010 mores										

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

CHP 202K (Rev. 8-08) OPI 051

56		
100	3/	•
	//	,

AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO.  South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV							
South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV	REA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	L NO.
	South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		18615

		SIMULATOR SOLUTION OF DRY GAS)**	ON .	P TEMI	AS P. (°C)	PAS AC	CURACY RESULTS!	CALIBI	RATION JIRED		areas are		distribution of the second of
DATE TIM	TEMF (°C)	Territoria de la companya della companya della companya de la companya della comp	VALUE	TEST#1	TEST #2		TEST:#2 (Optional)			PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLE COMMENTS
11/2013 /44	7 54	12B27-13-5-10-	.100	27		100			<i>A</i> D		Flick	15063	Printer B.O.
,	•	KKF24C											
		Prepared by:											
		Douglas C. Talbot		L									
		02-27-2012											
		Expires on:											
		02-27-2014											
													,
	,												
										***************************************			
					Y								
3.9													
						***************************************							~

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL

				The state of the s		
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		18626

		SIMULATOR SOLUTION (OR DRY GAS)**	ŌΝ	.P TEM	AS P (°C)	PAS AC CHECK F	CURACY RESULTS*	CALIBI	RATION JIRED					
DATE TIME	TEMP (°C)	LOT NO.	VALUE	TEST #1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR		I.D. NO.	REPAIRS/PROBLEMS COMMENTS
10/11/2013	34	12B27-13-5-10-	.100	22		101			7		Flick	1	5063	Printer B.O.
,	•	KKF24C				,								
,		Prepared by:												
		Douglas C. Talbot												
		02-27-2012												
		Expires on:												
		02-27-2014		-		***								
		Mento												
		***************************************				WW.								
			****											
				AMELINE AND A SECOND AND A SECOND ASSESSMENT AND A SECOND ASSESSMENT ASSESSME										
														Arne:
				•										
														. 0.000 ( 0.110)

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO.

## South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV 8696 PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

·	Salacar deconoció	AU D	EVICES SHALL BE C	HEORED	Townson States		PARCET SECURITION STREET	STATE STATE OF THE	A SECURITOR OF THE PARTY.	() () () () () () () () () () () () () (	JU ILOIO	, WINDINEVER O		
			SIMULATOR SOLUTION	ON .	. P	AS	PAS AC	CURACY	CALIBI	RATION		1000		
	1.00		(OR DRY GAS)**		TEM	P (°C)	CHECK	RESULTS*	REQ	JIRED	PAS			
		TEMP				TEST #2		TEST #2			RETEST			REPAIRS/PROBLEMS/
DATE	TIME	(°C)	LOT NO.	VALUE	TEST#1	(Optional)	TEST #1	(Optional)	YES	NO	RESULTS	OPERATOR	I.D. NO.	COMMENTS
10/11/2013	1448	34	12B27-13-5-10-	.100	21		108			0		Flick	15063	Printer B.O.
		7	KKF24C							7				
1			Prepared by:											
		-	Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
						**								
						_								
											***************************************			_
		****				<del></del>		-						_
* 1541				4 5.1	1 1 0		1 11				1.1 0.10			

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

•	•
STATE	OF CALIFORNIA
	MENT OF CALIFORNIA HIGHWAY PATROL

AREA NAME

South Los Angeles

AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	L NO.			
530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		¥	? 37	2/	
220	Officer Drian Frick	112002	mitoximeters mentaled beinger i t	1 1		11 1	1 /	

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

		SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P (°C)	PAS AC CHECK F	CURACY RESULTS*	CALIBI REQU	RATION JIRED				
DATE	TEMI TIME (°C)	LOT NO.	VALUE	TEST#1	TEST#2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATO	R I.D. NO	REPAIRS/PROBLEM COMMENTS
11/2013	144734	12B27-13-5-10-	.100	21		1131			X		Flick	15063	Printer B.O.
	77.07	KKF24C											
			******										
				<u> </u>									
		Prepared by:				ļ							
		Douglas C. Talbot				ļ							
		02-27-2012	<del></del>								ļ		
		Expires on:											
		02-27-2014								****			
				1						* **********			
											_		
													-
				,				-					
			···							· · · · · · · · · · · · · · · · · · ·			

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

, .	
STATE OF CAL	IFORNIA
DEPARTMENT	OF CALIFORNIA HIGHWAY PATROL

40

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18692

		SIMULATOR SOLUTION (OR DRY GAS)**		PAS PAS ACCURAC TEMP (°C) CHECK RESULT			CURACY RESULTS*	CALIBR REQU	RATION JIRED	PAS		See Marine		
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEM COMMENTS
0/11/2013	1131	34	12B27-13-5-10-	.100	22		096			٧		Flick	15063	Printer B.O.
	. • 51	,	KKF24C							,				
			Prepared by:											
			Douglas C. Talbot	***************************************										
			02-27-2012			w-107-1-1-1								
			Expires on:											
			02-27-2014											
						<del></del>								
														- TOTAL AND THE STATE OF THE ST

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALÍFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL

42

						~ ~
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	L NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		18762

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

	SIMULATOR SOLUTION PAS (OR DRY GAS)** TEMP (*C)						PASAC	CURACY RESULTS*	CALIB	RATION UIRED		, WIIIONE VEIX		
" DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/
10/11/2013	1447	34	12B27-13-5-10-	.100	21		100			2		Flick	15063	Printer B.O.
	<i>/ ( .</i>		KKF24C							7				
,														
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
			200											
					ż									
									_					

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

## STATE OF CALIFORNIA DEPARTMENT OF CALIFORNIA HIGHWAY PATROL PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18766

MILES CONTRACTOR OF THE PROPERTY OF THE PROPER	PAS DEVIC		CHECKED			EVERY 1					, WHICHEVER C		URS FI	
		MULATOR SOLUTION (OR DRY GAS)**	ON	12 565 Sept. 2000 Sept	AS *	PAS AC	CURACY RESULTS*	CALIBR	RATION	*				20
DATE	TEMP	LOT NO.	VALUE	TEST#1	TEST#2	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR		I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/11/2013		7-13-5-10-	.100		200000000000000000000000000000000000000	J 1N					Flick	201 201020213	and the second second second	Printer B.O.
	KKF	V ANTENNA POWER												
		red by:										$\bot \bot$		
		ouglas C. Talbot										1		
		-27-2012										44		
		es on:										++		-
	02	-27-2014										++		
												++		
		<del>-</del>										++		
							_					╁┼		
					***************************************				· · · · · · · · · · · · · · · · · · ·			1-1-		
										3,100				-
-														
			Series Se											
												11		
												-		<u>-</u>
				,										
												$\vdash$		
								لبب				$\perp$		:- 0.000 t 0.110)

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG CHP 202K (Rev. 8-08) OPI 051

44

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.				
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18691				

		246 D	EVICES SHALL BE	PHECKED		CUBACY		IO DAVO			EO TESTS		ED 00	700	DOT
	·	ASD	EVICES SHALL BE		er progresser conscensivent		STORE SECURITION OF THE SECURI	No. to the second control of the second cont	on the second	*******	001 1000HD10070070000000000000000	, WHICHEV	ER OC	CURS F	IKSI.
			SIMULATOR SOLUTI (OR DRY GAS)**	ON	TEM	PAS PAS ACCURACY CALIBRATION TEMP (*C) CHECK RESULTS* REQUIRED									
	100	-	1							T	PAS				
DATE	TIME	TEMF (°C)	LOT NO.	VALUE	TEST#1	TEST #2	) TEST #1	TEST #2	VES	NO	RETEST RESULTS	OPERAT	OB:	I.D. NO.	REPAIRS/PROBLEMS/. COMMENTS
10/11/2013		TO LANCOUR DESCRIPTION		.100	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	(Optional		(Optional)	16.0		REGOLIS	Flick	OK		
10/11/2013	176	17	KKF24C	.100	22		,104		-	$\downarrow \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \!$		FIICK		15063	Printer B.O.
		<del> /</del>	KKF24C											_	
	-	1 :				1			-			-		-	
		<del>                                     </del>				<del>                                     </del>				-					
		1	Prepared by:						ļ						
		+	Douglas C. Talbot						1						
		1	02-27-2012												
			Expires on:			ļ	-		<del> </del>	-					
			02-27-2014				<del>                                     </del>		_	-					
			02-27-2014							_					
										<u> </u>					
								1							
						<del> </del>	1			<del> </del>					
									<u> </u>						
· · · · · · · · · · · · · · · · · · ·												1			
										<del> </del>					
					<del></del>										White state
														_	

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

CHP 202K (Rev. 8-08) OPI 051

1	<
7	<i>)</i>

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	17990

			SIMULATOR SOLUTION (OR DRY GAS)**			PAS TEMP (°C)		PAS ACCURACY CHECK RESULTS*		RATION JIRED		Same and the same		
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST #1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO:	REPAIRS/PROBLEMS/ COMMENTS
10/11/2013			12B27-13-5-10-	.100			13.0				No.	Flick	15063	Printer B.O.
			KKF24C		4000000									
			Decreased have											
			Prepared by:										1	
			Douglas C. Talbot 02-27-2012	1							***************************************			
			Expires on:											
			02-27-2014										~	
			02-27-2014											
	70													
				, , , , ,										
	****													
							***************************************							
			-											
			WW 10											
	-													
			•											
					,									

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE	OF CALIFORNIA	
91/11-	OF CHEN CHANK	

DEPARTMENT OF CALIFORNIA HIGHWAY PATROL

### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	L NO.	- 0
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		1877	1
		· · · · · · · · · · · · · · · · · · ·					

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS. WHICHEVER OCCURS FIRST.

DATE	TIME (°C		ON VALUE	TEMI	AS (°C) TEST#2 (Optional)	CHECK	CURACY RESULTS* TEST #2 (Optional)	REQUI	ATION RED NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLE COMMENTS
1/2013		12B27-13-5-10-	.100	21		100			Ø		Flick	15063	Printer B.O.
		KKF24C				erec.							
		Prepared by:											
		Douglas C. Talbot								***** ********************************			
		02-27-2012											
		Expires on:											
		02-27-2014	****										
											•		
			<del></del>							www.aaa.aa.aa			
		THE STATE OF THE S											
			*										
										55-VIII			
				` .			34			WHICH STORY			
					_								

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	L NO.	
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		41486	
DAS DEVICES OF	MIL DE C	HEAVED FOR ACCURACY	T/EDV 40 D 4 VO 6	NO EVERY ARE TERTO MUNICUE	V/ED 0	COLUDA FIDAT	

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCC	CURS FIR	RST.
-------------------------------------------------------------------------------------------	----------	------

TAGE	EVICES SHALL BE C			TOTAL CONTRACTOR OF THE PARTY O	Mades Constitution Constitution	and the second second	Lancas and the same of the sam	311 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	Acres and and the rest of the	, WHICHEVER O	CCORS	INGI.
	SIMULATOR SOLUTION (OR DRY GAS)**	)N	P. TEMP	AS P. (°C)	PAS AC	CURACY ESULTS*	CALIBR	RATION				
	2000 000 00000								PAS			
DATE TIME (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST #1	TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	סא מו	REPAIRS/PROBLEM COMMENTS
	12B27-13-5-10-	.100			2105			×	,	Flick	15063	Printer B.O.
	KKF24C		2)		101					I HOK	15005	Timter B.o.
	Prepared by:											
	Douglas C. Talbot											,
	02-27-2012											
	Expires on:							_				
	02-27-2014						_					
	15											
								_				
			-									
									3			
									7-0-7-			
											_	
			-									
T64 4: - : - : : : : : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 : - : 1 :	(1) 0.010	4 64				***						

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110). If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

COORDINATOR NAME

Officer Brian Flick

AREA NO.

530

CHP 202K (Rev. 8-08) OPI 051

AREA NAME

South Los Angeles

I.D. NUMBER
15063

PAS MAKE/MODEL
PAS SERIAL NO.
15063

Intoximeters Inc./Alco-Sensor IV

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	SIMULATOR SOLUTION (OR DRY GAS)**		AS P (°C)	PAS AC CHECK F		CALIBRATIO REQUIRED		1.5		
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST #1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES NO	PAS RETEST RESULTS	OPERATO		REPAIRS/PROBLEM COMMENTS
/11/2013	145-1	34	12B27-13-5-10-	.100	20		a 095		$\infty$		Flick	15063	Printer B.O.
			KKF24C										
											ļ <u>.</u>		
			Prepared by:										
			Douglas C. Talbot										
			02-27-2012	uav.									
			Expires on:										
			02-27-2014										
							***************************************						
								-					
					3								

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	L NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		41502

	PAS L	DEVICES SHALL BE	HECKED	FOR ACC	URACY	EVERT	U DA 15	OK EV	ERY 1	50 1E515	, WHICHEVER O	CCURS FI	
DATE T	TEMI	SIMULATOR SOLUTION (OR DRY GAS)**  LOT NO.	ON VALUE	TEM	AS (°C) TEST #2 (Optional)	CHECK	CURACY RESULTS* TEST #2 (Optional)	CALIBF REQL YES	IRED	PAS RETEST RESULTS	OPERATOR	i.D. NÖ,	REPAIRS/PROBLEMS/COMMENTS
10/11/2013	DV 35	12B27-13-5-10-	.100	21		.097			X		Flick	15063	Printer B.O.
10/11/2013	01 01	KKF24C	.100	~/		0//	<del></del>	-	<u>/                                    </u>		A MON	13005	X I III I I I I I I I I I I I I I I I I
		KKF24C											
		Dung and have										_	
		Prepared by:											
		Douglas C. Talbot											
		02-27-2012											
		Expires on:											
		02-27-2014									•		
		O CONTRACTOR AND ADDRESS OF THE PARTY OF THE											
											And the state of t		
											,		
		1 1/2 WALT PART (1970)		٠	_								
										****			
													1

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

SGT'S PAS

### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIA	AL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		8874

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS. WHICHEVER OCCURS FIRST

			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P. TEMI	AS P.(°C)	PAS ACC	CURACY ESULTS*	RATION JIRED			**	7-0-1
DATE	TIME	TEME (°C)		VALUE		TEST #2	TEST#1	TEST#2	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEM GOMMENTS
/11/2013	1/42	34	12B27-13-5-10-	.100	2/		102		R		Flick	15063	Printer B.O.
-	,	•	KKF24C					1					
			Prepared by:										
			Douglas C. Talbot										
			02-27-2012										
			Expires on:										
			02-27-2014										
												_	
											1		
						-						-	
					*				 				
									 	<del></del>		-	

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).