STATE OF CALIFORNIA	
DEPARTMENT OF CALIFORNIA HIGHWAY P	ATRO

DEPARTMENT OF CALIFORNIA HIGHWAY PATROL PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG CHP 202K (Rev. 8-08) OPI 051



AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8501

			SIMULATOR SOLUTI (OR DRY GAS)**	ON	PA TEMP	s (°C)	PAS ACCURACY CHECK RESULTS:	REQUIRED	1 (1) (1) (1) (1) (1) (1) (1) (1) (1) (1				
DATE	TIME	TEMF (°C)	LOT NO:	VAĽUE	TEST #1.	TEST #2 (Optional)	TEST #2 (Optional)	P RE YES NO RES	AS TEST ULTS OPERATOR	LD, NO.	REPAIRS/PROBLEM COMMENTS		
/15/2013	1354	34	12B27-13-5-10-	.100	2 0		.096	X	Valadez	16071	Printer B.O.		
		1	KKF24C										
_													
			Prepared by:		_								
			Douglas C. Talbot	_									
			02-27-2012										
-			Expires on:	_									
-			02-27-2014		_								
·				_		_							
						_							
	_		i		_								
	_					-							
				_			:						
-													
	_	*					_						
						•							
			<u> </u>										
-					-	-				-			
	_		!			-							
	_			-	_								

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

					i l
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18783

			SIMULATOR SOLUTION (OR DRY GAS)**	NC	P	AS P: (°C)	PAS ACC	CURACY ESULTS:	CALIBR REQU	IIRED					
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST #1	TEST#2 (Optional)	TEST#1	TEST #2 (Optional)		. R	PAS ETEST ESULTS	OPER	ATOR	I.D. NO.	REPAIRS/PROBLEM COMMENTS
0/15/2013	1352	34	12B27-13-5-10-	.100	20		.099			X		Valadez		16071	Printer B.O.
		,	KKF24C							1					
														_	
			Prepared by:				_								
			Douglas C. Talbot												
			02-27-2012												
			Expires on:												
			02-27-2014												
												_			
															_
			_				_						<u> </u>		
	_						_								
						_							<u> </u>		· · ·
_			_	_		_	_						<u> </u>		
			·			_		_							
		-						:							
				_									Í		
			·				_						i		
				_			_						<u> </u>		

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110). If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#3

					The state of the s
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8546

			SIMULATOR SOLUTION (OR DRY GAS)***	ON.	P TEMI	AS P (°C)	PAS AC CHECK I	CURACY RESULTS*	CALIBI REQ	RATION JIRED	PAS					
DATE	TIME		LOTNO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPER	ATOR	î.D. NO.	REPAIRS/PROBLEM COMMENTS	
0/15/2013	1352	34	12B27-13-5-10-	.100	21		:100			X		Valadez		16071	Printer B.O.	
		•	KKF24C		,											
			Prepared by:													
			Douglas C. Talbot													
			02-27-2012													
-			Expires on:													
			02-27-2014													
-																
				<u> </u>												

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#4

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	82659

Listed on Colombian	a didaka dia mengenti	MO D	EVICES SHALL BE (a Portion residence from the first of the control	distributed street and area of the	a majoritary of the Superior Committee of the Advis-	NAMES OF A PERSON ASSESSED.		and Carabana in Court 1990	Long terraments assume entrances of	, WHICH	VER OU	ESTATUM	
			SIMULATOR SOLUTI (OR DRY GAS)**	ON	P TEM	AS P. MON	CHECKE	CURACY	DEM	IDED.					Programme and the second
.			(UKDKT GAS)		Management of the second secon	5760° C250554603346445255640034	CHLCKI	RESÚLTS*	I VLV	JINED	PAS		10000		
DATE	TIME	TEMP (°C)		VALUE	TEST#1	TEST#2	TEST#1	TEST#2	YES	NO	RETEST RESULTS	OPER	ATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
A STATE OF THE STA	**** *********************************	B 725 BZ V636	12B27-13-5-10-	.100	20		.103		256 St. 547 W.	X		Valadez	N Segrans	845 - Casa 240880 (Casa	Printer B.O.
10/13/2013	1742	0-1	KKF24C	.100	- 		1105					- uluuuz		10071	
			KKI 240									-			
				_											
			Prepared by:												
			Douglas C. Talbot												
			02-27-2012												
			Expires on:											_	-
			02-27-2014												
												_			
															<u> </u>
											-				
												.			

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



CHP 202K (Rev. 8-08) OPI 051

AREA NAME AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO. South Los Angeles 530 15063 Officer Brian Flick Intoximeters Inc./Alco-Sensor IV

			SIMULATOR SOLUTION PAS PAS ACCURACY CALIBRATION (OR DRY GAS)** TEMP (*C) CHECK RESULTS* REQUIRED												
DATE	TIME	TEMP (°C)				TEST #2 (Optional)	TEST #1°	TEST #2 (Optional)	YES	P. REI	EST -	RATOR	LD. NO.	REPAIRS/PROBLI	
/15/2013	1354	34	12B27-13-5-10-	.100	20		. 100	Acceptance of the second	S S F, G SHIP TO SEE FEE	X	Valadez	1	16071	Printer B.O.	
	•		KKF24C					_							
												1.			
					_			_							
_			D 11	_		_		_		-		 			
_			Prepared by:									1 -			
			Douglas C. Talbot 02-27-2012			-		-				<u> </u>			
			Expires on:			-									
	_		02-27-2014									11			
_			02-27-2011			-	_								
								-		_					
	_				_										
												<u> </u>			
	_				_										
												1			
	_				_							1			
						-		-				<u> </u>	_		
-												<u> </u>			
					-	-	-						_		
											· ·				

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL

CHP 202K	(Rev. 8-08)	OPI 051			

AREA NAME COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO. AREA NO. 8580 South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV

in all of Section 1			SIMULATOR SOLUTION (OR DRY GAS)**		PAS TEMP (°C		CCURACY RESULTS*	CALIBRA REQUIF	RED	AS		
DATE	TIME	TEMP (°C)		VALUE	TES	T#2 ional) TEST#	TEST#2 (Optional)	YES	RET	EST ULTS OPERAT	OR I.D. NO.	REPAIRS/PROBLEM COMMENTS
/15/2013	1348	34	12B27-13-5-10-	.100	20	./0(:	X	Valadez	16071	Printer B.O.
		1	KKF24C	_								
									1			
									_			
_			Prepared by:									
			Douglas C. Talbot									
			02-27-2012						_	i		
			Expires on:	_								
			02-27-2014_									
_												
							_					
				_								
_												
	_											<u> </u>
												<u> </u>
										1		
										i		

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

CHP 202K (Rev. 8-08) OPI 051

AREA NAME AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO. 83032 South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV

			SIMULATOR SOLUTION (OR DRY GAS))N	P/ TEMF	AS 2' (°C),	CHECK	CURACY ESULTS*	REQU	IIRED				
DATE	TIME -	EMP (°C)	LOT NO.	VALUE		TEST#2	TEST#1	TEST #2 (Optional)	YES		PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLE
/15/2013	1336 3	54	12B27-13-5-10-	.100	21	And the Charles and the Charles	.097	2.0	A1900 CE 14 26 15 16	X	Vala	idez	16071	Printer B.O.
			KKF24C									i		
_											_	!		
				1										
			Prepared by:											
			Douglas C. Talbot									j		
			02-27-2012											
			Expires on:									1		
			02-27-2014									!		
				_										
					_									
												i		
												i		
											_	<u>i</u>		
												_		
						_								
						_							_	
				_			_					1 2		
													_	

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#8

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8680

	P	AS D	EVICES SHALL BE C SIMULATOR SOLUTION	to product and the state of the state of	P	. In J. 1887 Report Land Com. Behavior of Printing	PAS AC	CURACY	CALIBRA	ATION	A describer for appropriate and the	, WHICHE	VEROC	CURS FI	KSI.
DATE	TIME	TEMF	(OR DRY GAS)**		TEMP	TEST #2 (Optional)	CHECK	RESULTS*	REOUI	RED.	PAS RETEST RESULTS	OPER	ATOR.	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/15/2013	Brings T. July 10	Photograph although	12B27-13-5-10-	.100	20	1. North 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	.100	As Negotics, A		X	is a building a second	Valadez		AT COMPANY STATE	Printer B.O.
10/13/2013	1717	-	KKF24C	1,200			710					, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		10071	
												!			
			Prepared by:												
			Douglas C. Talbot												
			02-27-2012	_	_	_					_				
			Expires on:				_					-!			
			02-27-2014												
												<u> </u>			
				_		_		_							
										-					
							<u> </u>	<u> </u>		-					
					_	_	_								
											_	!			
					_							!			
						-									
				_		_	· <u>-</u>	_				1			
												-			
											_	i	_		
	_											- 1			

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#9

CHP 202K (Rev. 8-08) OPI 051

AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKEMODEL PAS SERIAL NO. South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	ON		AS Ps(°C)	CHECK	CURACY CA	EQUIRED			
DATE	TIME	TEMP (°C)		VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST#2 (Optional) YI	RES NO RES	AS TEST JULTS OPERA	FOR LD.NO.	REPAIRS/PROBLEMS COMMENTS
0/15/2013	1337	34	12B27-13-5-10-	.100	ai		.096		X	Valadez	16071	Printer B.O.
		i	KKF24C					:		4		
										3 4 1		
			Duran and have							4		
			Prepared by:							- 1		
			Douglas C. Talbot 02-27-2012							1		
_			Expires on:							- !		
			02-27-2014									
			02 27 2011							1		-
-			_	_								
										il		
										1		
										1		
										- 1		
			_							1		
						_						
_												
				_								
										<u>i</u>		
_				l						- 1		

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	77505

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST. SIMULATOR SOLUTION PAS ACCURACY CALIBRATION PAS CHECK RESULTS* (OR DRY GAS)** TEMP (°C) REQUIRED PAS TEST#2 TEMP TEST#2 RETEST REPAIRS/PROBLEMS/ (°C) LOT NO. VALUE TEST#1 (Optional) TEST#1 (Optional) YES DATE TIME NO RESULTS **OPERATOR** LD. NO. COMMENTS ,095 12B27-13-5-10-.100 10/18/2013 Flick 15063 Printer B.O. KKF24C Prepared by: Douglas C. Talbot 02-27-2012 Expires on: 02-27-2014

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#(1

					
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	77479

			SIMULATOR SOLUTION (OR DRY GAS)**	ON.	P. TEMI	AS P. (°C)	CHECK RES	RACY CALIB OULTS* REQ	UIRED-			
DATE	ПМЕ	TEMF	ŁOŦNO.	VALUE	TEST #1	TEST #2 (Optional)	TEST#1 (C	EST#2 Optional) YES	RE	AS TEST PERATOR SULTS OPERATOR	1.D. NO.	REPAIRS/PROBLEM COMMENTS
0/15/2013	1338	34	12B27-13-5-10-	.100	20		.095		X	Valadez	16071	Printer B.O.
			KKF24C							.		
										i		
			Prepared by:							- 1		
			Douglas C. Talbot									
			02-27-2012		_							
_	_		Expires on:		_		_			!		
			02-27-2014									
						_						
					_					i		
_												
				_	_			_				
_						_			_			
				_								
				_			_					
							_			- 1	_	
-								-	_	!		

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#/2

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	82460

47. T			EVICES SHALL BE O SIMULATOR SOLUTION (OR DRY GAS)**	NC	"P TEMI	ÁS	The same actions of these states and	CURACY	CALIBI	RATION					
DÄTE	TIME	TEMF (°C)	LOT NO.	VALUE	TEST #1:	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPER	ATOR	LD. NO.	REPAIRS/PROBLEM COMMENTS
10/15/2013	1333	34	12B27-13-5-10-	.100	20		.095			X		Valadez		16071	Printer B.O.
			KKF24C									į			
												}			
											_				
					·							,			
		,	Prepared by:									-			
			Douglas C. Talbot												
			02-27-2012									i			
			Expires on:												
			02-27-2014									1			
_															
												:			
				_											
	_			_											
				_			_					1			
												i			
_															
-												1			
				_								i			
_												- 1			
_															
	_											i			
-				_		_						i			

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

期3

AREA NAME AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO. 8709 South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV

			SIMULATOR SOLUTION (OR DRY GAS)***)N	P TEM	AS P:(°C)	PAS AC CHECK I	CURACY RESULTS*	CALIBI REQI	RATION JIRED					
DATE	TIME	TEMP (°C)	LOT NO:	VALUE	TEST#1	TEST #2 (Optional)	TEST #1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPER	ATOR	I.D. NO.	REPAIRS/PROBLEM COMMENTS
0/15/2013	1343	34	12B27-13-5-10-	.100	21	_	.103			X		Valadez		16071	Printer B.O.
			KKF24C												
												i			
								ļ.							
			Prepared by:												
			Douglas C. Talbot		_			·				1			
			02-27-2012									;			
			Expires on:				•					!			
		,	02-27-2014												
											_				
												i	_		
												1			
				·											
												1			
								:							
												1			
_								:							
												<u> </u>			
								:				i			

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#14

					:	
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	2714
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		8 /17
					· · ·	

ECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150	

	۲	'A5 D	EVICES SHALL BE C	HECKED	FUR ACC	URACY	To the second of the second of the				S, WHICH	EVEROC	CURS FI	KSI.
			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P (CC)	PAS AC CHECK I	CURACY RESULTS	CALIBRATIC REQUIREE	No.				2000 T (185
DATE	TIME	TEME (°C)	LOTNO	VALUE	TEST#1	TEST#2 (Optional)	TEST#1	TEST.#2 (Optional)	YES NC	PAS RETEST RESULTS	OPE	RATOR	1.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/15/2013	1342	34	12B27-13-5-10-	.100	20		.103		X	A STATE OF THE PARTY OF THE PAR	Valadez	i i	16071	Printer B.O.
			KKF24C											
									_					
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012											_
			Expires on:											
			02-27-2014											
-					_				_		- :			
											- 1			
				<u> </u>				<u> </u>				<u> </u>		
														<u>·</u>
										-	!			
											i i	: 	-	
											1			
		_								_				

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#16

AREA NAME
AREA NO.
COORDINATOR NAME
LD. NUMBER
PAS MAKE/MODEL
PAS SERIAL NO.
South Los Angeles
530
Officer Brian Flick
15063
Intoximeters Inc./Alco-Sensor IV

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**		P JEM	? (°C)	CHECK	CURACY RESULTS*	REQU	RATION JIRED			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
DATE	TIME	TEMP (°C)		VALUE		TEST#2	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERAT		REPAIRS/PROBLEM
0/15/2013	1323	34	12B27-13-5-10-	.100	21		.099	. Section and all accounts	- Target Street Street S	X	Va	ladez	16071	Printer B.O.
			KKF24C									il 11		
					_									
			Prepared by:									1		
			Douglas C. Talbot									1		
			02-27-2012									1		
			Expires on:											
			02-27-2014											
												!		
												· il		
												- 1		
											,	- 11		
												- ! -		-
												- 1		
												- !!		_
												1		
	•													

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

1

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#1-

AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO. South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST,

			SIMULATOR SOLUTION (OR DRY GAS)**	SIMULATOR SOLUTION PAS PAS ACCURACY CALIBRATION (OR DRY GAS)** TEST #2 PAS RETEST									
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST TEST#1 (Optio	#2 nal) YES	NO RE	ETEST	I.D. NO	REPAIRS/PROBLEM COMMENTS	
/15/2013	1332	34	12B27-13-5-10-	.100	20		./00		X	Valadez	16071	Printer B.O.	
		•	KKF24C							1			
										i			
			Prepared by:							i			
			Douglas C. Talbot							i			
			02-27-2012							; 1			
			Expires on:										
			02-27-2014							:			
										i			
										1		_	
			_										
										i			
										9			
										İ		_	
										1			
										1			
										1			
										1			
										¥			

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

1

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#18

			_		
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8265 1

		デスタンは中央の石田市田	·····································	NC PROPERTY OF THE PROPERTY OF		AS P (°C)	CHECK	ESULTS*	CALIBRATIO REQUIRED	N PAS			
DATE	TIME	TEME (°C)		VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES NO	RETES	rlitushi	OR I.D. NO.	REPAIRS/PROBLET COMMENTS
0/15/2013	1324	34	12B27-13-5-10-	.100	2/	and a second sec	,095	Section of the Section of the Section	×		Valadez	16071	Printer B.O.
			KKF24C								- 1		
			Prepared by:								7		
			Douglas C. Talbot										
			02-27-2012								1		
			Expires on:										
			02-27-2014								•		
											1		
											.1		
			_										
			_							-			
											1		
											'!		
											! !		
											1		
											1		

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#19

AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO. South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV

	P	42 DI	EVICES SHALL BE C	HECKED	FUR ACC	URACY	EVERY	U DAYS	OREV	EKY 15	0 IESIS,	, WHICHE	VER OC	CUKS FI	K51.
			SIMULATOR SOLUTION	NC .	P	AS	PAS AC	CURACY	CALIBE	RATION					200 Pt 1000-77
1-12-21			(OR DRY GAS)**		TEMI					JIRED.				100 at 200	
		TEMP				TEST#2		TEST#2		107	PAS RETEST				REPAIRS/PROBLEMS/
DATE	TIME	(°C)	LOT NO:	VALUE	TEST#1	(Optional)	TEST #1	(Optional)	YES	NO	RESULTS	OPER	ATOR	I.D. NO.	
10/15/2013	1328	34	12B27-13-5-10-	.100	20	110-130-107	.096	and the property of		X	edemina ou a la sand, and femines as indiano. The	Valadez		16071	Printer B.O.
			KKF24C										İ		
												1			
												i			
													<u> </u>		
			Prepared by:									1			
			Douglas C. Talbot									i			
			02-27-2012									i			
			Expires on:									i			
			02-27-2014									!			
												I			
												i			
														4	
													<u> </u> 		
												1			
												1			
				,											
												:			
												I			
													<u> </u> 		
												1	<u> </u>		
												:	 		
												i			
												1			
	• • •		* (.) 0.010		1 1 6			1*1			*1 0 100	i			: 0.000 + 0.110

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

DEPARTMENT OF CALIFORNIA HIGHWAY PATROL

PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG

#20

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO. L CAL CALL
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18687
				-	

Tree or a tree of the state of	P	AS D	EVICES SHALL BE C	the last temporaries to the state to the second	eri a a di Grandina arriba Vinanzandarri	e nach would be fact traditional or Standar	edinorial (deputy gradiente carror à	E Johnson England Ministr	demanded and a rest	Malan Marin M. Tim	Acres Service Society (1990)	, WHICHE	VER UC	CURS FI	
40			SIMULATOR SOLUTION (OR DRY GAS)**	ON:	P TEMI	AS	PAS AC	CURACY RESULTS*	CALIB	RATION					
			(OR DRY GAS)		iEMI	7 (0)	CHECK		200000		PAS			100	
		TEMP				TEST#2		TEST#2			RÉTEST				REPAIRS/PROBLEMS/
DATE .	TIME	(°C)	A series of about all the contract of the cont	NEW TOWN THE STANDARD STAND	agruppessur, agranga	(Optional)	Lance serven were diseased the	(Optional)	YES.	Story Service Control of	RESULTS	25-02-05-05-05-0-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	ATOR -	I.D. NO.	
10/15/2013	1352	34	12B27-13-5-10-	.100	51		1102	:		入		Valadez		16071	Printer B.O.
			KKF24C									1			
												. !			
												;			
												i i			
			Prepared by:									!			
			Douglas C. Talbot									!			
			02-27-2012									f			
			Expires on:									:	!		
			02-27-2014									1			
								:					i i		
				,								1	ļ		
												i			
												1	<u> </u>		
												,	<u> </u> 	_	
												1			
												1	1		-
												-1			
												1	İ		
												;	i		-
	1, , ,				1 1 6		L	121 42			0 104				:- 0 000 +- 0 110)

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8635

4 1 2 4 2 4 2 4 2 4 2 4 2 4 2 4 2 4 2 4 2			SIMULATOR SOLUTION (OR DRY GAS)**	ON -	P TEMI	Así P (°C)	CHECK F	CURACY ESULTS*	REQ	RATION UIRED					
DATE	TIME	TEMP	LOT NO.	VALUE	TEST#1	TEST #2: (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPER	ATOR	LD NO.	REPAIRS/PROBLEMS/COMMENTS
10/15/2013	1329	34	12B27-13-5-10-	.100	ಎತ	The state of the s	.099	and thought a state of some	and a second	X	Second and on Life and Select an addition	Valadez	A STATE OF THE STATE OF THE STATE OF	16071	Printer B.O.
			KKF24C									1			
												- 1			
												* 1			
			Prepared by:									i			
			Douglas C. Talbot												,
			02-27-2012									!			
			Expires on:				_					<u>. i</u>			
			02-27-2014									1			
												!			
												,			
									_			i			
					_						_	i			···-
											_				
	_				_										
												1			
												- 1			
	_											- 1			
	_							<u> </u>			_			_	
	_											1			
			_							_				_	
															·

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#22

CHP 202K (Rev. 8-08) OPI 051

	_					
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	Coile
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		88 48

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	ON .	P TEM	AS P (°C)	PAS ACC	CURACY ESULTS	CALIBI REQL		PAS				
DATE	TIME	TEME (°C)		VALUE		TEST #2 (Optional)	TEST #1	TEST #2 (Optional).	YES		RETEST	OPER		. NO.	REPAIRS/PROBLEM
/15/2013	1323	Own come a service	12B27-13-5-10-	.100	20	- Joseph Strate white doubt	.105	- 123.2000 to 100.000	Contract Fred Late	入	reg tool of my left the stages (197 mg)	Valadez	160	071	Printer B.O.
	;		KKF24C									,1			
												!			
									_			1			
												i			
			Prepared by:					:				:			
			Douglas C. Talbot												
			02-27-2012												
			Expires on:					-				1			
			02-27-2014									;			
												i			
												·i			
												:			
				<u>. </u>	•							!			
												-			
												! !			
															_
	_											i l			

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

i |

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#23

!!

CHP 202K (Rev. 8-08) OPI 051

AREA NAME
South Los Angeles

AREA NO.
COORDINATOR NAME
LD. NUMBER
PAS MAKE/MODEL
Intoximeters Inc./Alco-Sensor IV

PAS SERIAL NO.
SAGS

SAGS

PAS MAKE/MODEL
Intoximeters Inc./Alco-Sensor IV

			SIMULATOR SOLUTION (OR DRY GAS)**		TEME	AS 2- (°C):	PAS AC CHECK F	CURACY CAL PESULTS* RE	IBRATION QUIRED	PAS				
DATE	TIME	TEMP (°C)	EOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional) YE	S NO	RETEST RESULTS	OPERA	TOR.	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/15/2013	1254	34	12B27-13-5-10-	.100	20		-098		メ		Valadez		16071	Printer B.O.
	,		KKF24C											
											i j			
											. 1			
											- 1			
			Prepared by:								:			
			Douglas C. Talbot								1			
			02-27-2012											
			Expires on:											
_			02-27-2014								.			
											: 1			
_														
											11			
						_					1			
											- :			
											.1			
											1			
											!		_	····
_											11			
					_						11			
											, ,			
			_								, ;			
-											11	I		
											, ,	<u> </u>		

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#24

CHP 202K (Rev. 8-08) OPI 051

AREA NO. COORDINATOR NAME LD. NUMBER PAS MAKE/MODEL PAS MAKE/MODEL PAS SERIAL NO. Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV							
South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV	AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	C = 101
	South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		8848

The feet has problem and the	F	AU D	EVICES SHALL BE C	HECKED	FUR ACC	UNACI	EVERTI	UDAIS	UKEV		00 15010	, WHICHEVER O	CURS F	IK31.
			SIMULATOR SOLUTION (OR DRY GAS)**		TEM	AS P (°C)	CHECK	CURACY RESULTS*	REQ	UIRED -				
DATE	TIME	TEMF (°C)	u e e e e e e e e e e e e e e e e e e e	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST#2 (Optional)	YES	NO.	PAS RETEST RESULTS	OPERATOR.	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/15/2013	1301	34	12B27-13-5-10-	.100	20		.102	-		X		Valadez	16071	Printer B.O.
		i -	KKF24C									1		
										_		:		
			Prepared by:											
			Douglas C. Talbot									1		
			02-27-2012					-				<u> </u>		
			Expires on:									1 1		
-			02-27-2014											
			02-27-2014						_			- 1		
												11		
												i		
												:		
												: 1		
						_						t į		
												:		
												5		
												11		
								-				.		
											_			
								-				ı İ		

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#25

REA NAME AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKEMODEL PAS SERIAL NO. 7759/ This is a serial no. 7759/						
South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV 7759/	REA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
	South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	7759/

			SIMULATOR SOLUTION (OR DRY GAS)**	NC	P. TEMI	AS P (°C)	CHECK	CURACY RESULTS*	REOU	JIRED			and the second second
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST #1.	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	RET	AS EST ULTS OPERATOR	I.D. NO.	REPAIRS/PROBLEM COMMENTS
)/15/2013	1255	34	12B27-13-5-10-	.100	19		.101		1,000	X	Valadez	16071	Printer B.O.
	,	,	KKF24C										
				_							11		
											. !!		
_								_		_	! !		
			Prepared by:	_									
		_	Douglas C. Talbot	_									
			02-27-2012		_								
			Expires on:							_			
			02-27-2014		_						:		
				_									
											.		
											1		
											i		
											1!		
	-			_							1		
					_				_	_			_
								_			1		
					_	_		-			1		
_	_						_				11		
_							_				11		
				_	_						: 1		

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

REA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8850	

	e de la companya de la companya de la companya de la companya de la companya de la companya de la companya de		SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS ⊇ (°C)	PAS AC CHECK F	CURACY RESULTS*	CALIBRA REQUI	ATION RED	PAS RETIEST RESULTS OPE		iz si	
DATE	TIME	TEMP		VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST OPE	RATOR LD	NO.	REPAIRS/PROBLE COMMENTS
/15/2013	1253	34	12B27-13-5-10-	.100	20		-100			X	Valadez)71	Printer B.O.
			KKF24C									1		
												- 1		
												:		
			Prepared by:											
			Douglas C. Talbot									11		
			02-27-2012											
			Expires on:									· i		
			02-27-2014									1		
												11		
												'		
												::		
												:		
												1		
												1		_
												1		
												!		
												11		
												i j		
												()		
												11		
												:		

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#27

	_		_		
REA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	775 /3

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

The state of the s	r Taganasan	AJD	EVICES SHALL BE C	te filming all the title and the second	Planterova - Heaven La	ter attraction of department of a second procedure	(femal), Tanistone, technical records	N. S. Ph. Thank St. of St. of Market St. of St. of St.	Allana also has been to	with the control of	Printers in curious not true.	, WHICHEVER OC	ELECTRICAL SECTION	NOTE
			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P:(°C)	CHECK	CURACY RESULTS*	REQ	UIRED.	PAS			The state of the s
DATE	TIME	TEMP (°C)	LOTNO	VALUE	TEST#1	TEST#2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	1.D. NO.	REPAIRS/PROBLEMS/
10/15/2013	1248	34	12B27-13-5-10-	.100	2/		. 699			X		Valadez	16071	Printer B.O.
			KKF24C									4 i		
												1		
												* 1		
					. <u> </u>							1!		
			Prepared by:											
			Douglas C. Talbot									11		<u> </u>
			02-27-2012									1		
		:	Expires on:		_							11		
			02-27-2014									Ti .		
							_					, l		
		_		_								.1		
												1:	-	
				_								. !		
				_							_	11		
										_		1		
												11		
												11		
										-		1		_
										_		1:		
			_								_	41		
												i		
											_			
												11		

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

11

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#28

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	830 > 1

#40 m /94			SIMULATOR SOLUTION (OR DRY GAS)**	NC.	P TEM	AS P (°C):	PAS AC CHECK I	CURACY RESULTS*	CALIBI REQU	RATION JIRED				
DATE	TIME	TEMP (°C)		VALUE		TEST #2 (Optional)		TEST #2			PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEM COMMENTS
0/15/2013	1245	34	12B27-13-5-10-	.100	21		.699			X		Valadez	16071	Printer B.O.
		'	KKF24C				, <u>, , , , , , , , , , , , , , , , , , </u>							
					-		_					: 1		
												:		
			Prepared by:	_										
			Douglas C. Talbot									П		
			02-27-2012									!		
			Expires on:									1		
			02-27-2014									.1		
												1 1		
												:		
								-			-	, ,		
										_		-1		
												1		
									1			t i I i		
												1		
				_								11	-	
				_								()		
								-				1		
		-									-	'		
									_					
												:1 :		
												ı		·
_				_								11		

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#30

CHP 202K (Rev. 8-08) OPI 051

•••				· · · · · · · · · · · · · · · · · · ·	
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	889/

to the second of	r Jana sanata	AS D	EVICES SHALL BE (NOWED THE STREET OF	al moved one to entreprise part	PER PROCESSAL SECTION AND	SECRETARY NO PROPERTY STATE	deco successiones	APLEACHMENT OF THE PARTY OF THE	m pic Sanaharbilikani-silikani	U IEƏIƏ	, WINCHEVER	OCCURS F	
			SIMULATOR SOLUTION (OR DRY GAS)**	ON.	P.	AS P.(°C)	PAS AC CHECK I	CURACY	CALIB				English of Language	100 TACK
		2000			1 EIVII	(.6)	CHECKI	KESULIS Tale	REU	JIKEU	PAS	And the second s		
50.77	TIME	TEMF	LOT NO.	VALUE	TEST	TEST#2	TEST#1	TEST#2	VEG	t i	RETEST	AND THE RESERVE AND THE PARTY OF THE PARTY O		REPAIRS/PROBLEMS/
DATE					Harrist Anna Contract	(Ориопаі)	Albania misteriori de la companione de l	(Фриопаі	YES	Service Transport Like	KESULIS	all the second responsibility of the second r	LD. NO.	The Control of the Co
10/15/2013	1822	54	12B27-13-5-10-	.100	ಖ		.105			X		Valadez	16071	Printer B.O.
			KKF24C					:	_					
												1.,		
		_	Prepared by:									*		
			Douglas C. Talbot									. 11		
			02-27-2012											
			Expires on:									1.1		
			02-27-2014					i.				• 1		
												!		
												:		
												. i		
												• 1		
												1		
												!		
												!		
	_											T T		
										-		·		
									-			i i		
												. ; I j		
												' '		

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#31

AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO. South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV

Consessed assess to acres 1865 by D	PAS L	DEVICES SHALL BE C		The second of the behavior to select the second		EVEKY 1	IU DAYS (JK EV	ERY 1	50 IESTS	, WHICHEVER O	JUKS F	IKSI.
		SIMULATOR SOLUTION	, NC	P	AS	PASAC	CURACY	CALIB	RATION				
	7 July 2	(OR DRY GAS)**		TEM	P (C)		RESULTS*.	为一个人的	UIRED.	PAS			and the second
	TEM	P LOTNO.			TEST#2		TEST#2			PAS RETEST			REPAIRS/PROBLEMS/
a. Chancal September September 126 [167] Bush	TIME (°C)	At 1 hour personal continue trade for 1 miles and 1 miles and 1 miles	VALUE	1ES1#1	∔ (Optional)	LESL#1	(Optional)	YES	NO .	RESULTS	M Nashandarah dalah darah at 2 dan sasar 12 dan sa	LD, NO.	COMMENTS
10/15/2013		12B27-13-5-10-	.100					-		_	Valadez	16071	Printer B.O.
		KKF24C									<u> </u>		
										_	!		_
							_			_	: :		
		Prepared by:	_										
		Douglas C. Talbot											
		02-27-2012									* 1		
		Expires on:				1 /							<u> </u>
		02-27-2014				/\(\)	V . (
											· · · · · ·		
				_									
								$^{\wedge}$	7				
							AAA	18		IN		_	
				_			001		\ <u>i</u>				
											1		
												 -	
_				_							, 1		
	_												
	_										* * * * * * * * * * * * * * * * * * * *		
										_	11		
				_		-	_						
											, i		

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

COORDINATOR NAME

AREA NO.

CHP 202K (Rev. 8-08) OPI 051

AREA NAME

32

PAS SERIAL NO.

: |

1.1

South Los A	ingeles		530	Officer Bri	ian Flick		15063	1	Intoxi	meters I	nc./Alco-Se	ensor IV	186	76
	F	AS D	EVICES SHALL BE C	HECKED	FOR ACC	CURACY	EVERY 1	0 DAYS	OR EV	ERY 1	50 TESTS	, WHICHEVER OC		
			SIMULATOR SOLUTION (OR DRY GAS)**	ONE SE	P TEM	AS P.(°C)	The Arts worth the contract to the	CURACY RESULTS*	200 6000 000 000 000 000	The second second				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	16 Add 0 87 20 20 10	FTEST #2 (Optional)	The Park of Land	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	@PERATOR	LD: NO.	REPAIRS/PROBLEMS/ COMMENTS
10/18/2013	1538	34	12B27-13-5-10-	.100	22		.093			\otimes		Flick	15063	Printer B.O.
			KKF24C									+ I		
												11		
												1.		
			Prepared by:									1		
			Douglas C. Talbot											
<u></u>			02-27-2012											
			Expires on:									1		
			02-27-2014									* 1		

I.D. NUMBER

PAS MAKE/MODEL

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

CHP 202K (Rev. 8-08) OPI 051 AREA NAME AREA NO. COORDINATOR NAME I.D. NUMBER

South Los Angeles 530 Officer Brian Flick PAS MAKE/MODEL Intoximeters Inc./Alco-Sensor IV PAS SERIAL NO.

15063

	PAS D	DEVICES SHALL BE C	HECKED	FOR ACC	CURACY	EVERY 1	0 DAYS	OR EVE	ERY 15	0 TESTS	, WHICHEVER C	CCURS F	IRST.
See that a		SIMULATOR SOLUTION (OR DRY GAS)** LOT NO.	DN.	P TEM	AS P.(°C)	PAS AC	CURACY RESULTS*	CALIBR REQU	ATION IRED	en ben PAS			
DATE TIM	TEMI	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)) TEST#1	TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	I.D. NO	REPAIRS/PROBLEMS/ COMMENTS
10/15/2013 /3/3	2 34	12B27-13-5-10-	.100	20		.104	1		X		Valadez	16071	Printer B.O.
	,	KKF24C									- !		
											ı		
											· i		
		Prepared by:									:		
		Douglas C. Talbot									1		
		02-27-2012											
		Expires on:									- 1		
		02-27-2014									."		
											. 1		
											Lie		
				_							: 1		
										_	· [
											ı		
											. I		
											· I		
											ı		
											1		
											1		
•							-				:		
							-				1		

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8877

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

等似地图75号和68	44/3999***		EVICES SHALL BE C	975.000 47.200 PT 11 5 February	Plants of the second	NEW STREET	ed rans members are market	SACTO SACRAME, INCOMPRISA CO.	dress wast to constitute	wanto water was be				
			SIMULATOR SOLUTION (OR DRY GAS)**	DN .	P TEMI	AS Pr(°C)	PAS AC	URACY ESULTS	CALIBI	RATION				
					LINE CONTRACTOR OF THE PERSON	44500000000000000000000000000000000000	The second second second	经验		2003/3/45	PAS			
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2	TEST#1	TEST #2	VEC	NO	RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
- Thinning Same Single	经济的基础的	MA CONTROLLER	APPLICATION OF CHARACTERISTICS AND APPLICATION OF THE STREET AND APPLICATION OF A STREET AND APPLICATION OF A	#4-14-21-4-05-07-34-0-0-1-0-1-0-1-0-1-0-1-0-1-0-1-0-1-0-1-	Club Brothells, somthet the self-co	ДОрнован	SCIT-No-STATE AND AND AND AND ADDRESS.	(Spironary	ILO.	4, \$1, \$2, \$2, \$2, \$2, \$2, \$2, \$2, \$2, \$2, \$2	TAL SOLING	・ というなどのできた。	新世(本, 小田) (A-で)かったりから)	Line of an exercise residence and detection of the service
10/15/2013	1390	57	12B27-13-5-10-	.100	20		,105			× _		Valadez	16071	Printer B.O.
_			KKF24C	_					_	-			-	
													_	
							,							
						_						• 1		
			Prepared by:									• 1		
			Douglas C. Talbot	_		_						1		
			02-27-2012						_				_	
			Expires on:											
			02-27-2014						_					
												1		
				_	_									
				_								.:		
												:	_	
												I		
												. 1		
												1		
_														
				_								1.4		
				_								E 1		
												.!		
												1.1		
	_				_	_								

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



					<u> </u>	
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		18615

			SIMULATOR SOLUTION (OR DRY-GAS)**	ON '	P TEM	AS P (°C):	CHECK	CURACY RESULTS*	REQU	RATION JIRED				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/15/2013	1316	34	12B27-13-5-10-	.100	21		.101			χ		Valadez	16071	Printer B.O.
		1	KKF24C											
												1 /	-	
					_									
			Prepared by:									1		
			Douglas C. Talbot									,		
			02-27-2012											
			Expires on:									:		
			02-27-2014									i		
								_						
										_				
												1		
												.:		
												- 1		
												1		
												1 1		
		_										1		
												? [- 1		
												1.1		

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#37

		_				
						_
REA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18624	

			SIMULATOR SOLUTION (OR DRY GAS)***	NC	P	AS P∹(°C)	PAS AC	CURACY	CALIB	RATION				
		TEMP				TEST#2		TEST#2			PAS RETEST			REPAIRS/PROBLE
DATE	TIME	(°C)	LOT NO:	VALUE	TEST#1	(Optional)	TEST #1	(Optional	YES	NO	RESULTS	OPERATOR	I.D. NO.	COMMENTS
)/15/2013	1312	34	12B27-13-5-10-	.100	21		.103			X		Valadez	16071	Printer B.O.
			KKF24C		,									
	•		Prepared by:									!		
			Douglas C. Talbot									i i		
			02-27-2012											
			Expires on:											
			02-27-2014	,								+ 1		
												ı		
						·								
												i i		
						· <u>-</u>						1		
											_			
												1		
												1		

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#38

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
SOUTH LOS Angeles

AREA NO. COORDINATOR NAME
SOUTH LOS Angeles

AREA NO. COORDINATOR NAME
SOUTH LOS Angeles

AREA NO. COORDINATOR NAME
SOUTH LOS Angeles

AREA NO. COORDINATOR NAME
SOUTH LOS Angeles

AREA NO. COORDINATOR NAME
SOUTH LOS Angeles

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR NAME
SOUTH LOS ANGELES

AREA NO. COORDINATOR

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**		TEM	AS (°C)	CHECK	CURACY RESULTS*	REQ	UIRED				
DATE	TIME	TEME (°C)	LOTNO.	Para Asia	Parks and the same of the same	TEST #2 (Optional)	TEST #1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/15/2013	1306	34	12B27-13-5-10-	.100	21		./11		$\boldsymbol{\chi}^-$			Valadez	16071	Printer B.O.
			KKF24C									:		
					_			_						
									_			-1	<u> </u>	
			Prepared by:	_	_									
			Douglas C. Talbot			_								
			02-27-2012	_								:		
			Expires on:											
			02-27-2014											
												1		
												» I		
												I		
												11		
_												* I		

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#39

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER		PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	83030

. No. 10 There ships	r Le sièce redire	A9 D	EVICES SHALL BE C	HECKEN	ed a for education classic second	actional to the comment	EVERY	IU DAYS	OK EVER	(Y 150 IEST	S, WHICHEVER OC	CURS F	IRSI.
			SIMULATOR SOLUTION	ON -	P	'AS	PASAC	CURACY	CALIBRA	FION			
	200		(OR DRY GAS)**		TEM	P: (°C)	到海岸市的海洋	Property and Company	REQUIR				
		TEME				TEST #2		TEST #2		PAS RETEST			REPAIRS/PROBLEMS/
DATE	TIME	(°C)	LOT NO.	VALUE	TEST#1	(Optional)	TEST#1	(Optional)	YES	NO RESULTS	OPERATOR	LD. NO.	
10/15/2013	1301	34 [°]	12B27-13-5-10-	.100	2/		.103		 ×	(Valadez	16071	Printer B.O.
			KKF24C										
											1		
											. 11		
			Prepared by:										
			Douglas C. Talbot										
			02-27-2012										
			Expires on:										
	_		02-27-2014								**		
		_											
											* 1		
											• 1		
							_						
							_				. 1		
											11		
											i l		
											11		

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18697

			SIMULATOR SOLUTION SOLUTION (OR DRY GAS)**	DN.	P. TEMI	AS P (°C)	PAS AC CHECK F	CURACY RESULTS*	CALIBI REQU	RATION JIRED			12.0	
DATE	TIME	TEME		VALUE		TEST.#2	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/15/2013	1304	34	12B27-13-5-10-	.100	21		./0/	:		X	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Valadez	16071	Printer B.O.
	, ,		KKF24C					:						
												'		
			Prepared by:											
			Douglas C. Talbot									. 1		
			02-27-2012											
			Expires on:											
			02-27-2014											
							_							
												:		
												,		
												11		

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

CHP 202K (Rev. 8-08) OPI 051

#ya

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18762

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULAFOR SOLUTION (OR DRY GAS)	400	- TEM	AS P=(°C)	CHECK	CURACY RESULTS*	REQ	JIRED :					
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST#2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	1.D: NO.	REPAIRS/PROBLEM COMMENTS	
0/15/2013	1236	34	12B27-13-5-10-	.100	20		1/00	:	,	~		Valadez	16071	Printer B.O.	
			KKF24C												
			Prepared by:												
	_		Douglas C. Talbot												
			02-27-2012												
			Expires on:												
	_		02-27-2014												
					-										
										_					
					_										
_							_				_				
								_							
				_			_								
											<u> </u>				
								_			_				
					_										
		_											_		
	_										_				
		_						_				- '	_		
						_									

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#43

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18766

			SIMULATOR SOLUTION (OR DRY GAS)**	ON.		AS P (°C)	PAS ACCURACY CALIBRATIO CHECK RESULTS* REQUIRED			RATION JIRED				
DATE:	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NÖ	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
10/15/2013	1238	34	12B27-13-5-10-	.100	21		.095			~		Valadez	16071	Printer B.O.
	, 0	,	KKF24C		,									
														_
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012											
			Expires on:	, <u> </u>		_								
			02-27-2014											
														_
									_			_		
								_	_					
_												: 1		
						_			,					
				_										

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#44

CHP 202K (Rev. 8-08) OPI 051

AREA NAME AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles 530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18691

			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEMI	AS P-(°C)	PAS AC CHECK F	CURACY ESULTS*	CALIBI REQI	RATION JIRED				
DATE	TIME	TEMP (°C)		VALUE	TEST #1	TEST #2* (Optional)	TEST #1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS		I,D. NO.	REPAIRS/PROBLEM COMMENTS
0/15/2013	1208	34	12B27-13-5-10-	.100	21		106			X		Valadez	16071	Printer B.O.
			KKF24C											
		_	Prepared by:						_					
			Douglas C. Talbot	_			_					'		
			02-27-2012										_	
			Expires on:				_							
		_	02-27-2014		_									
		-		_										
		-				-		_					_	
											_			
											_			
		-											-	
		-										<u> </u>		
						_								
		-			_								_	
										_				
_														
_				_										
										_		* 1		
		_				_							_	
		_				<u> </u>								

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#45

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	17990

tropped with the second	F.A.		VICES SHALL BE C	Manhousto Prodressora		FORAC I	wift Switchister, Wischer Technical Communication Communic	and the second s	of State of the St	Charles and College	F. 37 and a second 15 and a second	, WITHCHEVER OC	CUKS FI	ROI.
			SIMULATOR SOLUTION (OR DRY GAS)**	ON .	P	ÁS ⊇ (°C)	PAS AC	CURACY RESULTS*	CALIBI	RATION JIRED				
			(ON DIVI GAS)	Part Services	I-EIVH		A CONTRACTOR OF THE PARTY OF TH		7.00	икер.	PAS		122	
DATE	TIME	EMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2	TEST#1	TEST #2	VEQ	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS COMMENTS
10/15/2013		VO18.0-2 7- 4111	12B27-13-5-10-	.100		(Cpriones)		Copuoman			, ALOUL IC	Valadez	16071	Printer B.O.
.0/13/2013		_	KKF24C	.100								Valadez	10071	Fillier B.O.
						_	_						_	
	-	I	Prepared by:				_							
			Douglas C. Talbot					_						
			02-27-2012				_		-					
		F	Expires on:			/(1/	7						
			02-27-2014				10							
					_		<u> </u>	·						
										_				
		_						î		_				
									$\setminus \setminus$	R.	1/1			
								+	$/\langle \cdot \rangle$	M		1 1 1	_	
						_				_	1 01			
		-	·				_							
								_						
				_										
TC (1 1:			(1) 0.010											

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#46

AREA NAME

AREA NO. COORDINATOR NAME

I.D. NUMBER

PAS MAKE/MODEL

PAS SERIAL NO.

South Los Angeles

Date of the coordinator name of the coordinator

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**		P TEM	? (°C) :- ¸	CHECK	CURACY RESULTS*	REOL	RATION JIRED				
DATE	TIME	TËMP (°C)	STATE OF THE PARTY	VALUE	TEST#1	TEST #2 (Optional)	TEST #1	TEST#2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/15/2013	[307	34	12B27-13-5-10-	.100	21		.099			X		Valadez	16071	Printer B.O.
			KKF24C											
									_					
			Prepared by:								_			
		1	Douglas C. Talbot		_				_					
			02-27-2012			_								
			Expires on:			_					_		,	
			02-27-2014											
						_								
										. —				
								_			_			
	_													
_				_	_			_						
	-													

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#5U

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I,D, NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	41486

Table 1	SIMULATOR SOLUTION (OR DRY-GAS)**				- P TEMI	PAS ACCURACY CALIBRATION REQUIRED				ED PAS			en en en en en en en en en en en en en e	
DATE	TIME	TEME (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES.	NO	PAS RETEST RESULTS	ØPERATOR .	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
10/15/2013	1305	34	12B27-13-5-10-	.100	21		105			X	_	Valadez	16071	Printer B.O.
			KKF24C											
				_			_	·						
			D 11						_					
	_		Prepared by:								-			
_			Douglas C. Talbot 02-27-2012			_	_							
	_		Expires on:	_			_	-	t					
			02-27-2014											
			02 27 2011	_					-					
					-									
	-													
				_										
					_	_								
					_									
							_						-	
				<u> </u>	_		_							
	_	_				_			_				_	
						_				-				

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#51

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	41495

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	ON.	P JEM	AS P (°C)	PAS AC	CURACY PESULTS:	CALIBI REQI	RATION JIRED			N. C. C. C. C. C. C. C. C. C. C. C. C. C.	
DATE	TIME	TEMP	A THE COUNTY OF	VALUE		TEST #2		TEST #2			PAS RETEST RESULTS		f.D. NO.	REPAIRS/PROBLE COMMENTS
/15/2013	1153	34	12B27-13-5-10-	.100	20		.095			X		Valadez	16071	Printer B.O.
			KKF24C											
	_		Prepared by:											
			Douglas C. Talbot									·		
			02-27-2012											
_			Expires on:											
			02-27-2014							_				
				_		_								
	<u> </u>													
										_				
											_		ļ. —	
													-	
		_		_		_							 	
_		_						·						
						_					_			
			· · · · · · · · · · · · · · · · · · ·				_							
_								_						
-				_		_			_			-	_	

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	41502
	===	UEQUED EQD 4 QQUD4 Q\(EVEDV 40 D 43/0 /	D EVEDY 450 TEATA MUNICIPAL	TYPE COOLING FIRST

		SIMULATOR SOLUTION (OR DRY GAS)**			AS P_(°C)	PAS AC CHECK F	CURACY RESULTS*	CALIBI REQI	RATION JIRED				700 (200 (200 (200 (200 (200 (200 (200 (
DATE	TEN TIME (°C) LOT NO.	VÄLÜE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	* OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/18/2013	1338 34	12B27-13-5-10-	.100	24		.096	:		X		Flick	15063	Printer B.O.
		KKF24C											
					_	_							
		Prepared by:											
		Douglas C. Talbot											
		02-27-2012											
		Expires on:											
		02-27-2014								_			
										_			
					_	_	_						
					_								
					_								
				_	_					_			
							_						
										_			

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#53

AREA NAME
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

AREA NO.
South Los Angeles

A

			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P. (°C)	CHECK	ESULTS*	REQU	RATION JIRED	PAS			
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/15/2013	1152	34	12B27-13-5-10-	.100	21		.095	_		X		Valadez	16071	Printer B.O.
			KKF24C	<u> </u>										
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
					_									
						_								
		_												
							_							
		_												
		_										<u> </u>		
							_	_						
								_	_					
	-													

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

SGT.

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8879

the Time improve and the	Av 5-685-00-10516	A3 D	COLUMN TO SERVICE DE LA CONTRACTOR DE LA	JTION PAS PASACCURACY CALIBRATION						, Whichever oc	CURS F			
			SIMULATOR SOLUTI (OR DRY GAS)**	ON.	P	AS P (°C).	PAS AC	CURACY RESULTS*	CALIBI	RATION				
					I-EIVII		CHECK	ESULIS.	KEQI	JIKED	PAS			
D. T.		TEMP (°C)	LOTING.			TEST#2		TEST#2			RETEST	100		REPAIRS/PROBLEMS/
DATE	TIME	A 24. 1	The state of the s	Office a countries of the second con-	大学的会の地震などのようかの	(Optional)	TEST#1	(Optional)	YES	Company Committee	RESULIS	OPERATOR	LD. NO.	COMMENTS
10/15/2013	1154	34	12B27-13-5-10-	.100	<u>a/</u>		.102			X		Valadez	16071	Printer B.O.
			KKF24C											
					_									
<u>.</u>			· .		_									
_													ļ <u> </u>	
			Prepared by:						_					
			Douglas C. Talbot											
			02-27-2012			,								
			Expires on:											
			02-27-2014										_	
								·						
_						_								
								_						
				_										
	_			_	_	_								
				. 2.1			*			1.				

^{*} If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

^{**} If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.