

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	
	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8501	

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	ON .	P. TEMI	AS P (°C)	PAS AC CHECK F	CURACY RESULTS*	CALIBE REQU	RATION JIRED	Section 1			
DATE	TIME-	TEMP (°C)	ÉOT NO.	VALUE	TEST#1	TEST#2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	i.D. NO:	REPAIRS/PROBLEMS COMMENTS
0/23/2013	1341	34	12B27-13-5-10-	.100	20		.098	1		×		Valadez	16071	Printer B.O.
			KKF24C								-			_
			Prepared by:								-			
-			Douglas C. Talbot											
			02-27-2012	,										
			Expires on:											
			02-27-2014					ı						
								ı						_
								1						
												•		_
			_					1						_
		1												
								ı						
				_				ı						
***				-				1						

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL

## PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG



CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18780

			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P (°C)	A STATE OF THE PROPERTY.	CURACY RESULTS*	and the second second	RATION JIRED	8.2 de 22.5 2.5 de 22.5 3.5 de 22.5 3.5 de 22.5			
DATE	TIME	TEMP	LOT-NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1339	34	12B27-13-5-10-	.100	20		./00			<b>×</b>		Valadez	16071	Printer B.O.
			KKF24C									-		
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012					·						
			Expires on:											
			02-27-2014					ı						
			V2 21 2V1 1											
														_
												_		-
								ı						
														_
										,				
				•				:						
			_					1						
					-							_		
								I						
								I						
								I						
								1				_		
								I						

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8546

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	ON:		AS P (°C)	PAS AC CHECK T	CURACY RESULTS*	CALIBI REOL	RATION JIRED	PAS			
DATE	TIME	TEMP (°C)	LOT NO	VALUE	TEST#1	TEST #2 (Optional)		TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	EÐ: NO.	REPAIRS/PROBLEMS COMMENTS
.0/23/2013	1956	34	12B27-13-5-10-	.100	20		,099	ı		X		Valadez	16071	Printer B.O.
		•	KKF24C	_										
						_								
			Prepared by:					1						_
			Douglas C. Talbot					1						
			02-27-2012											_
			Expires on:					ı						
			02-27-2014											
														_
			_											
			_					i						
			· -	_										_
			-										-	
								I				_		
			_					1						_
								I						
				-										

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#4

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	82659

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)***	ÐN.		AS P-(°C)	PAS AC CHECK I	CURACY RESULTS*	CALIBE REQU	RATION JIRED	Company of the compan			
DATE	TIME	TEMP (°C)	EOT NO.	VALUE	TEST #1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1333	34	12B27-13-5-10-	.100	20		.105	ı		X		Valadez	16071	Printer B.O.
			KKF24C											
			_											
_														_
_			Prepared by:					ı						
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014					1						
								l					,	
								1						
								ı						
								ı						
								ı						
								ı						
								ı					-	
_								ı						
			_					i						
								1						
								ı			_			

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).



CHP 202K (Rev. 8-08) OPI 051

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
South Los Angeles

AREA NO. COORDINATOR NAME
1.D. NUMBER
15063

PAS MAKE/MODEL
Intoximeters Inc./Alco-Sensor IV

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	ON		AS P (°C)	PAS AC CHECK I	CURACY RESULTS*	CALIB REQ	RATION UIRED	PAS			
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST#2 (Optional)	TEŞT#1	TEST#2 (Optional)	YES	МО	RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013			12B27-13-5-10-	.100								Valadez	16071	Printer B.O.
			KKF24C					1						
			Prepared by:				4 1 2		,	$\gamma$				
	}		Douglas C. Talbot				$\Lambda \mathcal{M}$	) (	12	J				
			02-27-2012					I						
			Expires on:				i	(1)	K		7			
			02-27-2014				(	$\mathcal{M}^{\mathcal{C}}$	10	O'				
								1						
								1						
								1						
								1						
								I						

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).



CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	(a)
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	<i>δ</i>	.80

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	ON		AS P (°C)	PAS AC CHECK F	CURACY RESULTS*	CALIBI REQI	RATION JIRED				
DATE	TIME	TEMP	ŁOTNO:	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1337	34	12B27-13-5-10-	.100	20		.103	ı		<b>X</b>		Valadez	16071	Printer B.O.
	,	•	KKF24C											
							<u></u>							
								!						
			Prepared by:					ı				_		
			Douglas C. Talbot	_				:						
			02-27-2012					ı						
			Expires on:					ı						_
			02-27-2014			_		!						
												_		_
								I				_		
			_					ı						
								I I						
			_					ı						
												_		_
								I						
								ı						
								1						_
								I						
			- (1) 0.010					1 121 42		17		1 - 1 - 4		

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).



REA NAME	AREA NO.	COORDINATOR NAME	1.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	~
outh Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor PV		83037

			SIMULATOR SOLUTION (OR DRY GAS)**	<b>DN</b>	P TEM	AS: P (°C)	PAS AC CHECK I	CURACY RESULTS*	CALIBI REQU	RATION JIRED		450		- 10 miles
DATE	TIME	# . Aud.)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST #1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1324	34	12B27-13-5-10-	.100	20		.098	1		~		Valadez	16071	Printer B.O.
			KKF24C					1						
_								i						
								1				-		
			Prepared by:					1				_		
			Douglas C. Talbot		_	_		:						
			02-27-2012					1						
			Expires on:					!						
			02-27-2014	_										
_														
								<u> </u>						_
												_		
_			_	_										
								I				_		
					_			-						
_														
_								I						
-														
_								i						
				_				l						
-								i			_			
-														

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).



AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	0110	
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		8600	-

			SIMULATOR SOLUTION (OR DRY GAS)**	ON-	P TEM	AS P (°€)	PAS AC CHECK F	CURACY RESULTS*	CALIBE REQU	RATION JIRED				
DATE	TIME	TEMP (°C)		VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
0/23/2013	1334	34	12B27-13-5-10-	.100	20		,/00	İ		人		Valadez	16071	Printer B.O.
			KKF24C											
						-		1						
				_				1						
			Prepared by:											
			Douglas C. Talbot					1						
			02-27-2012					:						
			Expires on:											
			02-27-2014											
								_						
								1						
								.1						
_								  -						
					_									
_					_			-						
								-						
			· ·										`	
_											_			
_							_				_			
_								1			_			
							_							

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#9

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	82957

			SIMULATOR SOLUTION (OR DRY GAS)**		ŢEM	AS P (°C)	CHECK	RESULTS*	CALIBR REQU	ATION IRED	PAS			
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	THE STATE OF THE STATE OF	TEST#2 (Optional)	TEST#1	TEST#2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	ID NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1305	34	12B27-13-5-10-	.100	2		.094	1		X		Valadez	16071	Printer B.O.
	•		KKF24C											
								1						
				_										
								1						
_			Prepared by:		_							_		
			Douglas C. Talbot					1						
_			02-27-2012					1						
			Expires on:											
			02-27-2014				_							
								1						
	<del>-</del>							1						
_														
								1						
	· ·							I						
_								1			·			
								!						
_			-			_								
						_						_		
		_												

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



CHP 202K (Rev. 8-08) OPI 051

					,
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	77505

			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P.(°C)	PAS AC CHECK F	CURACY RESULTS*	CALIBI REQL	RATION JIRED		And State of the S		
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
10/23/2013	1324	34	12B27-13-5-10-	.100	20		,099	1		*		Valadez	16071	Printer B.O.
	3.		KKF24C					1						
								1			_			
_										_				
			Prepared by:	_			_	1						
			Douglas C. Talbot					1						
			02-27-2012					1						
			Expires on:								·			
			02-27-2014								٠			
								!						
													_	
								i						
								1						
				_			_							
				_										
								1			_	·		
	_													
								i _						
	_							_						
				_		_	_							
		-					_							
													_	·
								*		_				

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	77479

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P (°C)	PAS AC CHECK F	CURACY RESULTS*	CALIBI REQU	RATION JIRED				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	ÖPERATOR	I.Đ. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1326	34	12B27-13-5-10-	.100	20		.097			X		Valadez	16071	Printer B.O.
			KKF24C											
			Prepared by:											
			Douglas C. Talbot					-						
			02-27-2012											
			Expires on:											·
			02-27-2014											
														,
							1							
					,									
												-		

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	82660

The second secon			SIMULATOR SOLUTI (OR DRY GAS)**		TEMI	Service Control	PAS AC CHECK F	<b>计划编码公司</b>	REQ	RATION JIRED				
DATE	TIME	TEMP (°C)		VALUE		TEST #2 (Optional)	CLASSICAL NOT SELECT	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1321	34	12B27-13-5-10-	.100	20		.097			X		Valadez	16071	Printer B.O.
			KKF24C											
								1						
				_				· -						
			Prepared by:											
			Douglas C. Talbot					i						
			02-27-2012					<u>.</u>						
<u>.</u>			Expires on:					1						
			02-27-2014					<u>.                                      </u>						
						_		1						
								i						
							_	1						
											_			
				-				1						
_							_							
								<u> </u>						
_				_						_				
_								l .						
				_		_		-					-	
						_	_				_		_	
				_				· · ·					-	
		_				_								
-						_								

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#13

AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKEMODEL PAS SERIAL NO. South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV							
South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV	AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	
	South Los Angeles	530	Officer Brian Flick	15063		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	

			SIMULATOR SOLUTIO (OR DRY GAS)**	ON-		AS P. (°C)	PAS AC CHECK F	CURACY RESULTS*	REQ	RATION JIRED			The second secon	
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2, (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1327	34	12B27-13-5-10-	.100	21		104	I		X		Valadez	16071	Printer B.O.
		i	KKF24C		,		•							
								1						
												_		
			Prepared by:									_		
			Douglas C. Talbot	<u> </u>				İ						
			02-27-2012					i				_		
			Expires on:									_		
			02-27-2014											
								1						
								1						
						·		!						
								I						
								<u> </u>						
_														
								I						
								ı						
								I						
								l						
								l						

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#14

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8714

			SIMULATOR SOLUTION (OR DRY GAS)**	DN		AS P=(°C)	PAS ACC	CURACY RESULTS*	CALIBE REQL	RATION JIRED	PAS			
DATE	TIME	TEMP (°C)	LOT NO:	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	122	RETEST RESULTS	OPERATOR	i.d. No.	REPAIRS/PROBLEMS COMMENTS
10/23/2013	1324	34	12B27-13-5-10-	.100	w		.105			X		Valadez	16071	Printer B.O.
			KKF24C											
								1						
					_				_				<del>  -</del>	
			Prepared by:											
			Douglas C. Talbot	<u> </u>				<u> </u>						
			02-27-2012		_			<u> </u>						
			Expires on:					i						
			02-27-2014											
							_							
							_	<u> </u>						
					_	_								
							_	1						
						_								
								<u> </u>						
								<u> </u>						
								<u> </u>			_			
							_							

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8888

	***		SIMULATOR SOLUTI (OR DRY GAS)**	ON		AS P (°C)	PAS AC CHECK F	CURACY ESULTS*	CALIBF REQL	RATION JIRED	The state of the s			
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	d.D. No.	REPAIRS/PROBLEMS COMMENTS
0/23/2013	1309	34	12B27-13-5-10-	.100	21		.101	I		人		Valadez	16071	Printer B.O.
			KKF24C					!						
								I						
	_				_		_	1						
							_	<u> </u>						
	_		Prepared by:			_		i						
			Douglas C. Talbot											
			02-27-2012	_	_			1						
			Expires on:											
			02-27-2014					1						
_								· -						
								i						
								1						
											·			
														<u> </u>
								·						
							_	l						
				_				· _						
								_						
							_							

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

٤	STATE OF CAL	.IFORNIA		
I	DEPARTMENT	OF CALIFORNIA	HIGHWAY	<b>PATRO</b>

				- +				
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER		P.	AS MAKE/MODEL	PAS SERIAL NO.	
South Los Angeles	530	Officer Brian Flick	15063		Iı	ntoximeters Inc./Alco-Sensor IV	8783	

			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P (°C)	PAS AC CHECK F	CURA SESUL	CY CALIB	RATION UIRED	r PAS		The Sheet	
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST#2 (Optional)	TEST#1	TES (Opti	T#2	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS COMMENTS
0/23/2013	13/9	34	12B27-13-5-10-	.100	20		.102	1		X		Valadez	16071	Printer B.O.
		_ *	KKF24C							,				
										·				
							_							
			Prepared by:		_									
			Douglas C. Talbot	_										
			02-27-2012											
			Expires on:											
			02-27-2014		_									
								!						
_														
				_										
								<u> </u>						
								!						

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8265/

			SIMULATOR SOLUTION (OR DRY GAS)**	)N	P. TEMI	AS P (°C)	PAS AC CHECK F	CURACY RESULTS*	REQU	RATION JIRED				
DATE	TIME	TEMP	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST#2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS.
10/23/2013	13/1	34	12B27-13-5-10-	.100	20		, 097	I		X		Valadez	16071	Printer B.O.
			KKF24C					1						
								I						
					_			1						
								1						
			Prepared by:											
			Douglas C. Talbot			_								
			02-27-2012					I I						
			Expires on:					1						
			02-27-2014					İ						
								1						
												,		
								1						
								1						
	_							1						
_								į			_			
_						_					_			
						_		I						
				_				1						
					_		_							

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#19

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	CCAD
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		8810

			SIMULATOR SOLUTION (OR DRY GAS)**	ON.	P TEM	AS P. (°C)	PAS AC CHECK I	CURACY RESULTS*	CALIBI REQU	RATION JIRED	100			
DATE	TIMĚ	TEMP.	EOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I,D. ÑO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1313	34	12B27-13-5-10-	.100	20		.097	1		<b>X</b>		Valadez	16071	Printer B.O.
			KKF24C					I						
								-						
_		_	Prepared by:											
			Douglas C. Talbot					İ	_					
			02-27-2012								_		-	
			Expires on:					ı						
			02-27-2014											
								1			_	·		
							_	!						
								<u> </u>						
				_		<u>.</u>	_	-						
							_							
								1		_				
										-				
				_	_									
					-		_				<u>-</u>			
					-	-				_				

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#20

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	[808]

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

		SIMULATOR SOLUTION (OR DRY GAS)**	ON PAS TEMP (°C)		AS P (°C)	PAS ACCURACY CAL CHECK RESULTS* RI			CALIBRATION REQUIRED				
DATE TIME	TEMF	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
0/23/2013 1954	34	12B27-13-5-10-	.100	20		.100	!		X		Valadez	16071	Printer B.O.
, ,	,	KKF24C					1						
											-		
		-		_		-	1						
		Prepared by:								-			
		Douglas C. Talbot											
		02-27-2012					i						
		Expires on:					1						
		02-27-2014											
_							ı						
							I I						
							<u> </u>						
							1						
			_				<u> </u>						
							<u> </u>						
						_	1						
							<u> </u>						
			-				<u> </u>						
					-		i					_	
			_	_	-		I						

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO,	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	0632

			SIMULATOR SOLUTION (OR DRY GAS)**	NC.	PAS TEMP (°C):		PAS ACCURACY CHECK RESULTS*		CALIBRATION REQUIRED					
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO 3	PAS RETEST RESULTS	OPERATOR .	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
0/23/2013	1959	34	12B27-13-5-10-	.100	25		.69/	1		×		Valadez	16071	Printer B.O.
			KKF24C				,			′				
								1						
			Prepared by:											
			Douglas C. Talbot					1						
			02-27-2012					-						
			Expires on:					i						
			02-27-2014	_				!						
_								1						_
_								!						
_								!						
								1						
		_												
				_				<u> </u>						
_												-		

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#22

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8847

			SIMULATOR SOLUTION (OR DRY GAS)**		AS: ! P (°C)	PAS AC CHECK F	CURACY ESULTS*	REQL	RATION JIRED	DEO.				
DATE	TIME	TEMP (°C)	LOTNO.	_VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	1.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1311	34	12B27-13-5-10-	.100	20		.104			Х		Valadez	16071	Printer B.O.
			KKF24C											
											_			
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012					-						
			Expires on:							_				
			02-27-2014											
											_			
_														
								_						
				_				<u> </u>						
_														

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



				<u> </u>				_
REA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER		PAS MAKE/MODEL	PAS SERIAL NO.	0-16	_
outh Los Angeles	530	Officer Brian Flick	15063		Intoximeters Inc./Alco-Sensor IV		83873	

			SIMULATOR SOLUTION (OR DRY GAS)**	NC	PAS TEMP (°C)		PAS ACCURACY CHECK RESULTS*		CALIBRATION REQUIRED					
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST#2 (Optional)		TEST #2 (Optional)		NO	PAS REFEST RESULTS	OPERATOR	ED: NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1301	34	12B27-13-5-10-	.100	20		.097			*		Valadez	16071	Printer B.O.
			KKF24C											
_														
			Prepared by:								_			
			Douglas C. Talbot											
_			02-27-2012		<u> </u>									
			Expires on:	_										
_			02-27-2014											
								!						
					-			<u> </u>						
				_				<u> </u>						
	_					_	_	1						
	_			<u>.</u>				<u> </u>						
	_				_	_	_	<u> </u> 						
_						_	_	-  -						
				_										
-								<u> </u>						
				-	_		_							
				-	-			_						
							-							

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#24

AREA NAME
South Los Angeles
AREA NO. COORDINATOR NAME
LD. NUMBER
PAS MAKE/MODEL
PAS SERIAL NO.
SUMBER
Intoximeters Inc./Alco-Sensor IV

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**			AS P=(°C)	PAS AC CHECK F	CURACY ŒSULTS*	CALIBR REQU	ATION IRED			relation	
DATE	TIME	TEMP (°C)	LOT.NO.	VALUE	TEST#1	TEST #2 (Optional)	A TALL S. STATE BALLING	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
0/23/2013	1307	34	12B27-13-5-10-	.100	20		102	!		X		Valadez	16071	Printer B.O.
		*	KKF24C											
				_				ļ						
					_									
			Prepared by:					ļ. <u>-</u>						
			Douglas C. Talbot					<u> </u>						
			02-27-2012	_									-	
			Expires on:		<u> </u>									
			02-27-2014											
								! I						
						_								<u> </u>
		-	,			_								<u> </u>
													<u> </u>	
								'						
				_	_		_							
_				_									<del>-</del>	
				_				I						
	_				_						_			
				_				-						
_				_		_								

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).



CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	77591

		in the second	SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	PAS TEMP (°C)		CURACY RESULTS*	CALIB REQ	RATION UIRED				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	ÖPERATOR	LD. NO.	REPAIRS/PROBLEMS COMMENTS
10/23/2013	1303	34	12B27-13-5-10-	.100	20		.097			X		Valadez	16071	Printer B.O.
			KKF24C											
			Prepared by:											_
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
	,		02-27-2014											
								l						
														<u> </u>
								1						
								1		_		-		
							_	l I						
												,		
							· -							
			-				_							_

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#56

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	0000	
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		8860	

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS. WHICHEVER OCCURS FIRST.

		SIMULATOR SOLUTION (OR DRY GAS)**			PAS TEMP (°C)		PAS ACCURACY CHECK RESULTS*		REQUIRED			S		
DATE	TIME	TEMP (°C)	LOTINO	VALUE	TEST#1	TEST.#2 (Optional)	TEST#1	TEST #2 (Optional)		NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	41 JUNE 19 JUNE 20 SECULATION DE CHARLE
10/23/2013			12B27-13-5-10-	.100				,				Valadez	16071	Printer B.O.
			KKF24C											
			<u> </u>	_			_	!					_	
									_ <del>-</del>	_				
			Prepared by:					i		,				
_			Douglas C. Talbot			_	À	MT		_			_	
			02-27-2012					<u> </u>	1					
			Expires on:			_			•	_				
			02-27-2014			_				Kt	$\mathcal{X}$			
_				_					1	<i>y</i> ()(	٠ - ر			
			_		_									
-			<u> </u>	_				-						
_	_				_									
					_		<u> </u>							
-												_		
								<u> </u>			_			

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	17573
					<del></del>

			SIMULATOR SOLUTI (OR DRY GAS)**	P TEM	PAS TEMP (°C)		PAS ACCURACY CALIBRATION CHECK RESULTS* REQUIRED			PAS				
DATE	TIME	TEMP (°C)	LOT NO	VALUE	TEST,#1	TEST #2 (Optional)	TEST#1	TEST#2 (Optional)	YES	ŃΟ	RETEST RESULTS	OPERATOR	ED. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013			12B27-13-5-10-	.100								Valadez	16071	Printer B.O.
	_		KKF24C		_									
			Prepared by:	_	_		ا الم		1	7				
			Douglas C. Talbot				NIC	1	11	$\bigcup$				
			02-27-2012						•					
			Expires on:					$\perp$ / :	1	د, ا	1			
			02-27-2014	_					$) \cup$	U				
					_									
	_													
						_								
	_			_		_								
						_								
					_									
					_									
				_	_			<u> </u>						
_					<u> </u>									

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#28

<b>CHP 202K</b>	(Rev. 8-08)	OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8300 1

			SIMULATOR SOLUTI (OR DRY:GAS)**	ON	P TEM	AS. P. (°C)	CHECKE	CURACY RESULTS*	CALIBF REQU	RATION JIRED		PAS		
DATE	TIME.	TEMP	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1251	34	12B27-13-5-10-	.100	21		.099	<u> </u>		X		Valadez	16071	Printer B.O.
			KKF24C		_		•							
			Prepared by:	_										
			Douglas C. Talbot	-										
			02-27-2012					-				_		
			Expires on:											
			02-27-2014											
								İ						
				_										
					_									
				_			_				_			
<del>-</del>				<u> </u>	<u> </u>									
					_				-					_
					-									
											_			
				_										
								1.1		1.6	54 0 100			

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	889. /

		SIMULATOR SOLUTION (OR DRY GAS)**				PAS TEMP (°C)		ESULTS*					Personal Property of the Personal Property of	
DATE	TIME	TEMP (°C)		VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1301	34	12B27-13-5-10-	.100	20		.107			X		Valadez	16071	Printer B.O.
		3	KKF24C										_	
			Down and Law											
			Prepared by:  Douglas C. Talbot										-	
			02-27-2012			_								
		<u>-</u>	Expires on:		_		_							
		_	02-27-2014							_				
			322/2011											
		_		_										
											_			
_								 						
							_							
														·
				_										
·				_			_				_			
_							<del>-</del>						-	

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#31

AREA NAME AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO.  South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV							
South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV	AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	
	South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		

		SIMULATOR SOLUT (OR DRY GAS)**		TEMP_(°C)			REQU	RATION JIRED		S			
DATE	TIME	TEMP. (°C) LOT NO.		TEST#1	TEST#2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS		LD. NO.	REPAIRS/PROBLEMS COMMENTS
0/23/2013		12B27-13-5-10-	.100				į				Valadez	16071	Printer B.O.
		KKF24C											
				·		12	<u></u>						
				_		D.	<b>ν</b> .						
						-							
		Prepared by:											·
		Douglas C. Talbot											
		02-27-2012											
		Expires on:											
		02-27-2014					į					-	
											_		
													_
_													
													<u> </u>

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#32

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18696

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

	4.4		SIMULATOR SOLUTION (OR DRY GAS)**	DN .		AS P (°C)	PAS AC CHECK F	CURACY RESÜLTS*	CALIBI REQI	RATION JIRED				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)		NO	PAS RETEST RESULTS	OPERATOR	I.D. NO	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013			12B27-13-5-10-	.100				I				Valadez	16071	Printer B.O.
			KKF24C											
_			Prepared by:			A 1	4							
_			Douglas C. Talbot			///	/							
			02-27-2012					- 1	- A					
			Expires on:				100	Kr	YU					
			02-27-2014				00	7.00						
								<u> </u>						
								<u> </u>			_			
								<u> </u>						
								<u> </u>				_		
											_			
	_							_			_			
				_	_		_							
											_			
				. 6.1	1 1 6			144 /*		17				

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).



AREA NAME AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO. South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV

	F	AS D	EVICES SHALL BE O	HECKED	FOR AC	CURACY	EVERY 1	0 DAYS	OR EV	ERY 15	50 TESTS	, WHICHEVER O	CCURS F	RST.
			SIMULATOR SOLUTI (OR DRY GAS)**	ON	P TEM	AS P (°C)	PAS AC CHECK F	CURACY RESULTS*	CALIBE REQU	RATION JIRED				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD_NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1244	34	12B27-13-5-10-	.100	30		. 104			×		Valadez	16071	Printer B.O.
			KKF24C				,			•				
				_										
· ·			<u> </u>					!						
			Prepared by:											
			Douglas C. Talbot											
	,		02-27-2012											
			Expires on:											
			02-27-2014											
											_			
											_			
								_			_			

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

,						
REA NAME	AREA NO.	COORDINATOR NAME	I D MI IMPER	DAS MAKEMODEI	DAS SERIAL NO	
KEA NAME	AREA NO.	COORDINATOR NAME	I.D. NOWBER	PAS WAREIWODEL	PAS SERIAL NO.	7
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	087	/

			SIMULATOR SOLUTION (OR DRY GAS)**	ON .	P TEM	AS P (°C)	PAS AC CHECK F	CURACY ESULTS*	CALIBI REQI	RATION JIRED				
DATE	TIME	TEMP	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TËST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1252	34	12B27-13-5-10-	.100	2]		./05			+		Valadez	16071	Printer B.O.
		ł	KKF24C		,	_		<u> </u>						
				_										
				_										
	-													`
			Prepared by:					<u> </u>						
	_		Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
				_										
			<u> </u>											
				_	-		<u> </u>							
			_											
			_	_				<u> </u>						
					_									
											. <u> </u>			
					_									

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



CHP 202K (Rev. 8-08) OPI 051

AREA NAME AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO. South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV

			SIMULATOR SOLUTION (OR DRY GAS)**	NC.	P TEM	AS P (°C)	PAS AC CHECK I	CURACY RESULTS*	CALIBI REQI	RATION UIRED				
DATE	TIME	TEMP (°C)	LOT-NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	ÑO	PAS RETEST RESULTS	OPERATOR	LD NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1242	34	12B27-13-5-10-	.100	21		100			×		Valadez	16071	Printer B.O.
			KKF24C		•		1							
							:				_			
_								<u> </u>						
			Prepared by:								_			
			Douglas C. Talbot					<u></u>						
			02-27-2012											
			Expires on:				1							
			02-27-2014				-							
							j							
							_							
							<u> </u>					_		
_											<u> </u>			
							1	<u> </u>						
							1							
							1							
							- !				<u> </u>			
_		_					1			_				
			-				I .						_	
_				-										

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#37

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18626

			SIMULATOR SOLUTI (OR DRY GAS)**	ON		AS P=(°C)	CHECK	CURACY RESULTS*	REQU	RATION JIRED			19000	True
DATE	TIME	TEMP (°C)	ĿŌŦÑO.	VALUE	TEST#1	TEST #2 (Optional)	TEST #1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
10/23/2013	1232	34	12B27-13-5-10-	.100	21		-101			×		Valadez	16071	Printer B.O.
		_	KKF24C											
-														
							!							
			Prepared by:				1							
			Douglas C. Talbot											-
			02-27-2012											
			Expires on:				1							
			02-27-2014											
							1							
				_			-							
				_			1	_				· · ·		
														_
			<u> </u>	-							<u> </u>			
_							• !							
				-			_							
							-							
							!							
_														
_					_		:							

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed calibration shall be performed with a wet bath simulator.

#38

AREA NAME

AREA NO. COORDINATOR NAME

L.D. NUMBER

PAS MAKE/MODEL

PAS SERIAL NO.

South Los Angeles

530 Officer Brian Flick

15063 Intoximeters Inc./Alco-Sensor IV

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	ON.	P TEM	AS P (°C)	CHECK	CURACY RESULTS*	CALIBI - REQU	RATION JIRED				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013			12B27-13-5-10-	.100								Valadez	16071	Printer B.O.
_	_		KKF24C				_							
						A />			. 1	-				
_			Prepared by:			140	i		$\sim$					
			Douglas C. Talbot											
			02-27-2012				1 51	1						
	1		Expires on:				MC	1		-				
			02-27-2014			_				_				
<del>-</del> -														
					-									
_			<u> </u>					i						
_								<u> </u>						
-								<u> </u>	-					
-							_							
			_				_							
					_									
											_			
								_						
								1 101			*1 010			. 0.000 . 0.110)

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#39

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	83030	

			SIMULATOR SOLUTION (OR DRY GAS)**	ON.	P. TEMI	AS P (°C)	PAS AC CHECK I	CURACY RESULTS*	CALIBI REQU	RATION JIRED			Salahan Salahan Salahan	
DATE	TIME	TEMP (°C)	LOT-NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS COMMENTS
10/23/2013	1278	34	12B27-13-5-10-	.100	al		102	i		×		Valadez	16071	Printer B.O.
			KKF24C											
												_		
												_		
			Prepared by:									_		
			Douglas C. Talbot											
			02-27-2012	_										
			Expires on:											
			02-27-2014											
										·				
			_									_		
												_		
			_											
-														
			_									_		
												·		

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#40

							_
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	10100	
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		18698	

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

- 474			SIMULATOR SOLUTION (OR DRY GAS)**	NC		AS P (°C)		CURACY ESULTS*	CALIBI REQU	RATION JIRED		And the second s	Ministration of the Control of the C	
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1230	34	12B27-13-5-10-	.100	21		.102			X		Valadez	16071	Printer B.O.
			KKF24C						_					
			Duan and I have											
			Prepared by:  Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
								<u> </u>						
			-											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).



REA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18762

			SIMULATOR SOLUTION (OR DRY GAS)**	ON		AS ? (°C)	PAS AC CHECK I	CURACY RESULTS*	CALIBI REQU	RATION JIRED				
DATE	TIME	TEMP (°C)	LOT NO.	. VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1933	34	12B27-13-5-10-	.100	21		.102			×		Valadez	16071	Printer B.O.
			KKF24C											
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
•														
					,									

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



					_
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18766

			SIMULATOR SOLUTION (OR DRY GAS)**	NC		AS: P:(°C)	PAS AC CHECK F	CURACY RESULTS*	REQ	RATION JIRED				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	-NO	PAS RETEST RESULTS		LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1223	34	12B27-13-5-10-	.100	21		.097			人		Valadez	16071	Printer B.O.
			KKF24C_											
			Prepared by:											
			Douglas C. Talbot											·
			02-27-2012											
			Expires on:		-									
			02-27-2014											
			-											
			-	_										
												-		
			_									18 T 18 T 1		

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

theff

				·			
			<del></del>	 			
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	10101	
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		1867/	

			SIMULATOR SOLUTI (OR DRY GAS)**	, MC		AS <sub>e</sub> (°C)	PAS AC CHECK F	CURACY RESULTS*	CALIBI REQL	RATION JIRED				
DATE	TIME	TEMP	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST#2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	147	34	12B27-13-5-10-	.100	21		.105			*		Valadez	16071	Printer B.O.
			KKF24C											
							,							
			Prepared by:		•								-	_
			Douglas C. Talbot											
			02-27-2012										ï	
			Expires on:			·								
			02-27-2014											
														,
									_					
			,											
			· · · · · · · · · · · · · · · · · · ·					-			<del>-</del> -			
												_		

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#45

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	17990

			SIMULATOR SOLUTION (OR DRY GAS)**	ON		AS P (°C)	PAS AC CHECKT	CURACY RESULTS*		RATION UIRED				
DATE	TIME	TEMP		VALUE	TEST#1	TEST#2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013			12B27-13-5-10-	.100								Valadez	16071	Printer B.O.
			KKF24C								-			
			_											
							2							
			Prepared by:				<i>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</i>	<i>U</i> .				_		
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
•														
_														
														-

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

DEPARTMENT OF CALIFORNIA HIGHWAY PATROL

# PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG CHP 202K (Rev. 8-08) OPI 051

#46

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	,
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18170	1
<del>-</del>	_					

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P=(°C)	PAS AC CHECK I	CURACY RESULTS*	CALIB REQ	RATION UIRED				
DATE	TIME	TEMP	LOT NO.	VALUE	TEST#1	TEST#2 (Optional)		TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1208	34	12B27-13-5-10-	.100	21		.102			X		Valadez	16071	Printer B.O.
			KKF24C		•									
_														-
			Prepared by:									· .		
			Douglas C. Talbot										,	
			02-27-2012											
			Expires on:											
			02-27-2014											
									,					
		_												

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBÉR	PAS MAKE/MODEL	PAS SERIAL NO.	
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	4148	6

	And the second		SIMULATOR SOLUTION (OR DRY GAS)**	ON		AS P: (°C)	PAS AC CHECK F	CURACY RESULTS*	REQ	RATION UIRED				
DATE	TIME	TEMP (°C)		VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPÁIRS/PROBLEMS/ COMMENTS
10/23/2013	1208	34	12B27-13-5-10-	.100	21		106			×		Valadez	16071	Printer B.O.
			KKF24C											
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012											
			Expires on:	1										
			02-27-2014											
												_		
											-			
								<u> </u>						
											·			
				_										
_														
			: (1) 0 010									1.4		

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



				<u>-</u>	
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	41495

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

		SIMULATOR SOLUTION (OR DRY GAS)**			PAS TEMP (°C)		PAS ACCURACY CHECK RESULTS*		CALIBRATION REQUIRED		2000			
DATE	TIME	TÉMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2. (Optional)	TEST#1	TEST #2 (Optional)		NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1201	34	12B27-13-5-10-	.100	ao		.096			X		Valadez	16071	Printer B.O.
			KKF24C											
			_					<u> </u>				_		
				_										
	3		Prepared by:				,						-	
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
		·	02-27-2014									_		_
					_									
												<u> </u>		
			_											
				,										
			,											
			_											
														_
														_
				_										· _
			_											
												_		

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).



41502 AREA NAME COORDINATOR NAME AREA NO. I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO. South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV

DATE TIN		SIMULATOR SOLUTION (OR DRY GAS)**			PAS TEMP (°C)		PAS ACCURACY CHECK RESULTS*		CALIBRATION REQUIRED					
	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	.l.d. no.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1204	34	12B27-13-5-10-	.100	2/		.099			X	7 8 7 980	Valadez	16071	Printer B.O.
	,,,,,		KKF24C								_			
			Prepared by:											
			Douglas C. Talbot								<del>-</del>			
			02-27-2012											
		_	Expires on:							-				
		_	02-27-2014									_		
			_									·		
							_				_			
			_											_
-														
_														

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#53

		<u> </u>			
REA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	82654
		<u> </u>		<del>_</del>	

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST. SIMULATOR SOLUTION PAS PAS ACCURACY CALIBRATION (OR DRY GAS)\*\* TEMP (°C) CHECK RESULTS\* REQUIRED PAS TEMP TEST#2 TEST#2 RETEST REPAIRS/PROBLEMS/ DATE TIME (°C) LOT NO. VALUE TEST #1 (Optional) TEST #1 (Optional) YES NO RESULTS **OPERATOR** COMMENTS LD. NO. 34 12B27-13-5-10-.100 21 1096 10/23/2013 Valadez 16071 Printer B.O. KKF24C Prepared by: Douglas C. Talbot 02-27-2012 Expires on: 02-27-2014

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

SGT.

AREA NAME
AREA NO.
COORDINATOR NAME
I.D. NUMBER
PAS MAKEMODEL
PAS SERIAL NO.
South Los Angeles
530
Officer Brian Flick
15063
Intoximeters Inc./Alco-Sensor IV
8874

		SIMULATOR SOLUTION (OR DRY GAS)**			PAS TEMP (°C)		PAS ACCURACY CHECK RESULTS*		CALIBRATION REQUIRED					
DATE TIME	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO.	PAS RETEST RESULTS	ÖPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/23/2013	1202	34	12B27-13-5-10-	.100	21		.103			$\boldsymbol{\chi}$		Valadez	16071	Printer B.O.
		- 1	KKF24C								_			
						-								
			Duran and have											
			Prepared by:  Douglas C. Talbot		_							_		
			02-27-2012								_			
· <u>-</u>			Expires on:		_									
			02-27-2014											
				_				_						
-														
				_										
			_		_									
				_				_			_	_		
				_										
														_
			_			_								
														_

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.