5675.

CHP 202K (Rev. 8-08) OPI 051

AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO.  South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV							
	AREA NAME . AR	REA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	,
	South Los Angeles 53	30	Officer Brian Flick	15063		88 19	1

# PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST. SIMULATOR SOLUTION PAS PAS ACCURACY CALIBRATION (OR DRY GAS)\*\* TEMP (\*C) CHECK RESULTS\* REQUIRED TEMP TEMP (\*C) LOT NO: VALUE TEST #1 (Optional) TEST #1 (Optional) YES NO RESULTS OPERATOR LD. NO: COMMENTS

	(ORURY GAS)					CHECK RESULTS R		REQUIRED		DAG				
DATE	TIME	TEMP (°C)	LOT NO	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
10/31/2013	1335	34	12B27-13-5-10-	.100	.21		104			×		Valadez	16071	Printer B.O.
	•		KKF24C							- `				
			· · _											
			1								_			
			1					_						
			Prepared by:			_								
			Douglas C. Talbot											
			02-27-2012											
			Expires on:							_			_	
			02-27-2014											
			3						_					
			;	_										
			1										_	
_			1					_						
	_										_			
			1			_								
						_	_		_					
			į											
			1			_			_					
			1									. <u> </u>		
			1	_										
										_				
			1											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#1

	_ :						
AREA NAME		AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	Cerl
South Los Angeles	i.	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		8501

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS. WHICHEVER OCCURS FIRST.

		7 67 T	SIMULATOR SOLUTION (OR DRY GAS)**	P TEM	AS: P: (°C)	PAS ACCURACY C		REQ	RATION UIRED					
DATE	TIME	TEMP (°C)	LOT NO:	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1337	34	12B27-13-5-10-	.100	20		, 098			×		Valadez	16071	Printer B.O.
			KKF24C			_								
			i									_		
			1											
			Prepared by:											
			Douglas C. Talbot					-						
			02-27-2012											
			Expires on:		,									
			02-27-2014											
			5		_			<u>.</u>						
			***											
			¥										`	_
			<u> </u>											
			,											
			1											
			1											
			1											
			-											
			1											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#2

CHP 202K (Rev. 8-08) OPI 051

	i		_			
AREA NAME	· <u>-</u>	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	•	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18785

PAS DEVICES SHALL BE CHECK					UN ACC	CONACT I	to confirm the processing and the process of the pr				Later to consider a final	, WINCHEVER OC	CURS FI	NOI.
			SIMULATOR SOLUTH (OR DRY GAS)**	OR SOLUTION DRY GAS)** TE			PAS AC CHECK F	CURACY RESULTS*	CALIBRATION REQUIRED					100
DATE	TIME	TEMP	LOTNO	VALUE	TEST#1	TEST#2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1337	34	12B27-13-5-10-	.100	19		,/00			*		Valadez	16071	Printer B.O.
1010112010	7.07	•	KKF24C							-				
			1											
			1		_									
			1									_	_	
			Prepared by:		_							_		
			Douglas C. Talbot			_				_				
			02-27-2012											
			Expires on:											
			02-27-2014											
			:											
			:							_				
									_					
			·											
							_						_	
			1										_	
			1											
			-										_	
			-			_								
			i											
							_		_				_	
			<u> </u>											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#3

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	048
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		8546

			SIMULATOR SOLUTION (OR DRY GAS):**	TEMP (°C)		°(°C)	CHECK RESULTS* REQUIRED				PAS			
DATE	TIME	TEMP (°C)	LOTNO:	VALUE	1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS REJEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
0/31/2013	1341	34	12B27-13-5-10-	.100	21		./0/			X		Valadez	16071	Printer B.O.
	,	,	KKF24C		,									
			1											
			1											
			:											
			Prepared by:					-						
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
			:					_						
			:											
			i					:						
			:											
			***											
			;											
			3											
			1											
			- 400											
			: - 2											
			!											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#4

	;					•
AREA NAME	1	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	1	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	82659

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS. WHICHEVER OCCURS FIRST.

SIMULATOR SOLUTION	
TEMP	
KKF24C  Prepared by:  Douglas C. Talbot  02-27-2012  Expires on:	REPAIRS/PROBLEM ERATOR I.D. NO. COMMENTS
RKF24C  Prepared by:  Douglas C. Talbot  02-27-2012  Expires on:	2 16071 Printer B.O.
Prepared by: Douglas C. Talbot 02-27-2012 Expires on:	
Prepared by: Douglas C. Talbot 02-27-2012 Expires on:	
Douglas C. Talbot 02-27-2012 Expires on:	
Douglas C. Talbot 02-27-2012 Expires on:	
02-27-2012 Expires on:	
Expires on:	

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).



AREA NAME
South Los Angeles

AREA NO.
COORDINATOR NAME
LD. NUMBER
PAS MAKE/MODEL
PAS SERIAL NO.
South Los Angeles

Intoximeters Inc./Alco-Sensor IV

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**		PAS TEMP (°C)			CURACY RESULTS*	REQ	RATION UIRED	PAS			
DATE	TIME	TEMP (°C)	= LOT NO.	VALÚE	4 1 2 22 22 1 2 2 2 2 2 2 2 2 2 2 2 2 2	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	ŅO	RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1414	34	12B27-13-5-10-	.100	36		.106			~		Valadez	16071	Printer B.O.
			KKF24C											
		ļ												
			-										_	
			Prepared by:							_			<u> </u>	
			Douglas C. Talbot											
			02-27-2012											
	_		Expires on:											
			02-27-2014											
			· ·					-						
			÷											
			1											
			1											
			:					-						
			I											
			-											
			:											
	-		ļ											
			:											
			<u> </u>											
			i											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#6

	CHP 202K	(Rev. 8-08)	OPI 051
--	----------	-------------	---------

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8580

The second secon			SIMULATOR SOLUTION (OR DRY GAS)**	NC			PAS ACCURACY CALIBRATION CHECK RESULTS* REQUIRED			PAS				
DATE	TIME	TEMP (°C)	LOT-NO:	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	1.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1344	34	12B27-13-5-10-	.100	20		.104			<b>×</b>		Valadez	16071	Printer B.O.
			KKF24C				•							
•			i											
			Prepared by:	,										
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
			1											
			:											
			i											
			:											
			1											
			;											
			1											
			- :											
		_	1											
			1		,									
_														
				,										

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

世フ

AREA NAME	LAREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
i e			F		02.02
South Los Angeles	530	Officer Brian Flick	15063	Interview store In a /Alaa Campan IV	$\bigvee$
South Los Angeles	1330	Officer Brian Flick	13003	Intoximeters Inc./Alco-Sensor IV	8 30 3 2

	ve en - Pre-		SIMULATOR SOLUTION (OR DRY GAS)**	NC			CHECK F	ESULTS*	CALIBRATION REQUIRED			Topic Services		
DATE	TIME	TEMP (°C)	ŁOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS		I.D: NO.	REPAIRS/PRUBLEMS/
10/31/2013	1336	34	12B27-13-5-10-	.100	20		:101			X		Valadez	16071	Printer B.O.
	_	ļ į	KKF24C											
			:											
			i											
										·				
*			Prepared by:											
			Douglas C. Talbot											
			02-27-2012							_				
			Expires on:											
	1		02-27-2014										•	
			; ;											
			1											
			1											
			•											
			:											
			j											
			:											
			3 3	•										
			1						·.					
								•						
			:											
			1											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy, checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8620

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS. WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**		PAS TEMP (°C)		CHECK RESULTS*		REQUIRÉD		and the second	To the control of the	erak eras d	
DATE	TIME	TEMP	LOT NO	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)		NO	PAS RETEST RESULTS	-OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1351	34	12B27-13-5-10-	.100	20		,/02			人		Valadez	16071	Printer B.O.
		,	KKF24C											
			1											
			:											
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012											
			Expires on:					_						
			02-27-2014											
			,											
			:											
			,											
			1											
			1											
			i											
			i											
			1											
			1											
			i											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#9

AREA NO. COORDINATOR NAME LD. NUMBER PAS MAKE/MODEL PAS SERIAL NO. South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV \$2.957

			SIMULATOR SOLUTIO (OR DRY GAS);**		TEMP (°C)		PAS AC CHECK I	<b>多为的特别的</b>	REQU	RATION JIRED	PAS			
DĂTE	TIME	TEMP (°C)	- LOT NO:	VALUE	*TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS
10/31/2013	1342	34	12B27-13-5-10-	.100	21		.099			×		Valadez	16071	Printer B.O.
		,	KKF24C											
			1											
			đ								_			
			Prepared by:											
		,	Douglas C. Talbot			_								
			02-27-2012											
_			Expires on:	_		_								
			02-27-2014											
					_									
													-	
			d e											
			i											
			3											
				_										
												_		
	_		:											
	_		ą.											
			ı	_										
			1											
	_													
			:											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#10

AREA NAME	AREA NO.	COORDINATOR NAME	LD. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	77505

			SIMULATOR SOLUTION (OR DRY GAS)**	ON .	P TEM	AS P (°C)	CHECK	RESULTS*	CALIBRATION REQUIRED				11 10 20 20 20 20	
DATE	TIME	TEMP	LOT NO	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1344	34	12B27-13-5-10-	.100	20		,/66			X		Valadez	16071	Printer B.O.
			KKF24C											
			i .											
			: .											
			Prepared by:											
			Douglas C. Talbot											
	•		02-27-2012											
			Expires on:							_				
			02-27-2014											
			:							_				
			1							_				
										_				
			:											
			,											
			t										_	
			1										_	
			1											
			1				_							
			1			_					`			
												_		
			1											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#11

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	77479

			SIMULATOR SOLUTION (OR DRY GAS)**	DN.	P -TEM	AS P'(°C)	CHECK	CURACY ESULTS*	REQU	RATION JIRED				
DATE	TIME	TEMP (°C)	EOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS COMMENTS
0/31/2013	1352	34	12B27-13-5-10-	.100	20		.098			X		Valadez	16071	Printer B.O.
			KKF24C											
			1											
			1 .							_			_	
			Prepared by:			_	-							
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
						_								
			1									-		
			•											
			1											
			3										· ·	
			i							_				
			3				_							-
										_	_			
			:											
												·		
	,		<u> </u>										,	
· <u>-</u>			i			•								
			: -											_

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#12

CHP 202K (Rev. 8-08) OPI 051

AREA NAME		AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	ŧ	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8 રુલ્૯0

			SIMULATOR SOLUTION (OR DRY GAS)**	NC	P TEMI	AS P. (°C)	PAS ACC	CURACY RESULTS*	CALIBI REQI	RATION UIRED				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1401	34	12B27-13-5-10-	.100	21		.699			×		Valadez	16071	Printer B.O.
			KKF24C											
-			1											
			:									_		
			Prepared by:				_					-		_
			Douglas C. Talbot			_							<del>  -</del>	
			02-27-2012	_						<del>-</del>				
			Expires on:											
			÷ 02-27-2014								_			
			; 0Z-Z7-Z014								-	_		
							<del>-</del>				_	_		
											_			
_								-						
			:				_				_			
-			· ·				-							
			•						_					
			:											
	,													
						_								
			1											
			1				_							
						_								
			1											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#13

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8709

		SIMULATOR SOLUTION (OR DRY GAS)**	ON.	PAS TEMP (°C)		PAS ACCURACY. CHECK RESULTS*		CALIBI REQU	RATION JIRED				
DATE	TEME TIME (°C)	EOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST #1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	<b>OPERATOR</b>	I.D. NO	REPAIRS/PROBLEMS
10/31/2013	1441 34	12B27-13-5-10-	.100	21		,102			义		Valadez	16071	Printer B.O.
		KKF24C		,									
		,										_	
		4											
		D 1 I											
		Prepared by:  Douglas C. Talbot											
		02-27-2012											
		Expires on:											
		02-27-2014											
		02 27 2011											
		1											
		1											
		1											
		1											
		:											
		•											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL

# PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG CHP 202K (Rev. 8-08) OPI 051

#14

		<u>_</u>	_		
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8714

i produce de la companya de la comp			SIMULATOR SOLUTION (OR DRY GAS)**	NC	TEMI		CHECK	CURACY RESULTS*	REQU	RATION' JIRED	200			
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST #1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1444	34	12B27-13-5-10-	.100	20		.105			X		Valadez	16071	Printer B.O.
			KKF24C											
			Prepared by:						_					
			Douglas C. Talbot											
			02-27-2012				,							
			Expires on:		_									
			02-27-2014										,	_
			1											
			,											
			1											
			1											
			-									-		
	_													
			:				_							
			1											
			i .											
			1											
			·											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#16

					<u> </u>
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8888

			SIMULATOR SOLUTION (OR DRY GAS)™	NC	P TEM	AS P.(°C)	CHECK	CURACY RESULTS*	REQ	RATION JIRED			English September 1	Page 1
DATE	TIME	TEMP (°C)	LOT NO:	VALUE	A	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD, NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1428	34	12B27-13-5-10-	.100	21		.102			广		Valadez	16071	Printer B.O.
		,	KKF24C											
			i											
			:											
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012		_									
			Expires on:											_
			02-27-2014											
			1											
			t											
			ì											
·														
								:						
														ن
			<u> </u>											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

\*\* If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#17

AREA NAME
South Los Angeles
AREA NO. COORDINATOR NAME
South Los Angeles
COORDINATOR NAME
LD. NUMBER
PAS MAKE/MODEL
Intoximeters Inc./Alco-Sensor IV
PAS SERIAL NO.
8783

			SIMULATOR SOLUTION (OR DRY GAS)**	ON		AS P (°C)	PAS ACC	ESULTS*	REQI	RATION JIRED				
DATE	TIME	TEMP (°C)	EOT NO.	VÄLUE		TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NØ	PAS RETEST RESULTS		LD. NO.	REPAIRS/PROBLEMS COMMENTS
0/31/2013	1441	34	12B27-13-5-10-	.100	19		£103			~		Valadez	16071	Printer B.O.
_		,	KKF24C											
			1						_	4		-		
_			i .					_						
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
			1											
									_					
			1											
			1											
			ė											
			ŧ											
			ı			_			_					
			1											
			ı											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#18

AREA NAME
South Los Angeles

AREA NO. COORDINATOR NAME
LD. NUMBER
PAS MAKE/MODEL
PAS SERIAL NO.

\$2457

			SIMULATOR SOLUTION (OR DRY GAS)**		TEM	AS ?(°C)	PAS AC CHECK F	RESULTS*	<b>电影的</b>	RATION JIRED	PAS			
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST	OPERATOR	LD. NO.	REPAIRS/PROBLEMS COMMENTS
0/31/2013	1436	34	12B27-13-5-10-	.100	20		,098			×		Valadez	16071	Printer B.O.
		,	KKF24C											
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012										_	
			Expires on:			_				_				
			02-27-2014							_				
	_													
_								_						
			,											
					_									
	_													,
			1											
			1											
			\$											
								. 1					_	
											,			

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#19

AREA NAME

AREA NO. COORDINATOR NAME

LD. NUMBER

PAS MAKE/MODEL

PAS SERIAL NO.

South Los Angeles

530 Officer Brian Flick

15063 Intoximeters Inc./Alco-Sensor IV

			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P_(°C)	CHECK	CURACY RESULTS*	CALIBI REQI	RATION JIRED				en interest de la company
-DATE	TIME	TEMP (°C)		VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	ØPERATOR.	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
10/31/2013	1444	34	12B27-13-5-10-	.100	19		,099			X		Valadez	16071	Printer B.O.
		•	KKF24C											
			Prepared by:	,										
		<del></del>	Douglas C. Talbot		,									
			02-27-2012						_					
			Expires on:											
			02-27-2014											
													-	
							· <u>-</u>							
				_									<del>  -</del>	
	_													
								_				_		
								_			<u> </u>		-	
									_				-	

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#20

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18684

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

	Tajor y Liberty (C.)	programme and the second	SIMULATOR SOLUTI (OR DRY GAS)**	ION PAS TEMP (°C)		PAS AC	CURACY RESULTS*	CALIBI REQU	RATION JIRED				Control ( ) Section ( ) Pro-	
DATE	TIME	TEMP (°C)	LOT NO	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
10/31/2013	1447	34	12B27-13-5-10-	.100	21		105			ブ		Valadez	16071	Printer B.O.
	, ( , ,		KKF24C											
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
														_
			,											
			·									,		
													4.11	

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#21

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8635

			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P (°C)	PAS AC CHECK I	CURACY RESULTS*	CALIBI REQI	RATION JIRED				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)		NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1501	34	12B27-13-5-10-	.100	26		. 10 1			7		Valadez	16071	Printer B.O.
			KKF24C										_	
							-							
			Prepared by:											
			Douglas C. Talbot					:						
			. 02-27-2012											
			Expires on:					-						
			02-27-2014											
						_				_				
			÷											
		_												_
			-											
													_	
							_				<u> </u>			-
			· ·											
					,									<del></del>
			ì											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

CHP 202K (Rev. 8-08) OPI 051		· · · · · · · · · · · · · · · · · · ·				22	
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.		
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8845		_

			SIMULATOR SOLUTION (OR DRY GAS)**	ЙĆ		AST P (°C)	CHECK	CURACY RESULTS*	REQ	RATION JIRED -				
DATE	TIME	TEMF (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
11/01/2013	1404	34	13B06-16-5-10-	.100	21		1060			X		Flick	15063	Printer B.O.
			KKF24C							/				
			Prepared by:											_
			Douglas C. Talbot											-
			02-06-2013				-							
			Expires on:	·										
			02-06-2015											
	_				•									
											_			
						_							_	
										_				
			t										_	
									_					
			·											
· ·														

If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#23

CHP 202k	(Rev.	8-08)	OPI	05
----------	-------	-------	-----	----

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	82653

All Sports and		SIMULATOR SOLUTION (OR DRY GAS)**		P TEMI	AS <sup>P.</sup> (°C)	CHECK	<b>设置的图像</b>	REQL	RATION JIRED	PAS		
DATE	TEMP	LOT NO:	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST#2 (Optional)	YES	NO	RETEST OPERATOR		REPAIRS/PROBLEMS COMMENTS
0/31/2013	1451 34	12B27-13-5-10-	.100	20		.098			ブ	Valadez	16071	Printer B.O.
		KKF24C										
		Prepared by:							•			
		Douglas C. Talbot										
		02-27-2012										
		Expires on:										
		02-27-2014										
			•									
		;										
		:			1							
		,										
										,		
		,										
-												

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8848

			SIMULATOR SOLUTION (OR DRY GAS)**	NC	P TEMI		CHECK	500 Cuther of the First	REQ	JIRED:				
DATE	TIME	TEMP (°C)	LOT NO:	VALUE	TEST#1	TEST#2 (Optional)	TEST#1	TEST #2 (Optional)	ÝES		PAS, RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1501	34	12B27-13-5-10-	.100	20		:104			人		Valadez	16071	Printer B.O.
		, ,	KKF24C				800,							
												-		
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
	3		, 02-27-2014											
÷														
			1	,										
			÷											
_								<del> </del>						
			-											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



AREA NO. COORDINATOR NAME I.D. NUMBER PAS MAKE/MODEL PAS SERIAL NO.
South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV 77591

			SIMULATOR SOLUTION (OR DRY GAS)**	ЭN		AS P (°C)	PAS AC CHECK F	CALIBRATION REQUIRED						
DATE	TIME	TEMP (°C)	LOT NO:	VAEUE	TEŞT#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I:D: NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1459	34	12B27-13-5-10-	.100	19		.103			X		Valadez	16071	Printer B.O.
			KKF24C											
-			Prepared by:						-					
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014					_						
							_							
							_							
					_									
			:				_							

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#26

CHP 202K (Rev. 8-08) OPI 051

AREA NAME  AREA NO. COORDINATOR NAME  South Los Angeles  AREA NO. COORDINATOR NAME  1.D. NUMBER  PAS MAKE/MODEL  PAS SERIAL NO.  SOUTH LOS Angeles  Intoximeters Inc./Alco-Sensor IV						
South Los Angeles 530 Officer Brian Flick 15063 Intoximeters Inc./Alco-Sensor IV	AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
	South Los Angeles	530	Officer Brian Flick	15063		8,820

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

		SIMULATOR SOLUTION (OR DRY GAS)**			AS CC)		CURACY RESULTS*	REQU	RATION JIRED	PAS			
DATE	TE TIME (°		VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1500 32	12B27-13-5-10-	.100	20		.103			$\rightarrow$		Valadez	16071	Printer B.O.
		KKF24C											
	-												
		4 .									_		
		Prepared by:											
		Douglas C. Talbot											
		02-27-2012											
		Expires on:											
,		02-27-2014											
										-			
			·										
		1	. 64				1-1						

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

STATE OF CALIFORNIA	
DEPARTMENT OF CALIFORNIA HIGHWAY PAT	RO

#2-

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	7 75 73

			SIMULATOR SOLUTION (OR DRY GAS)**	SIMULATOR SOLUTION (OR DRY GAS)**			-CHECK E	CURACY RESULTS*	REQU	RATION JIRED				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST #1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST OPERATOR	ED, NO.	REPAIRS/PROBLEMS COMMENTS	
0/31/2013	1459	34	12B27-13-5-10-	.100	21		.098			*		Valadez	16071	Printer B.O.
	,	·	KKF24C											
			1											
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012									-		-
			Expires on:											
			02-27-2014											
								_						
_			·									_		
			:											
	-													
	-		•											
-														
_														

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8305 1

REPAIRS/PROBLEMS/ COMMENTS inter B.O.
COMMENTS
inter B.O.
*

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

DEPARTMENT OF CALIFORNIA HIGHWAY PATROL

### PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG CHP 202K (Rev. 8-08) OPI 051

#30

		_			
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	8897

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**			PAS TEMP (°C)		CHECK RESULTS*		RATION UIRED	PAS			
DATÉ	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST#2 (Optional)	TEST#1	TEST#2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS. COMMENTS
10/31/2013	1513	34	12B27-13-5-10-	.100	20		106			×		Valadez	16071	Printer B.O.
		1	KKF24C			,								
			Prepared by:											
			Douglas C. Talbot						-				-	
			02-27-2012											
			Expires on:											
			02-27-2014											·
														<u> </u>
										_				
			;											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#31

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18624

	SIMULATOR SOLUTION PAS PAS ACC (OR DRY GAS)** TEMP (°C) CHECK RI				PAS ACCURACY CALIBRATION HECK RESULTS* REQUIRED								
DATE	TEM TIME (°C)	P LOTNO.	VALUE	TEST#1	TEST #2 (Optional)	TEST #1	TEST.#2 (Optional)	YES	NO	PAS RETEST RESULTS	A CARLON CO.	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013		12B27-13-5-10-	.100								Valadez	16071	Printer B.O.
		KKF24C											
					B	.0.							
		Prepared by:											
		Douglas C. Talbot											
		02-27-2012											
		Expires on:									-		
		02-27-2014											
													·
		-											
		i .											
		<u> </u>											
					_							-	

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#32

_					
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER :	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18646
•					

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)***		TEM	AS P.(°C)	CHECK	CURACY RESULTS*	REQU	RATION JIRED	Marine Control			
DATE	TIME	TEMP (°C)	EOT NO.	VALUE		TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	contain discussion and the second	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
10/31/2013	1569	34	12B27-13-5-10-	.100	21		.098			メ		Valadez	16071	Printer B.O.
		,	KKF24C											
					·							·		
			Prepared by:										-	
			Douglas C. Talbot											
			02-27-2012								···			
			Expires on:											
	,		02-27-2014											
			:											
			•											
			1											
			•											
-		·	*								•			

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#33

CHP 202K (Rev. 8-08)	OPI	051
----------------------	-----	-----

AREA NO. COORDINATOR NAME I.D. NUMBER PAS MARE/MODEL PAS SERIA		1	
South Los Angeles 520 Officer Prior Elists 15062 Interviewed the Alex Sensor IV	ME AREA NO. COORDINATOR NAME		2
oduli Los Angeles   15005   Infoximeters inc./Arco-sensor IV	Los Angeles 530 Officer Brian Flick	Intoximeters Inc./Alco-Sensor IV	5

			SIMULATOR SOLUTION (OR DRY GAS)**			AS P (°C)	CHECK	RESULTS*	CALIBI REQU	RATION JIRED	D PAS			
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST #1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	LD: NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1502	34	12B27-13-5-10-	.100	20		.102	i		<b>*</b>		Valadez	16071	Printer B.O.
			KKF24C											
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
				ı										
													<u> </u>	
			_											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#34

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	8077
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		0011

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS. WHICHEVER OCCURS FIRST.

	700 m		SIMULATOR SOLUTION (OR DRY GAS)**		PAS PAS ACCURACY CALIBRATION TEMP (°C) CHECK RESULTS* REQUIRED									
DATE	TIME	TEMP	LOT NO.	VALUE		TEST#2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS		LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1514	34	12B27-13-5-10-	.100	20		104			Х	, , , , , , , , , , , , , , , , , , , ,	Valadez	16071	Printer B.O.
	,	•	KKF24C				<del>;                                    </del>						*	
:	·		Prepared by:											
			Douglas C. Talbot			_								
			02-27-2012											
			Expires on:											
			02-27-2014											
	_													
									_			·		
								<u> </u>						
						_								

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#36

REA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	( as sel
outh Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		18612

			SIMULATOR SOLUTION (OR DRY GAS)**	ON.	ON PAS TEMP <sup>i</sup> (°C)		PAS AC CHECK F	CURACY RESULTS*	REQUIRED			E Programmen		
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST #1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS		LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1574	34	12B27-13-5-10-	.100	21		100	:		X		Valadez	16071	Printer B.O.
		,	KKF24C				•					_		
			3											
			Prepared by:											
			Douglas C. Talbot	1,										
			02-27-2012				1							
			Expires on:				I							
			02-27-2014											·
							İ							
							İ							
			_											
														_
-														
							i							
														·

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

**华37** 

AREA NAME
AREA NO. COORDINATOR NAME
LD. NUMBER
PAS MAKE/MODEL
PAS SERIAL NO.
South Los Angeles
530
Officer Brian Flick
15063
Intoximeters Inc./Alco-Sensor IV

			SIMULATOR SOLUTION (OR DRY GAS)**	ON Property 2	P TEMI	AS P(°C)	CHECK	RESULTS*		RATION JIRED			100000	
DATE	TIME	EMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1512 3	34	12B27-13-5-10-	.100	21		,/02			X		Valadez	16071	Printer B.O.
			KKF24C											
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012											
			Expires on:										_	
			02-27-2014											
											_			
								:						
								1						
			ŝ.											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#38

CHP 202K (Rev. 8-08) OPI 051

						-
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18676	

			SIMULATOR SOLUTION (OR DRY GAS)**	ON-	P TEM	AS P (°C)	PAS AC CHECK I	CURACY RESULTS*	REQ	JIRED	PAS			
DATE	πмε	TEMP (°C)	LOT NO:	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS		LD. NO.	REPAIRS/PROBLEMS/
10/31/2013		34	12B27-13-5-10-	.100	- 1000 ACT - 1000 ACT						AND THE CONTRACT OF THE	Valadez	16071	Printer B.O.
		1	KKF24C											
							5,0	<i>7</i> .						
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012					-						
	1		Expires on:											
			02-27-2014											
•														
														_
			1											
			<u>'</u>											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#39

<b>CHP 202K</b>	(Rev. 8-08	OPI 05
-----------------	------------	--------

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	83030

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**	ON		AS P (°C)	PAS AC CHECK F	CURACY ESULTS*	CALIBE REQL	RATION JIRED				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
0/31/2013	1512	34	12B27-13-5-10-	.100	21		,/61			×		Valadez	16071	Printer B.O.
			KKF24C						_					
								-						
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014		,									
							_							
													-	
							1							
				_										

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#40

CHP	202K	(Rev.	8-08)	OPI	05

AREA NAME
South Los Angeles
AREA NO.
COORDINATOR NAME
LD. NUMBER
PAS MAKEMODEL
Intoximeters Inc./Alco-Sensor IV
PAS SERIAL NO.
18692

TEM			SIMULATOR SOLUTION (OR DRY GAS)***	ON-		AS P. (°C)	PAS AC CHECK F	CURACY RESULTS*	CALIBI REQU	RATION JIRED				DEPAIRS/IDOM-EMS/
DATE	TIME	TEMP	LOTNO.	VALUE	TEST#1	TEST #2 (Optional)	TEST #1	TEST#2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS, COMMENTS
10/31/2013	1517	34	12B27-13-5-10-	.100	21		:100			×		Valadez	16071	Printer B.O.
			KKF24C											
			,											
										_				
			Prepared by:											
			Douglas C. Talbot											
	}		02-27-2012											
_			Expires on:							_				
			02-27-2014							_				
	_		_											
								-						
			_											
			1		_									
_														
_								:						
								<u> </u>						
	<u>-</u>													
													<u> </u>	
						_								
			_			_							_	
			_									-	_	
			_	_									_	

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#42

CHP 202K (Rev. 8-08) OPI 051

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18762

			SIMULATOR SOLUTION (OR DRY GAS)**	ON .	P TEM	AS P (°C)	PAS AC CHECK I	CURACY RESULTS*	CALIBI REQU	RATION JIRED				
DATÉ	TIME	TEMP (°C)	LOT-NO:	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST#2 (Optional)	YES	ÑO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1513	34	12B27-13-5-10-	.100	20		.101			X		Valadez	16071	Printer B.O.
			KKF24C											
										,				
			Prepared by:											
			Douglas C. Talbot		_									
			02-27-2012											
			Expires on:											
			02-27-2014											
						_								
	· <u>-</u>												_	
							<u> </u>							
													_	

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.



AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	18764	

### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS. WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTI (OR DRY GAS)**	NC		AS P (°C)	CHECK	CURACY RESULTS*	REQU	RATION JIRED				
DATE	TIME.	TEMF (°C)		VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1518	34	12B27-13-5-10-	.100	20		. 096			X		Valadez	16071	Printer B.O.
		1	KKF24C											
			Prepared by:											
			Douglas C. Talbot											·
			02-27-2012											
			Expires on:									સે		
			02-27-2014							_				
			_											
										_				
	·		_							_				
													1	
														_
						_								
							_							
				,			· _				_			
			_				_	_						

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).



AREA NAME

AREA NO. COORDINATOR NAME

LD. NUMBER

PAS MAKE/MODEL

PAS SERIAL NO.

[869]

South Los Angeles

530

Officer Brian Flick

15063

Intoximeters Inc./Alco-Sensor IV

			SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P.(°C)	CHECK	CURACY RESULTS*	REQU	RATION JIRED	PAS RETEST				
DATE	TIME	TEMP (°C)	LØT NO	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD. NO.	REPAIRS/PROBLEMS/	
10/31/2013	1524	34	12B27-13-5-10-	.100	21		.104			X		Valadez	16071	Printer B.O.	
		,	KKF24C												
		. :													
			Prepared by:								•				
			Douglas C. Talbot												
			02-27-2012												
			Expires on:											_	
			02-27-2014												
			32 2 7 2 3 2 7												
													_		
												_			
						-					_			_	

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#45

		_	_			
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	: 00
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		17990

TIME			SIMULATOR SOLUTION (OR DRY GAS)**	The state of the s	TEM	AS P (°C)	PAS AC CHECK I	RESULTS*	Carlo di Sanciale a	JIRED				REPAIRS/PROBLEMS/
DATE	TIME	TEMP (°C)	LOT NO	VALUE		TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	LD. NO:	REPAIRS/PROBLEMS
10/31/2013		12	2B27-13-5-10-	.100								Valadez	16071	Printer B.O.
		K	KF24C			3.	$\sim$							
						101	U,							
		D.												
		Pi	repared by:  Douglas C. Talbot											
			02-27-2012											
		E	xpires on:											
		1	02-27-2014											
			02-27-201-1										_	
		_												
										_				
								,						
								:						
												_		
											<u> </u>			

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA DEPARTMENT OF CALIFORNIA HIGHWAY PATROL

# PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG CHP 202K (Rev. 8-08) OPI 051

#46

						•	
AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.		_
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		18774	

		SIMULATOR SOLUTION (OR DRY GAS)**				AS P (°C)	CHECK	CURACY ESULTS*	REQU	RATION JIRED				
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1:	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	ED-NO.	REPAIRS/PROBLEM COMMENTS
0/31/2013	1521	34	12B27-13-5-10-	.100	21		./01			入		Valadez	16071	Printer B.O.
			KKF24C											
			Prepared by:					_						
			Douglas C. Talbot											
			02-27-2012			_							_	
			Expires on:											
			02-27-2014											
					_									
_							•						_	
											•			
						_				_				
			1											
									_					
	_				_									
										_		-		

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

\*\* If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#50

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
					. 1
South Los Angeles	530	Officer Prior Eliek	15063	Intoximeters Inc./Alco-Sensor IV	41486
South Los Angeles	2.30	Officer Brian Frick	13003	intoximeters inc./Alco-Sensor IV	1 10 4

			SIMULATOR SOLUTION (OR DRY GAS)**			AS P (°C)	PAS ACCURACY CALIBRATION CHECK RESULTS* REQUIRED				PAS			
DATE	TIME	TEMP (°C)	ŁOTNO.	VALUE	TEST#1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	Kirk Bar 4	RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1523	34	12B27-13-5-10-	.100	21		,106			X		Valadez	16071	Printer B.O.
			KKF24C											
			D 11											
			Prepared by:			-								
			Douglas C. Talbot											
	}		02-27-2012						_					
			Expires on: 02-27-2014						_					
			02-27-2014											
													1	
			:											

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#57

AREA NAME
AREA NO. COORDINATOR NAME
I.D. NUMBER
PAS MAKE/MODEL
PAS SERIAL NO.
15063
Intoximeters Inc./Alco-Sensor IV

			SIMULATOR SOLUTION (OR DRY GAS)**		P TEMI	AS P(°C)				RATION JIRED	PAS			
DATE	TIME	TEMP (°C)	LOT NO.	VALUE	TEST#1	TEST#2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS COMMENTS
10/31/2013	1519	34	12B27-13-5-10-	.100	20		.096			X		Valadez	16071	Printer B.O.
			KKF24C											
_			Prepared by:					-						
_			Douglas C. Talbot		_									
			02-27-2012							_				
			Expires on:									-		
			02-27-2014								-			
								:						
												-		
			,											
	_									_				

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

<sup>\*\*</sup> If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#52

AREA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV	41502

	etrapie s. J 1		SIMULATOR SOLUTION (OR DRY GAS)**	ON	P TEM	AS P (°C)	PAS AC CHECK F		REQ	RATION UIRED		and desired the second		
DATE	TIME	· Salestan	LOT NO.	VALUE	TEST #1	TEST #2 (Optional)	TEST#1	TEST #2 (Optional)	YES	NO	PAS RETEST RESULTS	OPERATOR	I.D. NO.	REPAIRS/PROBLEMS/ COMMENTS
10/31/2013	1525	34	12B27-13-5-10-	.100	ಎ೦		.101			X		Valadez	16071	Printer B.O.
			KKF24C											
				1										
					_									
-			Prepared by:						_				_	
			Douglas C. Talbot							_				
			02-27-2012		_			_						
			Expires on:					_						
			02-27-2014											
							_							
	_													
								_						
						_								_
	_					_								

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

#53

REA NAME	AREA NO.	COORDINATOR NAME	I.D. NUMBER	PAS MAKE/MODEL	PAS SERIAL NO.	0015U
South Los Angeles	530	Officer Brian Flick	15063	Intoximeters Inc./Alco-Sensor IV		82637

#### PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

			SIMULATOR SOLUTION (OR DRY GAS)**			PAS TEMP (°C)		PAS ACCURACY CHECK RESULTS*		CALIBRATION REQUIRED				
DATE	TIME	TEMP (°C)		VALUE		TEST#2		TEST #2 (Optional)		NO	PAS RETEST RESULTS		1.D. NO.	REPAIRS/PROBLEMS/. COMMENTS
10/31/2013	1522	34	12B27-13-5-10-	.100	عا	87.127	-097		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Х	Angel - Mage & Security Angel - in 1, 1, 1, 1, 1, 1	Valadez	16071	Printer B.O.
			KKF24C					:						
			Prepared by:											
			Douglas C. Talbot											
			02-27-2012											
			Expires on:											
			02-27-2014											
														_
											_			0
													7	
												_		
								_						

<sup>\*</sup> If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).