

CHP SLA Calibration Log

| Unit Serial Number | Cal Date | Cal Time | Cal Standard | Check Date | Check Time | Check Standard | Check Result | UOM |
|--------------------|------------|----------|--------------|------------|------------|----------------|--------------|-----|
| 16040119 | 03/28/2019 | 3:25 PM | 0.1 | 08/06/2020 | 1:58 PM | 0.1 | 0.097 | |
| 16040140 | 04/12/2019 | 7:46 AM | 0.1 | 08/06/2020 | 1:55 PM | 0.1 | 0.096 | |
| 16040141 | 04/03/2020 | 2:17 PM | 0.1 | 08/06/2020 | 1:56 PM | 0.1 | 0.103 | |
| 16040161 | 02/03/2020 | 1:45 PM | 0.1 | 08/06/2020 | 2:03 PM | 0.1 | 0.098 | |
| 16040162 | 02/03/2020 | 3:25 PM | 0.1 | 08/06/2020 | 1:51 PM | 0.1 | 0.099 | |
| 16080013 | 02/03/2020 | 3:33 PM | 0.1 | 08/06/2020 | 2:04 PM | 0.1 | 0.112 | |
| 16080013 | 08/06/2020 | 2:05 PM | 0.1 | 08/06/2020 | 2:06 PM | 0.1 | 0.1 | |
| 16080014 | 07/05/2019 | 11:51 AM | 0.1 | 08/06/2020 | 2:06 PM | 0.1 | 0.098 | |
| 16080015 | 02/03/2020 | 3:44 PM | 0.1 | 08/06/2020 | 2:06 PM | 0.1 | 0.099 | |
| 16080027 | 02/24/2020 | 10:16 AM | 0.1 | 08/06/2020 | 2:10 PM | 0.1 | 0.095 | |
| 16080028 | 03/28/2019 | 4:05 PM | 0.1 | 08/06/2020 | 2:13 PM | 0.1 | 0.1 | |
| 16080030 | 03/28/2019 | 4:07 PM | 0.1 | 08/06/2020 | 2:14 PM | 0.1 | 0.095 | |
| 16080064 | 03/28/2019 | 4:12 PM | 0.1 | 08/06/2020 | 2:15 PM | 0.1 | 0.101 | |
| 16080065 | 03/05/2020 | 2:33 PM | 0.1 | 08/06/2020 | 2:18 PM | 0.1 | 0.105 | |
| 16080069 | 03/28/2019 | 4:18 PM | 0.1 | 08/06/2020 | 2:22 PM | 0.1 | 0.098 | |
| 16080071 | 08/14/2017 | 10:41 AM | 0.1 | 08/06/2020 | 2:21 PM | 0.1 | 0.098 | |
| 16080072 | 12/19/2017 | 2:05 PM | 0.1 | 08/06/2020 | 2:26 PM | 0.1 | 0.101 | |
| 16080075 | 03/28/2019 | 4:24 PM | 0.1 | 08/06/2020 | 2:28 PM | 0.1 | 0.1 | |
| 16080077 | 02/24/2020 | 10:51 AM | 0.1 | 08/06/2020 | 2:29 PM | 0.1 | 0.107 | |
| 16120175 | 03/28/2019 | 4:36 PM | 0.1 | 08/06/2020 | 2:29 PM | 0.1 | 0.103 | |
| 16120177 | 04/25/2017 | 9:50 AM | 0.1 | 08/06/2020 | 2:34 PM | 0.1 | 0.102 | |
| 16120188 | 03/05/2020 | 3:12 PM | 0.1 | 08/06/2020 | 2:35 PM | 0.1 | 0.111 | |
| 16120188 | 08/06/2020 | 2:36 PM | 0.1 | 08/06/2020 | 2:37 PM | 0.1 | 0.099 | |
| 16120189 | 04/12/2019 | 8:50 AM | 0.1 | 08/06/2020 | 2:39 PM | 0.1 | 0.1 | |
| 16120194 | 08/15/2019 | 12:20 PM | 0.1 | 08/06/2020 | 2:39 PM | 0.1 | 0.095 | |
| 16120195 | 06/09/2019 | 12:48 PM | 0.1 | 08/06/2020 | 2:42 PM | 0.1 | 0.101 | |
| 17170064 | 03/28/2019 | 5:05 PM | 0.1 | 08/06/2020 | 2:51 PM | 0.1 | 0.101 | |
| 17170066 | 03/24/2020 | 1:46 PM | 0.1 | 08/06/2020 | 2:50 PM | 0.1 | 0.101 | |
| 17170155 | 03/28/2019 | 4:46 PM | 0.1 | 08/06/2020 | 2:50 PM | 0.1 | 0.1 | |

CHP SLA PAS Usage Log

| Test Number | Result | ID | Test Time | Test Date | Cal Time | Cal Date | Check Result | Check Time | Check Date | Unit Serial Number |
|-------------|--------|----|-----------|------------|----------|------------|--------------|------------|------------|--------------------|
| 160 | 0.22 | | 7:47 PM | 07/30/2020 | 3:25 PM | 03/28/2019 | 0.097 | 2:08 PM | 07/27/2020 | 16040119 |
| 161 | 0.216 | | 7:50 PM | 07/30/2020 | 3:25 PM | 03/28/2019 | 0.097 | 2:08 PM | 07/27/2020 | 16040119 |
| 162 | 0.053 | | 4:58 PM | 08/01/2020 | 3:25 PM | 03/28/2019 | 0.097 | 2:08 PM | 07/27/2020 | 16040119 |
| 163 | 0.052 | | 5:01 PM | 08/01/2020 | 3:25 PM | 03/28/2019 | 0.097 | 2:08 PM | 07/27/2020 | 16040119 |
| 142 | 0.18 | | 12:46 AM | 08/02/2020 | 2:17 PM | 04/03/2020 | 0.101 | 2:09 PM | 07/27/2020 | 16040141 |
| 143 | 0.193 | | 12:49 AM | 08/02/2020 | 2:17 PM | 04/03/2020 | 0.101 | 2:09 PM | 07/27/2020 | 16040141 |
| 484 | 0.164 | | 8:41 PM | 07/31/2020 | 3:25 PM | 02/03/2020 | 0.102 | 2:01 PM | 07/27/2020 | 16040162 |
| 485 | 0.158 | | 8:42 PM | 07/31/2020 | 3:25 PM | 02/03/2020 | 0.102 | 2:01 PM | 07/27/2020 | 16040162 |
| 198 | 0.165 | | 9:59 PM | 08/01/2020 | 3:33 PM | 02/03/2020 | 0.101 | 2:22 PM | 07/27/2020 | 16080013 |
| 199 | 0.175 | | 10:02 PM | 08/01/2020 | 3:33 PM | 02/03/2020 | 0.101 | 2:22 PM | 07/27/2020 | 16080013 |
| 200 | 0.152 | | 1:13 AM | 08/02/2020 | 3:33 PM | 02/03/2020 | 0.101 | 2:22 PM | 07/27/2020 | 16080013 |
| 201 | 0.153 | | 1:17 AM | 08/02/2020 | 3:33 PM | 02/03/2020 | 0.101 | 2:22 PM | 07/27/2020 | 16080013 |
| 133 | 0 | | 11:50 PM | 07/31/2020 | 3:44 PM | 02/03/2020 | 0.098 | 2:24 PM | 07/27/2020 | 16080015 |
| 134 | 0.073 | | 3:17 AM | 08/01/2020 | 3:44 PM | 02/03/2020 | 0.098 | 2:24 PM | 07/27/2020 | 16080015 |
| 135 | 0.074 | | 3:20 AM | 08/01/2020 | 3:44 PM | 02/03/2020 | 0.098 | 2:24 PM | 07/27/2020 | 16080015 |
| 136 | 0.15 | | 5:27 AM | 08/01/2020 | 3:44 PM | 02/03/2020 | 0.098 | 2:24 PM | 07/27/2020 | 16080015 |
| 137 | 0.141 | | 5:30 AM | 08/01/2020 | 3:44 PM | 02/03/2020 | 0.098 | 2:24 PM | 07/27/2020 | 16080015 |
| 138 | 0.104 | | 2:39 AM | 08/02/2020 | 3:44 PM | 02/03/2020 | 0.098 | 2:24 PM | 07/27/2020 | 16080015 |
| 139 | 0.102 | | 2:42 AM | 08/02/2020 | 3:44 PM | 02/03/2020 | 0.098 | 2:24 PM | 07/27/2020 | 16080015 |
| 140 | 0.055 | | 4:34 AM | 08/02/2020 | 3:44 PM | 02/03/2020 | 0.098 | 2:24 PM | 07/27/2020 | 16080015 |
| 141 | 0.054 | | 4:37 AM | 08/02/2020 | 3:44 PM | 02/03/2020 | 0.098 | 2:24 PM | 07/27/2020 | 16080015 |
| 197 | 0.021 | | 11:39 PM | 07/30/2020 | 4:18 PM | 03/28/2019 | 0.093 | 3:01 PM | 07/27/2020 | 16080069 |
| 198 | 0.019 | | 11:40 PM | 07/30/2020 | 4:18 PM | 03/28/2019 | 0.093 | 3:01 PM | 07/27/2020 | 16080069 |
| 525 | 0.236 | | 2:09 AM | 08/01/2020 | 10:41 AM | 08/14/2017 | 0.094 | 3:02 PM | 07/27/2020 | 16080071 |
| 526 | 0.237 | | 2:12 AM | 08/01/2020 | 10:41 AM | 08/14/2017 | 0.094 | 3:02 PM | 07/27/2020 | 16080071 |
| 527 | 0.138 | | 2:36 PM | 08/02/2020 | 10:41 AM | 08/14/2017 | 0.094 | 3:02 PM | 07/27/2020 | 16080071 |
| 528 | 0.142 | | 2:38 PM | 08/02/2020 | 10:41 AM | 08/14/2017 | 0.094 | 3:02 PM | 07/27/2020 | 16080071 |
| 56 | 0.158 | | 1:46 AM | 08/02/2020 | 4:24 PM | 03/28/2019 | 0.096 | 3:13 PM | 07/27/2020 | 16080075 |
| 57 | 0.149 | | 1:49 AM | 08/02/2020 | 4:24 PM | 03/28/2019 | 0.096 | 3:13 PM | 07/27/2020 | 16080075 |
| 231 | 0.137 | | 12:10 AM | 08/01/2020 | 9:50 AM | 04/25/2017 | 0.1 | 3:18 PM | 07/27/2020 | 16120177 |
| 232 | 0.136 | | 12:12 AM | 08/01/2020 | 9:50 AM | 04/25/2017 | 0.1 | 3:18 PM | 07/27/2020 | 16120177 |
| 178 | 0 | | 9:32 PM | 07/28/2020 | 3:12 PM | 03/05/2020 | 0.107 | 3:18 PM | 07/27/2020 | 16120188 |
| 453 | 0 | | 1:44 AM | 08/02/2020 | 12:48 PM | 06/09/2019 | 0.097 | 3:24 PM | 07/27/2020 | 16120195 |

CHP SLA PAS Usage Log

| Test Number | Result | ID | Test Time | Test Date | Cal Time | Cal Date | Check Result | Check Time | Check Date | Unit Serial Number |
|-------------|--------|----|-----------|------------|----------|------------|--------------|------------|------------|--------------------|
| 454 | 0.255 | | 2:56 AM | 08/02/2020 | 12:48 PM | 06/09/2019 | 0.097 | 3:24 PM | 07/27/2020 | 16120195 |
| 455 | 0.235 | | 2:59 AM | 08/02/2020 | 12:48 PM | 06/09/2019 | 0.097 | 3:24 PM | 07/27/2020 | 16120195 |
| 456 | 0.181 | | 11:53 AM | 08/04/2020 | 12:48 PM | 06/09/2019 | 0.097 | 3:24 PM | 07/27/2020 | 16120195 |
| 457 | 0.186 | | 11:55 AM | 08/04/2020 | 12:48 PM | 06/09/2019 | 0.097 | 3:24 PM | 07/27/2020 | 16120195 |

#1

| | | | | | |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|-----------------------------------|
| AREA NAME South Los Angeles | AREA NO. 530 | COORDINATOR NAME Edward McElroy | I.D. NUMBER 16193 | PAS MAKE/MODEL Lifelog FC20 | PAS SERIAL NO. <i>16040162</i> |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|-----------------------------------|

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|-------------|--------------------------------------|-----------|-----------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | <i>1350</i> | <i>34</i> | 191P41102 | .100 | <i>22</i> | <i>099</i> | | | | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OPI 051

#2

AREA NAME: South Los Angeles
 AREA NO.: 530
 COORDINATOR NAME: Edward McElroy
 I.D. NUMBER: 16193
 PAS MAKE/MODEL: Lifeloc FC20
 PAS SERIAL NO.: 16040119

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/COMMENTS |
|------------|------|-----------------------------------|-----------|-------|---------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|-----------|----------|---------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 1557 | 34 | 19IP41102 | .100 | 23 | | .097 | | | | | M. Tippet | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

Destroy Previous Editions

Chp202K_1108.pdf

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OPI 051

#3

| | | | | | |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|----------------------------|
| AREA NAME South Los Angeles | AREA NO. 530 | COORDINATOR NAME Edward McElroy | I.D. NUMBER 16193 | PAS MAKE/MODEL Lifeloc FC20 | PAS SERIAL NO. 16040140 |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|----------------------------|

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|-----------|-------|-----------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 1354 | 34 | 19IP41102 | .100 | 23 | | 096 | | | | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (\pm) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g. with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#4

| | | | | | |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|-----------------------------------|
| AREA NAME South Los Angeles | AREA NO. 530 | COORDINATOR NAME Edward McElroy | I.D. NUMBER 16193 | PAS MAKE/MODEL Lifeloc FC20 | PAS SERIAL NO. <i>16040141</i> |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|-----------------------------------|

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|-------------|--------------------------------------|-----------|------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|----------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | TEMP #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | <i>1352</i> | <i>34</i> | 19IP41102 | | | <i>22</i> | | <i>103</i> | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
CHP 202K (Rev. 8-08) OP1 051

#5

| | | | | | |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|-----------------------------------|
| AREA NAME South Los Angeles | AREA NO. 530 | COORDINATOR NAME Edward McElroy | I.D. NUMBER 16193 | PAS MAKE/MODEL Lifeloc FC20 | PAS SERIAL NO. <i>16040161</i> |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|-----------------------------------|

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|-------------|--------------------------------------|-----------|-------|------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | <i>1403</i> | <i>34</i> | 19IP41102 | .100 | <i>22</i> | | <i>098</i> | | | | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.
Destroy Previous Editions
Chp202K_1108.pdf

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OPI 051

#6

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: Edward MCElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifeloc FC20 PAS SERIAL NO.: *16040163*

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/COMMENTS |
|------------|------|-----------------------------------|-----------|---------------|--------------------|---------|-----------------------------|--------------------|----------------------|----|--------------------|------------|----------|---------------------------|
| | | TEMP (°C) | LOT NO. | TEMP #1 | TEST #1 (Optional) | TEST #2 | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | | | 191P41102 | | .100 | | | | | | | M. Tippett | 20137 | <i>OUT OF SERVICE</i> |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.
 Destroy Previous Editions
 Chp202k_1108.pdf

#7

| | | | | | |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|-----------------------------------|
| AREA NAME South Los Angeles | AREA NO. 530 | COORDINATOR NAME Edward McElroy | I.D. NUMBER 16193 | PAS MAKE/MODEL Lifeloc FC20 | PAS SERIAL NO. <i>16080013</i> |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|-----------------------------------|

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | TEMP (°C) | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|-------------|--------------|--------------------------------------|--|-------|---------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|-----------|----------|-------------------------------|
| | | | LOT NO. | | | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | <i>1404</i> | <i>34</i> | 19IP41102 | | .100 | <i>22</i> | | <i>.112</i> | | <i>X</i> | | <i>100</i> | M. Tippet | 20137 | |
| | | | | | | | | | | | | | | | |
| | | | Solution prepared by: | | | | | | | | | | | | |
| | | | Cesar Munoz | | | | | | | | | | | | |
| | | | Date: 09-17-19 | | | | | | | | | | | | |
| | | | Expiration date: | | | | | | | | | | | | |
| | | | 09-17-21 | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OPI 051

#8

| | | | | | |
|-------------------|----------|------------------|-------------|----------------|----------------|
| AREA NAME | AREA NO. | COORDINATOR NAME | I.D. NUMBER | PAS MAKE/MODEL | PAS SERIAL NO. |
| South Los Angeles | 530 | Edward McElroy | 16193 | Lifefloc FC20 | 16080014 |

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | TEMP (°C) | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/COMMENTS |
|------------|--------|-----------|-----------------------------------|---------|-------|--------------------|--------------------|-----------------------------|-----|----------------------|---|--------------------|------------|----------|---------------------------|
| | | | LOT NO. | TEST #1 | | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | | |
| 08/06/2020 | 140634 | | 19JP41102 | | .100 | 23 | | .098 | | | X | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

Destroy Previous Editions

Chp202K_1108.pdf

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OPI 051

#9

AREA NAME: South Los Angeles
 AREA NO.: 530
 COORDINATOR NAME: Edward McElroy
 I.D. NUMBER: 16193
 PAS MAKE/MODEL: Lifeloc FC20
 PAS SERIAL NO.: 16080015

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|-----------|-------|-----------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|-----------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 1405 | 34 | 19IP41102 | .100 | 22 | | .099 | | | X | | M. Tippet | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (\pm) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OP1 051

| | | | | | |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|----------------------------|
| AREA NAME South Los Angeles | AREA NO. 530 | COORDINATOR NAME Edward McElroy | I.D. NUMBER 16193 | PAS MAKE/MODEL Lifeloc FC20 | PAS SERIAL NO. 16680027 |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|----------------------------|

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|-----------|---------------|-----------------------|-----------------------|--------------------------------|-----|-------------------------|--|--------------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | | |
| 08/06/2020 | 1410 | 34 | 19IP41102 | .100 | 2.3 | | .095 | | | | X | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (\pm) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

4/10

#11

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: Edward McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifeloc FC20 PAS SERIAL NO.: 16080028

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|----------|-------|-----------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 1413 | 34 | 19P41102 | .100 | 22 | | .100 | | | | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#12

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: Edward McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifefoc FC20 PAS SERIAL NO.: 16080030

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | TEMP (°C) | LOT NO. | VALUE | TEST #1 | TEST #2 (Optional) | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|-----------------------------------|------|-----------|-----------|-------|---------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|-----------|----------|----------------------------|
| | | | | | | | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 1414 | 34 | 19IP41102 | .100 | 22 | | 095 | | | X | | M. Tippet | 20137 | |
| Solution prepared by: Cesar Munoz | | | | | | | | | | | | | | |
| Date: 09-17-19 | | | | | | | | | | | | | | |
| Expiration date: 09-17-21 | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OPI 051

#13

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: Edward McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifeloc FC20 PAS SERIAL NO.: 16080064

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS | |
|------------|--------|--------------------------------------|---------|---------------|-----------------------|--------------------------------|-----------------------|-------------------------|-----|--------------------------|----------|------------|-------------------------------|----|
| | | TEMP (°C) | LOT NO. | VALUE | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | | | | | NO |
| 08/06/2020 | 141534 | 191P41102 | | .100 | 22 | | 101 | | | X | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (\pm) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OPI 051

AREA NAME: South Los Angeles
 AREA NO.: 530
 COORDINATOR NAME: Edward McElroy
 I.D. NUMBER: 16193
 PAS MAKE/MODEL: Lifeloc FC20
 PAS SERIAL NO.: 76080065

#14

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/COMMENTS |
|------------|------|-----------------------------------|-----------|-------|---------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|------------|----------|---------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 1418 | 34 | 19IP41102 | .100 | 22 | | 105 | | | X | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.
 Destroy Previous Editions
 Cnp202k_1108.pdf

15

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: Edward McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifenloc FC20 PAS SERIAL NO.: 16080069

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | TEMP (°C) | LOT NO. | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/COMMENTS |
|------------|--------|-----------|-----------|-------|---------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|------------|----------|---------------------------|
| | | | | | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 142134 | 19.1 | 191P41102 | .100 | 23 | | 098 | | | | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
CHP 202K (Rev. 8-08) OPI 051

#16

| | | | | | |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|----------------------------|
| AREA NAME South Los Angeles | AREA NO. 530 | COORDINATOR NAME Edward McElroy | I.D. NUMBER 16193 | PAS MAKE/MODEL Lifeloc FC20 | PAS SERIAL NO. 16080071 |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|----------------------------|

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|--|------|--------------------------------------|-----------|-------|------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|-----------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| | | | | | | | | | | | | | | |
| 08/06/2020 | 1421 | 34 | 19IP41102 | .100 | 23 | | .098 | | | | | M. Tippet | 20137 | |
| Solution prepared by: Cesar Munoz Date: 09-17-19 Expiration date: 09-17-21 | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OP1 051

#17

AREA NAME: South Los Angeles | AREA NO.: 530 | COORDINATOR NAME: Edward McElroy | I.D. NUMBER: 16193 | PAS MAKE/MODEL: Lifeloc FC20 | PAS SERIAL NO.: 16080072

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | TEMP (°C) | LOT NO. | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|-----------|-----------|-------|--------------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|------------|----------|-------------------------------|
| | | | | | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 1426 | 39 | 19IP41102 | .100 | 22 | | 101 | | | | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.
 Destroy Previous Editions
 Chp202K_1108.pdf

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OP1 051

#18

AREA NAME: South Los Angeles
 AREA NO.: 530
 COORDINATOR NAME: Edward McElroy
 I.D. NUMBER: 16193
 PAS MAKE/MODEL: Lifeloc FC20
 PAS SERIAL NO.: 16880075

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | TEMP (°C) | LOT NO. | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/COMMENTS |
|------------|--------|-----------|----------|-------|--------------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|-----------|----------|---------------------------|
| | | | | | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 142834 | | 19P41102 | .100 | 22 | | 100 | | | | | M. Tippet | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (\pm) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#19

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: Edward McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifeloc FC20 PAS SERIAL NO.: 16080077

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|-----------|-------|-----------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 1429 | 34 | 19IP41102 | .100 | 23 | | 107 | | | | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#20

| | | | | | |
|-------------------|----------|------------------|-------------|----------------|----------------|
| AREA NAME | AREA NO. | COORDINATOR NAME | I.D. NUMBER | PAS MAKE/MODEL | PAS SERIAL NO. |
| South Los Angeles | 530 | Edward McElroy | 16193 | Lifeloc FC20 | 16120175 |

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/COMMENTS |
|------------|---------|-----------------------------------|---------|---------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|------------|----------|---------------------------|
| | | TEMP (°C) | LOT NO. | TEMP #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 1429 34 | 191P41102 | .100 | 22 | | 103 | | | X | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OPI 051

#21

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: Edward McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifeloc FC20 PAS SERIAL NO.: *16120177*

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|-------------|-----------------------------------|-----------|--------------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|------------|----------|----------------------------|
| | | TEMP (°C) | LOT NO. | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | <i>1433</i> | <i>34</i> | 191P41102 | | | | | | | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
CHP 202K (Rev. 8-08) OP1 051

22

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: Edward McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifeloc FC20 PAS SERIAL NO.: 16120188

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | TEMP (°C) | LOT NO. | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/COMMENTS |
|------------|------|--------------|-----------|-------|---------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|------------|----------|---------------------------|
| | | | | | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 1455 | 34 | 191P41102 | .100 | 23 | | .111 | | | | X | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (\pm) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OPI 051

#23

| | | | | | |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|-----------------------------------|
| AREA NAME South Los Angeles | AREA NO. 530 | COORDINATOR NAME Edward McElroy | I.D. NUMBER 16193 | PAS MAKE/MODEL Lifeloc FC20 | PAS SERIAL NO. <i>16120189</i> |
|--------------------------------|-----------------|------------------------------------|----------------------|--------------------------------|-----------------------------------|

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | TEMP (°C) | LOT NO. | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|-------------|--------------|-----------|-------|---------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|------------|----------|-------------------------------|
| | | | | | TEST #1 | TEST #2 (Optional) | TEST #1 | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | <i>1438</i> | <i>34</i> | 19IP41102 | .100 | <i>23</i> | | <i>100</i> | | | | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OPI 051

#24

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: Edward McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifefloc FC20 PAS SERIAL NO.: 16120194

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS | |
|------------|------|--------------------------------------|-----------|-------|-----------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|----------|-----------|-------------------------------|--|
| | | TEMP (°C) | LOT NO. | | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | | |
| 08/06/2020 | 1438 | 34 | 191P41102 | .100 | 22 | | | 095 | | | | | M. Tippet | 20137 | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#25

| | | | |
|--------------------------------|-----------------|------------------------------------|--------------------------------|
| AREA NAME South Los Angeles | AREA NO. 530 | COORDINATOR NAME Edward McElroy | I.D. NUMBER 16193 |
| | | | PAS MAKE/MODEL Lifeloc FC20 |
| | | | PAS SERIAL NO. 16120195 |

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|-----------|-------|--------------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 1441 | 34 | 191P41102 | .100 | 22 | | 101 | | | | X | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (\pm) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OPI 051

#26

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: Edward McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifeloc FC20 PAS SERIAL NO.: 16120197

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|---------|---------------|---------|--------------------------------|---------|-------------------------|-----|--------------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | VALUE | TEST #1 | TEST #2 (Optional) | TEST #1 | TEST #2 (Optional) | YES | | | | |
| 08/06/2020 | | 191P41102 | | .100 | | | | | | | M. Tippett | 20137 | OUT OF SERVICE |
| | | Solution prepared by: | | | | | | | | | | | |
| | | Cesar Munoz | | | | | | | | | | | |
| | | Date: 09-17-19 | | | | | | | | | | | |
| | | Expiration date: 09-17-21 | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#27

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: Edward McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifeloc FC20 PAS SERIAL NO.: *17170066*

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | TEMP (°C) | LOT NO. | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|-------------|--------------|-----------|-------|-----------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|------------|----------|-------------------------------|
| | | | | | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | <i>1449</i> | <i>34</i> | 19IP41102 | .100 | <i>22</i> | | <i>101</i> | | | | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

Destroy Previous Editions

Chp202k_1108.pdf

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OP1051

#28

AREA NAME: South Los Angeles | AREA NO.: 530 | COORDINATOR NAME: Edward McElroy | I.D. NUMBER: 16193 | PAS MAKE/MODEL: Lifetec FC20 | PAS SERIAL NO.: 17170150

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|--|-------|------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|-----------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | | | 19IP41102 | .100 | | | | | | | | M. Tippet | 20137 | OUT OF SERVICE |
| | | | Solution prepared by: Cesar Munoz Date: 09-17-19 Expiration date: 09-17-21 | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

Destroy Previous Editions

Chp202K_1108.pdf

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
CHP 202K (Rev. 8-08) OPI 051

#29

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: Edward McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifeloc FC20 PAS SERIAL NO.: 17170155

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|-----------|-------|------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 1450 | 34 | 191P41102 | .100 | 22 | | 100 | | | | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution. no calibration is required (e.g., with a 0.100 percent solution. an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks. note the canister serial number in the lot no. column. If needed. calibration shall be performed with a wet bath simulator.

#30

AREA NAME: South Los Angeles
 AREA NO.: 530
 COORDINATOR NAME: Edward McElroy
 I.D. NUMBER: 16193
 PAS MAKE/MODEL: Lifelog FC20
 PAS SERIAL NO.:

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | TEMP (°C) | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | TEST #1 | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/COMMENTS |
|------------|------|-----------|-----------------------------------|--------------------|-------|---------|--------------------|--------------------|-----------------------------|----|----------------------|--|--------------------|------------|----------|---------------------------|
| | | | LOT NO. | TEST #2 (Optional) | | | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | | | |
| 08/06/2020 | | | 191P41102 | | .100 | | | | | | | | | M. Tippett | 20137 | DEVICE IS OUT OF SERVICE |
| | | | Solution prepared by: | | | | | | | | | | | | | |
| | | | Cesar Munoz | | | | | | | | | | | | | |
| | | | Date: 09-17-19 | | | | | | | | | | | | | |
| | | | Expiration date: | | | | | | | | | | | | | |
| | | | 09-17-21 | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.
 Destroy Previous Editions
 Chp202k_1108.pdf

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
CHP 202K (Rev. 8-08) OPI 051

31

AREA NAME: South Los Angeles
AREA NO.: 530
COORDINATOR NAME: Edward McElroy
I.D. NUMBER: 16193
PAS MAKE/MODEL: Lifeloc FC20
PAS SERIAL NO.: 17170064

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|-----------|---------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | TEMP #1 | TEMP #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 08/06/2020 | 1450 | 34 | 19IP41102 | .100 | 22 | | 101 | | X | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

* If the reading is within plus or minus (\pm) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.