

CHP SIA PAS USAGE LOGS 3/11/21

| Test Number | Result | ID | Test Time | Test Date | Cal Time | Cal Date | Check Result | Check Time | Check Date | Unit Serial Number |
|-------------|--------|----|-----------|------------|----------|------------|--------------|------------|------------|--------------------|
| 243 | 0 | | 4:31 AM | 03/06/2021 | 3:25 PM | 03/28/2019 | 0.091 | 7:52 AM | 03/03/2021 | 16040119 |
| 244 | 0.211 | | 5:29 AM | 03/06/2021 | 3:25 PM | 03/28/2019 | 0.091 | 7:52 AM | 03/03/2021 | 16040119 |
| 245 | 0.198 | | 5:30 AM | 03/06/2021 | 3:25 PM | 03/28/2019 | 0.091 | 7:52 AM | 03/03/2021 | 16040119 |
| 246 | 0.258 | | 6:15 AM | 03/06/2021 | 3:25 PM | 03/28/2019 | 0.091 | 7:52 AM | 03/03/2021 | 16040119 |
| 247 | 0.246 | | 6:16 AM | 03/06/2021 | 3:25 PM | 03/28/2019 | 0.091 | 7:52 AM | 03/03/2021 | 16040119 |
| 248 | 0.169 | | 11:24 PM | 03/09/2021 | 3:25 PM | 03/28/2019 | 0.091 | 7:52 AM | 03/03/2021 | 16040119 |
| 249 | 0.164 | | 11:26 PM | 03/09/2021 | 3:25 PM | 03/28/2019 | 0.091 | 7:52 AM | 03/03/2021 | 16040119 |
| 243 | 0 | | 10:15 AM | 03/04/2021 | 7:46 AM | 04/12/2019 | 0.092 | 7:51 AM | 03/03/2021 | 16040140 |
| 244 | 0.21 | | 1:26 AM | 03/05/2021 | 7:46 AM | 04/12/2019 | 0.092 | 7:51 AM | 03/03/2021 | 16040140 |
| 245 | 0.208 | | 1:30 AM | 03/05/2021 | 7:46 AM | 04/12/2019 | 0.092 | 7:51 AM | 03/03/2021 | 16040140 |
| 246 | 0 | | 9:46 AM | 03/11/2021 | 7:46 AM | 04/12/2019 | 0.092 | 7:51 AM | 03/03/2021 | 16040140 |
| 247 | 0 | | 9:48 AM | 03/11/2021 | 7:46 AM | 04/12/2019 | 0.092 | 7:51 AM | 03/03/2021 | 16040140 |
| 188 | 0.175 | | 2:22 AM | 03/04/2021 | 2:17 PM | 04/03/2020 | 0.094 | 7:54 AM | 03/03/2021 | 16040141 |
| 189 | 0.154 | | 2:27 AM | 03/04/2021 | 2:17 PM | 04/03/2020 | 0.094 | 7:54 AM | 03/03/2021 | 16040141 |
| 190 | 0.15 | | 2:30 AM | 03/04/2021 | 2:17 PM | 04/03/2020 | 0.094 | 7:54 AM | 03/03/2021 | 16040141 |
| 191 | 0.169 | | 4:47 PM | 03/05/2021 | 2:17 PM | 04/03/2020 | 0.094 | 7:54 AM | 03/03/2021 | 16040141 |
| 192 | 0.158 | | 4:50 PM | 03/05/2021 | 2:17 PM | 04/03/2020 | 0.094 | 7:54 AM | 03/03/2021 | 16040141 |
| 256 | 0 | | 10:06 PM | 03/05/2021 | 8:07 AM | 03/03/2021 | 0.094 | 8:08 AM | 03/03/2021 | 16080013 |
| 257 | 0.185 | | 10:37 PM | 03/05/2021 | 8:07 AM | 03/03/2021 | 0.094 | 8:08 AM | 03/03/2021 | 16080013 |
| 258 | 0.186 | | 10:40 PM | 03/05/2021 | 8:07 AM | 03/03/2021 | 0.094 | 8:08 AM | 03/03/2021 | 16080013 |
| 213 | 0.135 | | 11:26 PM | 03/03/2021 | 7:17 AM | 01/13/2021 | 0.101 | 7:42 AM | 03/03/2021 | 16080027 |
| 214 | 0.131 | | 11:29 PM | 03/03/2021 | 7:17 AM | 01/13/2021 | 0.101 | 7:42 AM | 03/03/2021 | 16080027 |
| 215 | 0.144 | | 11:22 PM | 03/05/2021 | 7:17 AM | 01/13/2021 | 0.101 | 7:42 AM | 03/03/2021 | 16080027 |
| 216 | 0.144 | | 11:24 PM | 03/05/2021 | 7:17 AM | 01/13/2021 | 0.101 | 7:42 AM | 03/03/2021 | 16080027 |
| 217 | 0.147 | | 1:03 AM | 03/07/2021 | 7:17 AM | 01/13/2021 | 0.101 | 7:42 AM | 03/03/2021 | 16080027 |
| 218 | 0.155 | | 1:07 AM | 03/07/2021 | 7:17 AM | 01/13/2021 | 0.101 | 7:42 AM | 03/03/2021 | 16080027 |
| 137 | 0 | | 2:30 PM | 03/05/2021 | 8:37 AM | 01/13/2021 | 0.099 | 8:26 AM | 03/03/2021 | 16080030 |
| 138 | 0.044 | | 2:50 AM | 03/07/2021 | 8:37 AM | 01/13/2021 | 0.099 | 8:26 AM | 03/03/2021 | 16080030 |
| 139 | 0 | | 2:12 AM | 03/09/2021 | 8:37 AM | 01/13/2021 | 0.099 | 8:26 AM | 03/03/2021 | 16080030 |
| 393 | 0 | | 1:28 AM | 03/09/2021 | 2:33 PM | 03/05/2020 | 0.097 | 8:30 AM | 03/03/2021 | 16080065 |
| 394 | 0.246 | | 9:20 PM | 03/09/2021 | 2:33 PM | 03/05/2020 | 0.097 | 8:30 AM | 03/03/2021 | 16080065 |
| 395 | 0.235 | | 9:21 PM | 03/09/2021 | 2:33 PM | 03/05/2020 | 0.097 | 8:30 AM | 03/03/2021 | 16080065 |
| 396 | 0.207 | | 9:36 PM | 03/09/2021 | 2:33 PM | 03/05/2020 | 0.097 | 8:30 AM | 03/03/2021 | 16080065 |

CHP SLA PAS USAGE LOGS 3/11/21

| Test Number | Result | ID | Test Time | Test Date | Cal Time | Cal Date | Check Result | Check Time | Check Date | Unit Serial Number |
|-------------|--------|----|-----------|------------|----------|------------|--------------|------------|------------|--------------------|
| 397 | 0.223 | | 9:38 PM | 03/09/2021 | 2:33 PM | 03/05/2020 | 0.097 | 8:30 AM | 03/03/2021 | 16080065 |
| 249 | 0.25 | | 3:22 AM | 03/08/2021 | 6:19 AM | 01/22/2021 | 0.098 | 8:33 AM | 03/03/2021 | 16080069 |
| 250 | 0.235 | | 3:24 AM | 03/08/2021 | 6:19 AM | 01/22/2021 | 0.098 | 8:33 AM | 03/03/2021 | 16080069 |
| 251 | 0.079 | | 11:27 PM | 03/10/2021 | 6:19 AM | 01/22/2021 | 0.098 | 8:33 AM | 03/03/2021 | 16080069 |
| 252 | 0.076 | | 11:30 PM | 03/10/2021 | 6:19 AM | 01/22/2021 | 0.098 | 8:33 AM | 03/03/2021 | 16080069 |
| 112 | 0 | | 2:53 PM | 03/03/2021 | 2:05 PM | 12/19/2017 | 0.091 | 8:44 AM | 03/03/2021 | 16080072 |
| 113 | 0.161 | | 1:38 AM | 03/06/2021 | 2:05 PM | 12/19/2017 | 0.091 | 8:44 AM | 03/03/2021 | 16080072 |
| 114 | 0.152 | | 1:40 AM | 03/06/2021 | 2:05 PM | 12/19/2017 | 0.091 | 8:44 AM | 03/03/2021 | 16080072 |
| 72 | 0.195 | | 2:54 AM | 03/05/2021 | 4:24 PM | 03/28/2019 | 0.09 | 8:45 AM | 03/03/2021 | 16080075 |
| 73 | 0.202 | | 2:57 AM | 03/05/2021 | 4:24 PM | 03/28/2019 | 0.09 | 8:45 AM | 03/03/2021 | 16080075 |
| 74 | 0 | | 12:04 AM | 03/06/2021 | 4:24 PM | 03/28/2019 | 0.09 | 8:45 AM | 03/03/2021 | 16080075 |
| 75 | 0 | | 12:15 AM | 03/06/2021 | 4:24 PM | 03/28/2019 | 0.09 | 8:45 AM | 03/03/2021 | 16080075 |
| 76 | 0.082 | | 4:16 AM | 03/06/2021 | 4:24 PM | 03/28/2019 | 0.09 | 8:45 AM | 03/03/2021 | 16080075 |
| 77 | 0.082 | | 4:18 AM | 03/06/2021 | 4:24 PM | 03/28/2019 | 0.09 | 8:45 AM | 03/03/2021 | 16080075 |
| 212 | 0.155 | | 9:45 PM | 03/06/2021 | 4:36 PM | 03/28/2019 | 0.091 | 8:49 AM | 03/03/2021 | 16120175 |
| 213 | 0.153 | | 9:47 PM | 03/06/2021 | 4:36 PM | 03/28/2019 | 0.091 | 8:49 AM | 03/03/2021 | 16120175 |
| 288 | 0.119 | | 7:09 AM | 03/07/2021 | 9:50 AM | 04/25/2017 | 0.091 | 8:54 AM | 03/03/2021 | 16120177 |
| 289 | 0.12 | | 7:10 AM | 03/07/2021 | 9:50 AM | 04/25/2017 | 0.091 | 8:54 AM | 03/03/2021 | 16120177 |
| 290 | 0 | | 4:07 AM | 03/08/2021 | 9:50 AM | 04/25/2017 | 0.091 | 8:54 AM | 03/03/2021 | 16120177 |
| 234 | 0.184 | | 1:52 AM | 03/06/2021 | 8:50 AM | 04/12/2019 | 0.09 | 9:08 AM | 03/03/2021 | 16120189 |
| 235 | 0.182 | | 1:54 AM | 03/06/2021 | 8:50 AM | 04/12/2019 | 0.09 | 9:08 AM | 03/03/2021 | 16120189 |

#1

AREA NAME
 South Los Angeles

AREA NO.
 530

COORDINATOR NAME
 E. McElroy

ID. NUMBER
 16193

PAS MAKE/MODEL
 Lifefoc FC20

PAS SERIAL NO.
 16040162

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|-----------|------------------|-----------------------|--------------------------------|-----------------------|-------------------------|-----|--------------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | VALUE | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | | | | |
| 03/11/2021 | 1308 | 34 | 19IP41101 | .100 | 20 | .092 | | | X | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

* If the reading is within plus or minus (\pm) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g. with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
CHP 202K (Rev. 8-08) OPI 051

#2

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: E. McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifelog FC20 PAS SERIAL NO.: *16040119*

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/COMMENTS |
|------------|------|-----------------------------------|-----------|-------|---------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|------------|----------|---------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 03/11/2021 | 1437 | 34 | 19DP41101 | .100 | 22 | | | | | X | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OPI 051

#3

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: E. McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifeloc FC20 PAS SERIAL NO.: 16040140

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|-----------|------------------|-----------------------|--------------------------------|-----------------------|-------------------------|-----|--------------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | VALUE | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | | | | |
| 03/11/2021 | 1437 | 34 | 19IP41101 | .100 | 21 | | 091 | | | X | M. Tippett | 20137 | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

Destroy Previous Editions

Chp202k_1108.pdf

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
CHP 202K (Rev. 8-08) OPI 051

#4

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: E. McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifenoc FC20 PAS SERIAL NO.: 16040141

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|---------|--------------------------------------|-----------|-------|-----------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|-----------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | VALUE | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 03/11/2021 | 1314 34 | | 19IP41101 | .100 | 19 | | 0.095 | | | | | M. Tippet | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#5

AREA NAME: South Los Angeles
AREA NO.: 530
COORDINATOR NAME: E. McElroy
I.D. NUMBER: 16193
PAS MAKE/MODEL: Lifefoc FC20
PAS SERIAL NO.: 16040161

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/COMMENTS |
|------------|------|-----------------------------------|-----------|-------|---------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|-----------|----------|---------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 03/11/2021 | 1320 | 34 | 19DP41101 | .100 | 19 | | 093 | | | X | | M. Tippet | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g. with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OP1 051

#6

AREA NAME **South Los Angeles** AREA NO. **530** COORDINATOR NAME **E. McElroy** I.D. NUMBER **16193** PAS MAKE/MODEL **Lifeloc FC20** PAS SERIAL NO. **16040163**

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|---------|---------------|---------|-----------------------------|--------------------|----------------------|-----|--------------------|-----------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | VALUE | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | | | | |
| 03/11/2021 | | 19DP41101 | | .100 | | | | | | | M. Tippet | 20137 | OUT OF SERVICE |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
CHP 202K (Rev. 8-08) OP1 051 #7

AREA NAME: South Los Angeles
AREA NO.: 530
COORDINATOR NAME: E. McElroy
I.D. NUMBER: 16193
PAS MAKE/MODEL: Lifeloc FC20
PAS SERIAL NO.: 16080013

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|---------|--------------------------------------|---------|-------|---------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 03/11/2021 | 1721 34 | 19IP41101 | | .100 | 20 | | 1087 | | X | | 1102 | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#8

AREA NAME
South Los Angeles

AREA NO.
530

COORDINATOR NAME
E. McElroy

I.D. NUMBER
16193

PAS MAKE/MODEL
Lifelog FC20

PAS SERIAL NO.
16080014

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|---------|--------------------------------------|-----------|---------------|--------------------|-----------------------------|--------------------|----------------------|-----|--------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | VALUE | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | | | | |
| 03/11/2021 | 1:24:54 | | 19DP41101 | .100 | 21 | .096 | | | | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.
Destroy Previous Editions
CHP202K_1108.pdf

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
CHIP 202K (Rev. 8-08) OPI 051

#10

| | | | | | |
|--------------------------------|-----------------|--------------------------------|----------------------|--------------------------------|----------------------------|
| AREA NAME South Los Angeles | AREA NO. 530 | COORDINATOR NAME E. McElroy | I.D. NUMBER 16193 | PAS MAKE/MODEL Lifeloc FC20 | PAS SERIAL NO. 16080027 |
|--------------------------------|-----------------|--------------------------------|----------------------|--------------------------------|----------------------------|

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|---------|--------------------------------------|-----------|------------------|---------|--------------------------------|-----------------------|-------------------------|-----|--------------------------|-----------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | VALUE | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | | | | |
| 03/11/2021 | 1527 34 | | 19DP41101 | .100 | 20 | | 101 | | X | | M. Tippet | 20137 | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g. with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).

** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
CHP 202K (Rev. 8-08) OPI 051

#11

AREA NAME: South Los Angeles
AREA NO.: 530
COORDINATOR NAME: E. McElroy
I.D. NUMBER: 16193
PAS MAKE/MODEL: Lifeloc FC20
PAS SERIAL NO.: 16080028

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/COMMENTS |
|------------|------|-----------------------------------|-----------|---------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|-----------|----------|---------------------------|
| | | TEMP (°C) | LOT NO. | TEMP #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 03/11/2021 | 1330 | 74 | 19IP41101 | 20 | | 096 | | | X | | M. Tippet | 20137 | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#12

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: E. McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifeloc FC20 PAS SERIAL NO.: 16080030

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|-----------|---------------|---------|-----------------------------|--------------------|----------------------|-----|--------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | VALUE | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | | | | |
| 03/11/2021 | 1531 | 34 | 19DP41101 | .100 | 20 | | 102 | | X | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OPI 051

#13

AREA NAME: South Los Angeles | AREA NO.: 530 | COORDINATOR NAME: E. McElroy | I.D. NUMBER: 16193 | PAS MAKE/MODEL: Lifoloc FC20 | PAS SERIAL NO.: 16080064

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|-----------|------------------|--------------------------------|-----------------------|-------------------------|-----|--------------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | | VALUE | TEST #1 (Optional) | TEST #2 (Optional) | YES | | | | |
| 03/11/2021 | 1332 | 54 | 19IP41101 | .100 | 19 | Pass | | X | | M. Tippett | 20137 | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#14

AREA NAME
 South Los Angeles

AREA NO.
 530

COORDINATOR NAME
 E. McElroy

I.D. NUMBER
 16193

PAS MAKE/MODEL
 Lifeloc FC20

PAS SERIAL NO.
 16080065

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|-----------|-------|-----------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|-----------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 03/11/2021 | 1335 | 34 | 19JP41101 | .100 | 19 | | | 094 | | | X | M. Tippet | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 Percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.
 Destroy Previous Editions
 Chp202k_1108.pdf

#15

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: E. McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifeloc FC20 PAS SERIAL NO.: 16080069

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|-----------|-------|------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|-----------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | VALUE | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 03/11/2021 | 1334 | 34 | 19DP41101 | .100 | 19 | | .099 | | | X | | M. Tippet | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g. with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#16

| | | | | | |
|-------------------|----------|------------------|-------------|----------------|----------------|
| AREA NAME | AREA NO. | COORDINATOR NAME | I.D. NUMBER | PAS MAKE/MODEL | PAS SERIAL NO. |
| South Los Angeles | 530 | E. McElroy | 16193 | Lifefac FC20 | 16080671 |

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP #1 (°C) | TEST #2 (Optional) | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/COMMENTS |
|------------|------|-----------------------------------|-----------|-------|------------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|------------|----------|---------------------------|
| | | TEMP (°C) | LOT NO. | | | | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 03/11/2021 | 1341 | 34 | 19DP41101 | 100 | 19 | | 102 | | | X | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (\pm) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.
 Destroy Previous Editions
 CHP202K_1103.pdf

#18

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: E. McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifelog FC20 PAS SERIAL NO.: 16080075

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | TEMP (°C) | LOT NO. | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/COMMENTS |
|----------------------------|------|-----------|-----------|-------|---------------|--------------------|-----------------------------|--------------------|----------------------|----|--------------------|------------|----------|---------------------------|
| | | | | | TEST #1 | TEST #2 (Optional) | TEST #1 | TEST #2 (Optional) | YES | NO | | | | |
| 03/11/2021 | 1344 | 34 | 19DP41101 | .100 | 19 | | .092 | | | | X | M. Tippett | 20137 | |
| Solution prepared by: | | | | | | | | | | | | | | |
| Cesar Munoz | | | | | | | | | | | | | | |
| Date: 09-10-19 | | | | | | | | | | | | | | |
| Expiration date: 09-170-21 | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
 DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
 CHP 202K (Rev. 8-08) OPI 051

#22

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: E. McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifeloc FC20 PAS SERIAL NO.: 16120188

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|---------|--------------------------------------|-----------|-------|------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|------------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | VALUE | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | |
| 03/11/2021 | 1409 34 | | 19DP41101 | .100 | 22 | | 095 | | | X | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#24

| | | | | | |
|--------------------------------|-----------------|--------------------------------|----------------------|---------------------------------|----------------------------|
| AREA NAME South Los Angeles | AREA NO. 530 | COORDINATOR NAME E. McElroy | I.D. NUMBER 16193 | PAS MAKE/MODEL Lifefloc FC20 | PAS SERIAL NO. 16120194 |
|--------------------------------|-----------------|--------------------------------|----------------------|---------------------------------|----------------------------|

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS | |
|------------|------|--------------------------------------|-----------|---------------|---------|-----------------------------|--------------------|----------------------|-----|--------------------|----------|-----------|-------------------------------|----|
| | | TEMP (°C) | LOT NO. | VALUE | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | | | | | NO |
| 03/11/2021 | 1411 | 34 | 19DP41101 | .100 | 20 | .098 | | | | X | | M. Tippet | 20137 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

STATE OF CALIFORNIA
DEPARTMENT OF CALIFORNIA HIGHWAY PATROL
PRELIMINARY ALCOHOL SCREENING (PAS) DEVICE ACCURACY CHECK/CALIBRATION LOG
CHP 202K (Rev. 8-08) OPI 051

#25

| | | | | | |
|--------------------------------|-----------------|--------------------------------|---------------------|--------------------------------|----------------------------|
| AREA NAME South Los Angeles | AREA NO. 530 | COORDINATOR NAME E. McElroy | ID. NUMBER 16193 | PAS MAKE/MODEL Lifeloc FC20 | PAS SERIAL NO. 16120195 |
|--------------------------------|-----------------|--------------------------------|---------------------|--------------------------------|----------------------------|

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | VALUE | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | ID. NO. | REPAIRS/PROBLEMS/ COMMENTS | |
|------------|------|--------------------------------------|-----------|-------|------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|----------|------------|-------------------------------|--|
| | | TEMP (°C) | LOT NO. | | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | NO | | | | | |
| 03/11/2021 | 14/3 | 34 | 19IP41101 | .100 | 20 | | | | | | X | | M. Tippett | 20137 | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

Handwritten mark

AREA NAME: South Los Angeles AREA NO.: 530 COORDINATOR NAME: E. McElroy I.D. NUMBER: 16193 PAS MAKE/MODEL: Lifeloc FC20 PAS SERIAL NO.: 17170066

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | PAS TEMP (°C) | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS | |
|-----------------------------------|------|-----------------------------------|-----------|---------------|-----------------------------|---------|----------------------|--------------------|--------------------|----------|------------|----------------------------|--------------------|
| | | TEMP (°C) | LOT NO. | | VALUE | TEST #1 | TEST #2 (Optional) | TEST #1 (Optional) | | | | | TEST #2 (Optional) |
| 03/11/2021 | 1420 | 34 | 19IP41101 | .100 | 19 | | .095 | | | X | M. Tippett | 20137 | |
| | | | | | | | | | | | | | |
| Solution prepared by: Cesar Munoz | | | | | | | | | | | | | |
| Date: 09-10-19 | | | | | | | | | | | | | |
| Expiration date: 09-170-21 | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#30

AREA NAME: South Los Angeles | AREA NO.: 530 | COORDINATOR NAME: E. McElroy | I.D. NUMBER: 16193 | PAS MAKE/MODEL: Lifeloc FC20 | PAS SERIAL NO.: 90102844-82

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|------------|------|--------------------------------------|---------|-------|------------------|-----------------------|--------------------------------|-----------------------|-------------------------|----|--------------------------|----------|----------------|-------------------------------|
| | | TEMP (°C) | LOT NO. | VALUE | TEST #1 | TEST #2 (Optional) | TEST #1 | TEST #2 (Optional) | YES | NO | | | | |
| 03/11/2021 | | 19IP41101 | | .100 | | | | | | | M. Tippett | 20137 | OUT OF SERVICE | |
| | | Solution prepared by: | | | | | | | | | | | | |
| | | Cesar Munoz | | | | | | | | | | | | |
| | | Date: 09-10-19 | | | | | | | | | | | | |
| | | Expiration date: 09-170-21 | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.

#31

| | | | | | |
|--------------------------------|-----------------|--------------------------------|----------------------|--------------------------------|-----------------------------|
| AREA NAME South Los Angeles | AREA NO. 530 | COORDINATOR NAME E. McElroy | I.D. NUMBER 16193 | PAS MAKE/MODEL Lifeloc FC20 | PAS SERIAL NO. 171-70064 |
|--------------------------------|-----------------|--------------------------------|----------------------|--------------------------------|-----------------------------|

PAS DEVICES SHALL BE CHECKED FOR ACCURACY EVERY 10 DAYS OR EVERY 150 TESTS, WHICHEVER OCCURS FIRST.

| DATE | TIME | SIMULATOR SOLUTION (OR DRY GAS)** | | TEMP (°C) | PAS TEMP (°C) | | PAS ACCURACY CHECK RESULTS* | | CALIBRATION REQUIRED | | PAS RETEST RESULTS | OPERATOR | I.D. NO. | REPAIRS/PROBLEMS/ COMMENTS |
|---|------|--------------------------------------|-----------|-----------|------------------|-----------------------|--------------------------------|-----------------------|-------------------------|-----|--------------------------|----------|----------|-------------------------------|
| | | TEMP (°C) | LOT NO. | | VALUE | TEST #1 (Optional) | TEST #2 (Optional) | TEST #1 (Optional) | TEST #2 (Optional) | YES | | | | |
| 03/11/2021 | 1423 | 34 | 19IP41101 | .100 | 18 | | | | X | | M. Tippett | 20137 | | |
| Solution prepared by: Cesar Munoz Date: 09-10-19 Expiration date: 09-170-21 | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

* If the reading is within plus or minus (±) 0.010 percent of the actual value of the alcohol solution, no calibration is required (e.g., with a 0.100 percent solution, an acceptable range is 0.090 to 0.110).
 ** If using dry gas for accuracy checks, note the canister serial number in the lot no. column. If needed, calibration shall be performed with a wet bath simulator.
 Destroy Previous Editions
 CHP202K_1108.pdf